

# SR122A6R8DAR

### SR122A6R8DAR Information

Heisener.com	 SR122A6R8DAR AVX Corporation Capacitors Ceramic Capacitors CAP CER 6.8PF 200V NP0 RADIAL Radial For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## SR122A6R8DAR Specifications

ManufacturerAVX CorporationCategoryCapacitorsPackageRadialPackageSkyCap? SRCapacitance6.8pFTolerance9.0vVVoltage - RatedCOG, NPOOperating Temperature-5°C ~ 125°CFeatures-AphicationsGeneral PurposeAphications-Aphications-Faitures Rated-Aphications-Aphications-Aphications-Faiture Rate-Faiture		
CapacitorsPackageRadialSeriesSkyCap? SRCapacitance6.8pFTolerance±0.5pFVoltage - RatedC00 VOperating Temperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CPattings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSiz / Dimension0.10° (2.54mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.20° (5.08mm)Lead StyleFormed Leads	Manufacturer Part Number	SR122A6R8DAR
Ceramic CapacitorsPackageRadialSeriesSkyCap? SRCapacitance6.8pFTolerance±0.5pFVoltage - Rated200VTemperature CoefficientCOG, NP0Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.100° (2.54mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing6.200° (5.08mm)Lead StyleFormed Leads	Manufacturer	AVX Corporation
PackageRadialSeriesSkyCap? SRCapacitance6.8pFTolerance±0.5pFVoltage - Rated200VTemperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HoleSize / Dimension0.150° L x 0.150° W (3.81mm x 3.81mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.200° (5.08mm)Lead StyleFormed Leads	Category	Capacitors
Series   SkyCap? SR     Capacitance   6.8pF     Tolerance   ±0.5pF     Voltage - Rated   200V     Temperature Coefficient   COG, NPO     Operating Temperature   -55°C ~ 125°C     Features   -     Ratings   -     Applications   General Purpose     Failure Rate   -     Noutring Type   Through Hole     Size / Dimension   0.150" L x 0.150" W (3.81mm x 3.81mm)     Height - Seated (Max)   -     Thickness (Max)   -     Lead Spacing   0.200" (5.08mm)     Lead Style   Formed Leads		Ceramic Capacitors
Capacitance6.8pFTolerance±0.5pFVoltage - Rated200VTemperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.100" (2.54mm)Height - Seated (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads	Package	Radial
Tolerance±0.5pFVoltage - Rated200VTemperature CoefficientCOG, NP0Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.150° L x 0.150° W (3.81mm x 3.81mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.200° (5.08mm)Lead StyleFormed Leads	Series	SkyCap? SR
Voltage - Rated200VTemperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.100" (2.54mm) (3.81mm x 3.81mm)Height - Seated (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads	Capacitance	6.8pF
Temperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.100" (2.54mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads	Tolerance	±0.5pF
Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.150" L x 0.150" W (3.81mm x 3.81mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads	Voltage - Rated	200V
Features-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.150" L x 0.150" W (3.81mm x 3.81mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads	Temperature Coefficient	C0G, NP0
Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.150" L x 0.150" W (3.81mm x 3.81mm)Height - Seated (Max)0.100" (2.54mm)Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads	Operating Temperature	-55°C ~ 125°C
ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.150" L x 0.150" W (3.81mm x 3.81mm)Height - Seated (Max)0.100" (2.54mm)Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads	Features	-
Failure Rate-Failure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.150" L x 0.150" W (3.81mm x 3.81mm)Height - Seated (Max)0.100" (2.54mm)Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads	Ratings	-
Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.150" L x 0.150" W (3.81mm x 3.81mm)Height - Seated (Max)0.100" (2.54mm)Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads	Applications	General Purpose
Package / CaseRadialSize / Dimension0.150" L x 0.150" W (3.81mm x 3.81mm)Height - Seated (Max)0.100" (2.54mm)Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads	Failure Rate	-
Size / Dimension 0.150" L x 0.150" W (3.81mm x 3.81mm)   Height - Seated (Max) 0.100" (2.54mm)   Thickness (Max) -   Lead Spacing 0.200" (5.08mm)   Lead Style Formed Leads	Mounting Type	Through Hole
Height - Seated (Max)0.100" (2.54mm)Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads	Package / Case	Radial
Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads	Size / Dimension	0.150" L x 0.150" W (3.81mm x 3.81mm)
Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads	Height - Seated (Max)	0.100" (2.54mm)
Lead Style Formed Leads	Thickness (Max)	-
•	Lead Spacing	0.200" (5.08mm)
Report errors?	Lead Style	Formed Leads
		Report errors?

#### SR122A6R8DAR Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### SR122A6R8DAR Payment Methods



## SR122A6R8DAR Shipping Methods



If you have any question about SR122A6R8DAR, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com