

SR201C104KART

SR201C104KART Information

	Part Number	SR201C104KART	
www.heisener.com For Reference Only	Part Number	SK201C104KAK1	
	Manufacturer	AVX Corporation	I II A SAI
	Category	Capacitors Ceramic Capacitors	
	Description	CAP CER 0.1UF 100V X7R RADIAL	1898 F.
	Package	Radial	
		For the pricing/inventory/lead time, please contact us	
		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



SR201C104KART Specifications

Manufacturer Part Number SR201C104KART Manufacturer AVX Corporation Capacitors Capacitors Package Radial Scries SkyCap? SR Capacitance 0.1µF Yoltage - Rated 100V Operating Temperature Coefficient 010V Operating Temperature 5°C ~ 125°C Package General Purpose Applications General Purpose Applications General Purpose Package / Case Adial Strippe Through Hole Package / Case Radial Size / Dimension 0.200° (S.08mm x 3.18mm) Height - Seated (Max) 0.200° (S.08mm x 3.18mm) Thickness (Max) - Lead Spacing 0.100° (2.54mm)		
CategoryCapacitorsPackageRadialPackageSkyCap? SRCapacitance0.1µFColerance±10%Voltage - Rated100VTomperature Coefficient×7ROperating Temperature-55°C ~ 125°CPactangs-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeNinoug HolePackage / Case.20°U x 0.125°W (5.08mm x 3.18mm)Pickage / Case.20°U x 0.125°W (5.08mm x 3.18mm)Height - Seated (Max).200° (5.08mm)Thickness (Max).200° (5.08mm)Lead SpacingMonting TypeStage Maximum.200° (5.08mm)Stage Maximum.200° (5.08mm) <td>Manufacturer Part Number</td> <td>SR201C104KART</td>	Manufacturer Part Number	SR201C104KART
Ceramic CapacitorsPackageRadialSeriesSkyCap? SRCapacitance0.1μFTolerance±10%Voltage - Rated100VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSiz / Dimension0.200° (5.08mm) x 3.18mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.100° (2.54mm)Lead StyleStraight	Manufacturer	AVX Corporation
PackageRadialSeriesSkyCap? SRCapacitance0.1µFTolerance±10%Voltage - Rated100VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HoleSize / Dimension0.200° L x 0.125° W (5.08mm x 3.18mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.100° (2.54mm)Lead StyleStraight	Category	Capacitors
Arror SkyCap? SR Capacitance 0.1μF Tolerance ±10% Voltage - Rated 100V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Mounting Type Through Hole Size / Dimension 0.200° L x 0.125° W (5.08mm x 3.18mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing 0.100° (2.54mm) Lead Style Straight		Ceramic Capacitors
Capacitance 0.1μF Tolerance ±10% Voltage - Rated 100V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.200" (5.08mm) x 3.18mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing 0.100" (2.54mm)	Package	Radial
Tolerance±10%Voltage - Rated100VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200° L x 0.125° W (5.08mm x 3.18mm)Height - Seated (Max)-Lead Spacing0.100° (2.54mm)Lead StyleSiraight	Series	SkyCap? SR
Voltage - Rated100VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeHolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)-Thickness (Max)0.100" (2.54mm)Lead SpacingStraight	Capacitance	0.1µF
Temperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)-Thickness (Max)0.100" (2.54mm)Lead SpacingStraight	Tolerance	$\pm 10\%$
Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.100" (2.54mm)Lead StyleStraight	Voltage - Rated	100V
Features.Ratings.ApplicationsGeneral PurposeFailure Rate.Mounting TypeThrough HolePackage / CaseRadiaSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max).Thickness (Max).Lead Spacing0.100" (2.54mm)Kead StyleStraight	Temperature Coefficient	X7R
Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)0.200" (5.08mm)Thickness (Max)-Lead Spacing0.100" (2.54mm)Lead StyleStraight	Operating Temperature	-55°C ~ 125°C
ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)0.200" (5.08mm)Thickness (Max)-Lead Spacing0.100" (2.54mm)Lead StyleStraight	Features	-
Failure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)0.200" (5.08mm)Thickness (Max)-Lead Spacing0.100" (2.54mm)Lead StyleStraight	Ratings	-
Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)0.200" (5.08mm)Thickness (Max)-Lead Spacing0.100" (2.54mm)Lead StyleStraight	Applications	General Purpose
Package / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)0.200" (5.08mm)Thickness (Max)-Lead Spacing0.100" (2.54mm)Lead StyleStraight	Failure Rate	-
Size / Dimension 0.200" L x 0.125" W (5.08mm x 3.18mm) Height - Seated (Max) 0.200" (5.08mm) Thickness (Max) - Lead Spacing 0.100" (2.54mm) Lead Style Straight	Mounting Type	Through Hole
Height - Seated (Max)0.200" (5.08mm)Thickness (Max)-Lead Spacing0.100" (2.54mm)Lead StyleStraight	Package / Case	Radial
Thickness (Max)-Lead Spacing0.100" (2.54mm)Lead StyleStraight	Size / Dimension	0.200" L x 0.125" W (5.08mm x 3.18mm)
Lead Spacing0.100" (2.54mm)Lead StyleStraight	Height - Seated (Max)	0.200" (5.08mm)
Lead Style Straight	Thickness (Max)	-
· · ·	Lead Spacing	0.100" (2.54mm)
Report errors?	Lead Style	Straight
		Report errors?

SR201C104KART Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DISCOVER

SR201C104KART Payment Methods



SR201C104KART Shipping Methods



If you have any question about SR201C104KART, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com