

# SR211A750JAA

**Request a Quote** 

## SR211A750JAA Information



## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## SR211A750JAA Specifications

Manufacturer Part NumberSR211A750JAAManufacturerAVX CorporationCategoryCapacitorsPackageRadialSeriesSkyCap? SRCapacitance±5%Yoltage - Rated100VYoltage - RatedCoG, NPOOperating Temperature-55°C ~ 125°CFatures-ApplicationsGeneralPurposeApplicationsGeneralPurposeNoting Type-Mounting TypeStory SN (5.08mm x 3.18mm)Fated (Max)-Size / Dimension-Size / Dimension-Fickers (Max)-Size / Dimension-Size / Dimension-Fickers (Max)-Size / Dimension-Size / Dimension-Size / Dimension-Fickers (Max)-Fickers (Max)-Size / Dimension-Size / Dimension-Size / Dimension-Size / Dimension-Fickers (Max)-Fickers (Max)- <t< th=""><th>-</th><th></th></t<>	-	
CategoryCapacitorsPackageRadialSeriesSkyCap? SRCapacitance75pFTolerance±5%Voltage - Rated100VTemperature CoefficientCOG, NP0Operating Temperature-55°C ~ 125°CFeatures-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200° L x 0.125° W (5.08mm x 3.18mm)Height - Seated (Max).300° (7.62mm)Height Seated (Max)-Lead Spacing0.200° (5.08mm)Lead StyleFormed Leads - Kinked	Manufacturer Part Number	SR211A750JAA
Indext of the section of the sectio	Manufacturer	AVX Corporation
PackageRadialSeriesSkyCap? SRCapacitance75pFTolerance±5%Voltage - Rated00VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeatures-ApplicationsGeneral PurposeFailure Rate-Mounting TypeStrong HolePackage / CaseRadialSize / Dimension0.200° L x 0.125° W (5.08mm x 3.18mm)Height - Seated (Max)-Hickness (Max)-Lead Spacing0.200° (5.08mm)Lead StyleFormed Leads - Kinked	Category	Capacitors
Series SkyCap? SR   Capacitance 75pF   Tolerance ±5%   Voltage - Rated 100V   Temperature Coefficient COG, NPO   Operating Temperature -55°C ~ 125°C   Features -   Applications General Purpose   Failure Rate -   Mounting Type Through Hole   Size / Dimension 0.200" L x 0.125" W (5.08mm x 3.18mm)   Size / Dimension 0.300" (7.62mm)   Thickness (Max) -   Lead Spacing 0.200" (5.08mm)   Lead Style Formed Leads - Kinked		Ceramic Capacitors
Capacitance 75pF   Tolerance ±5%   Voltage - Rated 100V   Temperature Coefficient COG, NPO   Operating Temperature -55°C ~ 125°C   Features -   Ratings -   Applications General Purpose   Failure Rate -   Mounting Type Through Hole   Size / Dimension 0.200° L x 0.125° W (5.08mm x 3.18mm)   Height - Seated (Max) -   Thickness (Max) -   Lead Spacing 0.200° (5.08mm)   Lead Style Formed Leads - Kinked	Package	Radial
Tolerance±5%Voltage - Rated100VTemperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200° L x 0.125° W (5.08mm x 3.18mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.200° (5.08mm)Lead StyleFormed Leads - Kinked	Series	SkyCap? SR
Voltage - Rated100VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)-Thickness (Max)0.200" (5.08mm)Lead SpacingDizor (5.08mm)Lead StyleFormed Leads - Kinked	Capacitance	75pF
TemperatureCOG, NPOOperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Tolerance	±5%
Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Voltage - Rated	100V
Features-Features-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Temperature Coefficient	C0G, NP0
Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Operating Temperature	-55°C ~ 125°C
ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)0.300" (7.62mm)Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Features	-
Failure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)0.300" (7.62mm)Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Ratings	-
Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)0.300" (7.62mm)Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Applications	General Purpose
Package / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)0.300" (7.62mm)Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Failure Rate	-
Size / Dimension 0.200" L x 0.125" W (5.08mm x 3.18mm)   Height - Seated (Max) 0.300" (7.62mm)   Thickness (Max) -   Lead Spacing 0.200" (5.08mm)   Lead Style Formed Leads - Kinked	Mounting Type	Through Hole
Height - Seated (Max)0.300" (7.62mm)Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Package / Case	Radial
Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Size / Dimension	0.200" L x 0.125" W (5.08mm x 3.18mm)
Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Height - Seated (Max)	0.300" (7.62mm)
Lead Style Formed Leads - Kinked	Thickness (Max)	-
	Lead Spacing	0.200" (5.08mm)
Report errors?	Lead Style	Formed Leads - Kinked
		Report errors?

### SR211A750JAA Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

## SR211A750JAA Payment Methods



## SR211A750JAA Shipping Methods



If you have any question about SR211A750JAA, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com