

# SR215E223ZARTR1

#### SR215E223ZARTR1 Information

Heisener.com Ordal terrice cards here	 SR215E223ZARTR1 AVX Corporation Capacitors Ceramic Capacitors CAP CER 0.022UF 50V Z5U RADIAL Radial For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## SR215E223ZARTR1 Specifications

ManufacturerAVX CorporationCapacitorsCaramic CapacitorsPackageRadialSeriesSkyCap? SRCapacitance0.022µFTolerance20%, +80%Voltage - Rated50VTomperature Coefficient25UOperating Temperature10°C ~ 85°CRatings-ApplicationsGeneral PurposeFaiture Rate-ApplicationsGeneral PurposeFaiture Rate-Strings AgeSiller AgeApplicationsCancel AgeFaiture Rate-ApplicationsCancel AgeSize / Dimension0.200° L x 0.125° W (5.08mm x 3.18mm)Height - Seated (Max)-Thickness (Max)6.200° (5.08mm)Lead Spacing0.200° (5.08mm)	-	
CategoryCapacitorsPackageRadialPackageSkyCap? SRCapacitance0.022µFColerance-20%, +80%Voltage - Rated50VTemperature Coefficient25UOperating Temperature10°C ~ 85°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200° L x 0.125° W (5.08mm x 3.18mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing6.200° (5.08mm)Lead StyleFormed Leads - Kinked	Manufacturer Part Number	SR215E223ZARTR1
Ceramic CapacitorsPackageRadialSeriesSkyCap? SRCapacitance0.022µFTolerance-20%, +80%Voltage - Rated50VTemperature Coefficient25UOperating Temperature10°C ~ 85°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)-Thickness (Max)-Lead SpacingFormed Leads - Kinked	Manufacturer	AVX Corporation
PackageRadialSeriesSkyCap? SRCapacitance0.022µFTolerance-20%, +80%Voltage - Rated50VTomperature CoefficientZ5UOperating Temperature10°C ~ 85°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead SyleFormed Leads - Kinked	Category	Capacitors
Series     SkyCap? SR       Capacitance     0.022µF       Tolerance     -20%, +80%       Voltage - Rated     50V       Temperature Coefficient     Z5U       Operating Temperature     10°C ~ 85°C       Features     -       Ratings     -       Applications     General Purpose       Failure Rate     -       Mounting Type     Through Hole       Size / Dimension     0.200" L x 0.125" W (5.08mm x 3.18mm)       Height - Seated (Max)     -       Thickness (Max)     -       Lead Spacing     0.200" (5.08mm)       Lead Style     Formed Leads - Kinked		Ceramic Capacitors
Capacitance0.022µFTolerance-20%, +80%Voltage - Rated50VTemperature Coefficient25UOperating Temperature10°C ~ 85°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200° L x 0.125° W (5.08mm x 3.18mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.200° (5.08mm)Lead StyleFormed Leads - Kinked	Package	Radial
Tolerance-20%, +80%Voltage - Rated50VTemperature CoefficientZ5UOperating Temperature10°C ~ 85°CFeatures-Ratings-ApplicationsGeneral PurposeMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)-Thickness (Max)-Lad StyleGormed Leads - Kinked	Series	SkyCap? SR
Voltage - Rated50VTemperature CoefficientZ5UOperating Temperature10°C ~ 85°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Capacitance	0.022µF
Temperature CoefficientZ5UOperating Temperature10°C ~ 85°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Tolerance	-20%, +80%
Operating Temperature     10°C ~ 85°C       Features     -       Ratings     -       Applications     General Purpose       Failure Rate     -       Mounting Type     Through Hole       Package / Case     Radial       Size / Dimension     0.200" L x 0.125" W (5.08mm x 3.18mm)       Height - Seated (Max)     -       Thickness (Max)     -       Lead Spacing     0.200" (5.08mm)       Lead Style     Formed Leads - Kinked	Voltage - Rated	50V
Features-Features-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Temperature Coefficient	Z5U
Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leades - Kinked	Operating Temperature	$10^{\circ}\text{C} \sim 85^{\circ}\text{C}$
ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)0.300" (7.62mm)Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Features	-
Failure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)0.300" (7.62mm)Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Ratings	-
Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)0.300" (7.62mm)Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Applications	General Purpose
Package / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)0.300" (7.62mm)Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Failure Rate	-
Size / Dimension   0.200" L x 0.125" W (5.08mm x 3.18mm)     Height - Seated (Max)   0.300" (7.62mm)     Thickness (Max)   -     Lead Spacing   0.200" (5.08mm)     Lead Style   Formed Leads - Kinked	Mounting Type	Through Hole
Height - Seated (Max)0.300" (7.62mm)Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Package / Case	Radial
Thickness (Max) -   Lead Spacing 0.200" (5.08mm)   Lead Style Formed Leads - Kinked	Size / Dimension	0.200" L x 0.125" W (5.08mm x 3.18mm)
Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Height - Seated (Max)	0.300" (7.62mm)
Lead Style Formed Leads - Kinked	Thickness (Max)	-
-	Lead Spacing	0.200" (5.08mm)
Report errors?	Lead Style	Formed Leads - Kinked
		Report errors?

#### SR215E223ZARTR1 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DISCOVER

#### SR215E223ZARTR1 Payment Methods



### SR215E223ZARTR1 Shipping Methods



If you have any question about SR215E223ZARTR1, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com