

SR385C334KAR

Request a Quote

SR385C334KAR Information

Heisener.com	Part Number	SR385C334KAR
	Manufacturer	AVX Corporation
	Category	Capacitors Ceramic Capacitors
	Description	CAP CER 0.33UF 50V X7R RADIAL
	Package	Radial
		For the pricing/inventory/lead time, please contact
For Reference Only		us
		Website: https://www.heisener.com
		E-mail: salesdept@heisener.com



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



SR385C334KAR Specifications

ManufacturerAVX CorporationCapacitorsPackageRadialPackageSkyCap? SRCapacitance0.33µFYoltage - Rated50VYoltage - Rated50VOperating Temperature Coefficient×7RPactage-55°C ~ 125°CRatings-ApplicationsGeneral PurposeFailure Rate-Mounting Type-Package / CaseRadialSize / Dimension0.30° L x 0.150° W (7.62mm x 3.81mm)Height - Seated (Max)-Height - Seated (Max)-Thickness (Max)0.307° (9.52mm)	*	
CategoryCapacitorsPackageRadialPackageRadialSeriesSkyCap? SRCapacitance0.33µFTolerance±10%Voltage - Rated50VTemperature Coefficient×7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.300° L x 0.150° W (7.62mm x 3.81mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing6375° (9.52mm)Lead StyleFormed Leads	Manufacturer Part Number	SR385C334KAR
Ceramic CapacitorsPackageRadialSeriesSkyCap? SRCapacitance0.33µFTolerance±10%Voltage - Rated50VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.425° (10.80mm)Height - Seated (Max)-Thickness (Max)-Lead SpacingGorrent Leads	Manufacturer	AVX Corporation
PackageRadialSeriesSkyCap? SRCapacitance0.33µFTolerance±10%Voltage - Rated50VTomperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.300" L x 0.150" W (7.62mm x 3.81mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing6.375" (9.52mm)Lead StyleFormed Leads	Category	Capacitors
Series SkyCap? SR Capacitance 0.33µF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.300" L x 0.150" W (7.62mm x 3.81mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing 0.375" (9.52mm)		Ceramic Capacitors
Capacitance 0.33µF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Size / Dimension 0.300" L x 0.150" W (7.62mm x 3.81mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing 0.375" (9.52mm)	Package	Radial
Tolerance±10%Voltage - Rated50VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.425" (10.80mm)Height - Seated (Max)0.425" (10.80mm)Thickness (Max)6.375" (9.52mm)Lead StyleFormed Leads	Series	SkyCap? SR
Voltage - Rated50VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.300" L x 0.150" W (7.62mm x 3.81mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.375" (9.52mm)Lead StyleFormed Leads	Capacitance	0.33µF
Temperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.300" L x 0.150" W (7.62mm x 3.81mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.375" (9.52mm)Lead StyleFormed Leads	Tolerance	±10%
Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.300" L x 0.150" W (7.62mm x 3.81mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.375" (9.52mm)Lead StyleFormed Leads	Voltage - Rated	50V
Features-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.300" L x 0.150" W (7.62mm x 3.81mm)Height - Seated (Max)0.425" (10.80mm)Thickness (Max)-Lead Spacing0.375" (9.52mm)Lead StyleFormed Leads	Temperature Coefficient	X7R
Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.300" L x 0.150" W (7.62mm x 3.81mm)Height - Seated (Max)0.425" (10.80mm)Thickness (Max)-Lead Spacing0.375" (9.52mm)Lead StyleFormed Leads	Operating Temperature	-55°C ~ 125°C
ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.300" L x 0.150" W (7.62mm x 3.81mm)Height - Seated (Max)0.425" (10.80mm)Thickness (Max)-Lead Spacing0.375" (9.52mm)Lead StyleFormed Leads	Features	-
Failure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.300" L x 0.150" W (7.62mm x 3.81mm)Height - Seated (Max)0.425" (10.80mm)Thickness (Max)-Lead Spacing0.375" (9.52mm)Lead StyleFormed Leads	Ratings	-
Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.300" L x 0.150" W (7.62mm x 3.81mm)Height - Seated (Max)0.425" (10.80mm)Thickness (Max)-Lead Spacing0.375" (9.52mm)Lead StyleFormed Leads	Applications	General Purpose
Package / CaseRadialSize / Dimension0.300" L x 0.150" W (7.62mm x 3.81mm)Height - Seated (Max)0.425" (10.80mm)Thickness (Max)-Lead Spacing0.375" (9.52mm)Lead StyleFormed Leads	Failure Rate	-
Size / Dimension 0.300" L x 0.150" W (7.62mm x 3.81mm) Height - Seated (Max) 0.425" (10.80mm) Thickness (Max) - Lead Spacing 0.375" (9.52mm) Lead Style Formed Leads	Mounting Type	Through Hole
Height - Seated (Max)0.425" (10.80mm)Thickness (Max)-Lead Spacing0.375" (9.52mm)Lead StyleFormed Leads	Package / Case	Radial
Thickness (Max)-Lead Spacing0.375" (9.52mm)Lead StyleFormed Leads	Size / Dimension	0.300" L x 0.150" W (7.62mm x 3.81mm)
Lead Spacing0.375" (9.52mm)Lead StyleFormed Leads	Height - Seated (Max)	0.425" (10.80mm)
Lead Style Formed Leads	Thickness (Max)	-
	Lead Spacing	0.375" (9.52mm)
Report errors?	Lead Style	Formed Leads
		Report errors?

SR385C334KAR Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE SUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

SR385C334KAR Payment Methods





If you have any question about SR385C334KAR, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com