



SR405A333KAA Information



For Reference Only

Part Number SR405A333KAA
Manufacturer AVX Corporation
Category Capacitors

Ceramic Capacitors

Description CAP CER 0.033UF 50V NP0 RADIAL

Package Radia

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SR405A333KAA Specifications

Manufacturer Part Number SR405A33KAA Manufacturer AVX Corporation Category Capacitors Package Radial Series SkyCap? SR Capacitance 0.033µF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient COG, NPO Operating Temperature -55°C ~ 125°C Features - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.400" L x 0.150" W (10.16mm x 3.81mm) Height - Seated (Max) 0.460" (11.68mm) Thickness (Max) - Lead Spacing 0.200" (5.08mm) Lead Style Straight	•	
Category Capacitors Package Radial Series SkyCap? SR Capacitance 0.033µF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.400" L x 0.150" W (10.16mm x 3.81mm) Height - Seated (Max) 0.460" (11.68mm) Thickness (Max) - Lead Spacing 0.200" (5.08mm)	Manufacturer Part Number	SR405A333KAA
Package Radial Series SkyCap? SR Capacitance 0.033μF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient C0G, NPO Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.400" L x 0.150" W (10.16mm x 3.81mm) Height - Seated (Max) 0.460" (11.68mm) Thickness (Max) - Lead Spacing 0.200" (5.08mm)	Manufacturer	AVX Corporation
Package Radial Series SkyCap? SR Capacitance 0.033µF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.400" L x 0.150" W (10.16mm x 3.81mm) Height - Seated (Max) 0.460" (11.68mm) Thickness (Max) - Lead Spacing 0.200" (5.08mm)	Category	Capacitors
Series SkyCap? SR Capacitance 0.033μF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.400" L x 0.150" W (10.16mm x 3.81mm) Height - Seated (Max) 0.460" (11.68mm) Thickness (Max) - Lead Spacing 0.200" (5.08mm)		Ceramic Capacitors
Capacitance 0.033µF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.400" L x 0.150" W (10.16mm x 3.81mm) Height - Seated (Max) 0.460" (11.68mm) Thickness (Max) - Lead Spacing 0.200" (5.08mm)	Package	Radial
Tolerance $\pm 10\%$ Voltage - Rated $50V$ Temperature Coefficient $C0G$, NP0Operating Temperature -55° C $\sim 125^{\circ}$ CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension 0.400° L x 0.150° W $(10.16\text{mm x } 3.81\text{mm})$ Height - Seated (Max) 0.460° (11.68mm)Thickness (Max)-Lead Spacing 0.200° (5.08mm)	Series	SkyCap? SR
Voltage - Rated50VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.400" L x 0.150" W (10.16mm x 3.81mm)Height - Seated (Max)0.460" (11.68mm)Thickness (Max)-Lead Spacing0.200" (5.08mm)	Capacitance	0.033µF
Temperature Coefficient Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension O.400" L x 0.150" W (10.16mm x 3.81mm) Height - Seated (Max) O.460" (11.68mm) Thickness (Max) Lead Spacing O.200" (5.08mm)	Tolerance	±10%
Operating Temperature Features -55°C ~ 125°C Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension O.400" L x 0.150" W (10.16mm x 3.81mm) Height - Seated (Max) O.460" (11.68mm) Thickness (Max) Lead Spacing O.200" (5.08mm)	Voltage - Rated	50V
Features - General Purpose - Applications General Purpose - General Purpose - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.400" L x 0.150" W (10.16mm x 3.81mm) Height - Seated (Max) 0.460" (11.68mm) - Lead Spacing 0.200" (5.08mm)	Temperature Coefficient	C0G, NP0
Ratings - General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.400" L x 0.150" W (10.16mm x 3.81mm) Height - Seated (Max) 0.460" (11.68mm) Thickness (Max) - Lead Spacing 0.200" (5.08mm)	Operating Temperature	-55°C ~ 125°C
Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.400" L x 0.150" W (10.16mm x 3.81mm) Height - Seated (Max) 0.460" (11.68mm) Thickness (Max) - Lead Spacing 0.200" (5.08mm)	Features	-
Failure Rate Mounting Type Through Hole Package / Case Radial Size / Dimension 0.400" L x 0.150" W (10.16mm x 3.81mm) Height - Seated (Max) 0.460" (11.68mm) Thickness (Max) - Lead Spacing 0.200" (5.08mm)	Ratings	-
Mounting Type Package / Case Radial Size / Dimension 0.400" L x 0.150" W (10.16mm x 3.81mm) Height - Seated (Max) 7 hickness (Max) Lead Spacing - 0.200" (5.08mm)	Applications	General Purpose
Package / Case Radial Size / Dimension 0.400" L x 0.150" W (10.16mm x 3.81mm) Height - Seated (Max) 0.460" (11.68mm) Thickness (Max) - Lead Spacing 0.200" (5.08mm)	Failure Rate	-
Size / Dimension 0.400" L x 0.150" W (10.16mm x 3.81mm) Height - Seated (Max) 0.460" (11.68mm) Thickness (Max) - Lead Spacing 0.200" (5.08mm)	Mounting Type	Through Hole
Height - Seated (Max) 0.460" (11.68mm) Thickness (Max) - Lead Spacing 0.200" (5.08mm)	Package / Case	Radial
Thickness (Max) - Lead Spacing 0.200" (5.08mm)	Size / Dimension	0.400" L x 0.150" W (10.16mm x 3.81mm)
Lead Spacing 0.200" (5.08mm)	Height - Seated (Max)	0.460" (11.68mm)
	Thickness (Max)	-
Lead Style Straight	Lead Spacing	0.200" (5.08mm)
	Lead Style	Straight
Report errors?		Report errors?

SR405A333KAA Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SR405A333KAA Payment Methods





















SR405A333KAA Shipping Methods













If you have any question about SR405A333KAA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com