



SR405A683KAA Information



For Reference Only

Part Number SR405A683KAA
Manufacturer AVX Corporation
Category Capacitors

y Capacitors Ceramic Capacitors

Description CAP CER 0.068UF 50V NP0 RADIAL

Package Radia

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SR405A683KAA Specifications

Manufacturer Part Number SR405A683KAA Manufacturer AVX Corporation Category Capacitors Package Radial Series SkyCap? SR Capacitance 0.068µF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient C0G, NPO Operating Temperature -55°C ~ 125°C Features - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.400" L x 0.150" W (10.16mm x 3.81mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing 0.200" (5.08mm) Lead Style Straight		
Category Capacitors Package Radial Series SkyCap? SR Capacitance 0.068μF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient C0G, NPO Operating Temperature -55°C ~ 125°C Features - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.400" L x 0.150" W (10.16mm x 3.81mm) Height - Seated (Max) 0.460" (11.68mm) Thickness (Max) - Lead Spacing 0.200" (5.08mm) Lead Style Straight	Manufacturer Part Number	SR405A683KAA
Package Radial Series SkyCap? SR Capacitance 0.068µF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.400" L x 0.150" W (10.16mm x 3.81mm) Height - Seated (Max) 0.460" (11.68mm) Thickness (Max) - Lead Spacing 0.200" (5.08mm) Lead Style Straight	Manufacturer	AVX Corporation
Package Radial Series SkyCap? SR Capacitance 0.068μF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.400" L x 0.150" W (10.16mm x 3.81mm) Height - Seated (Max) 0.460" (11.68mm) Thickness (Max) - Lead Spacing 0.200" (5.08mm) Lead Style Straight	Category	Capacitors
Series SkyCap? SR Capacitance 0.068µF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.400" L x 0.150" W (10.16mm x 3.81mm) Height - Seated (Max) 0.460" (11.68mm) Thickness (Max) - Lead Spacing 0.200" (5.08mm) Lead Style Straight		Ceramic Capacitors
Capacitance 0.068μF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.400" L x 0.150" W (10.16mm x 3.81mm) Height - Seated (Max) 0.460" (11.68mm) Thickness (Max) - Lead Spacing 0.200" (5.08mm) Lead Style Straight	Package	Radial
Tolerance ±10% Voltage - Rated 50V Temperature Coefficient COG, NP0 Operating Temperature -55°C ~ 125°C Features Ratings Applications General Purpose Failure Rate Mounting Type Through Hole Package / Case Radial Size / Dimension 0.400" L x 0.150" W (10.16mm x 3.81mm) Height - Seated (Max) 0.460" (11.68mm) Thickness (Max) Lead Spacing 0.200" (5.08mm) Lead Style Straight	Series	SkyCap? SR
Voltage - Rated50VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.400" L x 0.150" W (10.16mm x 3.81mm)Height - Seated (Max)0.460" (11.68mm)Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleStraight	Capacitance	0.068μF
Temperature Coefficient Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension O.400" L x 0.150" W (10.16mm x 3.81mm) Height - Seated (Max) Thickness (Max) - Lead Spacing O.200" (5.08mm) Lead Style	Tolerance	±10%
Operating Temperature Features -55°C ~ 125°C Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.400" L x 0.150" W (10.16mm x 3.81mm) Height - Seated (Max) Thickness (Max) Lead Spacing 0.200" (5.08mm) Lead Style	Voltage - Rated	50V
Features - Ratings - Applications General Purpose Failure Rate - Through Hole Package / Case Radial Size / Dimension 0.400" L x 0.150" W (10.16mm x 3.81mm) Height - Seated (Max) 0.460" (11.68mm) - Lead Spacing 0.200" (5.08mm) Lead Style Straight	Temperature Coefficient	C0G, NP0
Ratings - General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.400" L x 0.150" W (10.16mm x 3.81mm) Height - Seated (Max) 0.460" (11.68mm) Thickness (Max) - Lead Spacing 0.200" (5.08mm) Lead Style Straight	Operating Temperature	-55°C ~ 125°C
Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.400" L x 0.150" W (10.16mm x 3.81mm) Height - Seated (Max) 0.460" (11.68mm) Thickness (Max) - Lead Spacing 0.200" (5.08mm) Lead Style Straight	Features	-
Failure Rate Mounting Type Through Hole Package / Case Radial Size / Dimension 0.400" L x 0.150" W (10.16mm x 3.81mm) Height - Seated (Max) 0.460" (11.68mm) Thickness (Max) - Lead Spacing 0.200" (5.08mm) Lead Style Straight	Ratings	-
Mounting Type Package / Case Radial Size / Dimension 0.400" L x 0.150" W (10.16mm x 3.81mm) Height - Seated (Max) 0.460" (11.68mm) Thickness (Max) Lead Spacing 0.200" (5.08mm) Lead Style Straight	Applications	General Purpose
Package / Case Radial Size / Dimension 0.400" L x 0.150" W (10.16mm x 3.81mm) Height - Seated (Max) 0.460" (11.68mm) Thickness (Max) - Lead Spacing 0.200" (5.08mm) Lead Style Straight	Failure Rate	-
Size / Dimension 0.400" L x 0.150" W (10.16mm x 3.81mm) Height - Seated (Max) 0.460" (11.68mm) Thickness (Max) - Lead Spacing 0.200" (5.08mm) Lead Style Straight	Mounting Type	Through Hole
Height - Seated (Max) Thickness (Max) Lead Spacing O.200" (5.08mm) Lead Style Straight	Package / Case	Radial
Thickness (Max) Lead Spacing 0.200" (5.08mm) Lead Style Straight	Size / Dimension	0.400" L x 0.150" W (10.16mm x 3.81mm)
Lead Spacing 0.200" (5.08mm) Lead Style Straight	Height - Seated (Max)	0.460" (11.68mm)
Lead Style Straight	Thickness (Max)	-
	Lead Spacing	0.200" (5.08mm)
Report errors?	Lead Style	Straight
		Report errors?

SR405A683KAA Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SR405A683KAA Payment Methods





















SR405A683KAA Shipping Methods













If you have any question about SR405A683KAA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com