



SR501C155KAR Information



For Reference Only

Part Number SR501C155KAR
Manufacturer AVX Corporation
Category Capacitors

Ceramic Capacitors

Description CAP CER 1.5UF 100V X7R RADIAL

Package Radia

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SR501C155KAR Specifications

Manufacturer Part Number SR501C155KAR Manufacturer AVX Corporation Category Capacitors Package Radial Series SkyCap? SR Capacitance 1.5µF Tolerance ±10% Voltage - Rated 100V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.500" L x 0.200" W (12.70mm x 5.08mm) Height - Seated (Max) 0.560" (14.22mm) Thickness (Max) - Lead Spacing 0.400" (10.16mm) Lead Style Straight		
Category Capacitors Package Radial Series SkyCap? SR Capacitance 1.5µF Tolerance ±10% Voltage - Rated 100V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.500" L x 0.200" W (12.70mm x 5.08mm) Height - Seated (Max) 0.560" (14.22mm) Thickness (Max) - Lead Spacing 0.400" (10.16mm) Lead Style Straight	Manufacturer Part Number	SR501C155KAR
Package Radial Series SkyCap? SR Capacitance 1.5μF Tolerance ±10% Voltage - Rated 100V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.500" L x 0.200" W (12.70mm x 5.08mm) Height - Seated (Max) 0.560" (14.22mm) Thickness (Max) - Lead Spacing 0.400" (10.16mm) Lead Style Straight	Manufacturer	AVX Corporation
Package Radial Series SkyCap? SR Capacitance 1.5µF Tolerance ±10% Voltage - Rated 100V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.500" L x 0.200" W (12.70mm x 5.08mm) Height - Seated (Max) 0.560" (14.22mm) Thickness (Max) - Lead Spacing 0.400" (10.16mm) Lead Style Straight	Category	Capacitors
Series SkyCap? SR Capacitance 1.5μF Tolerance ±10% Voltage - Rated 100V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.500" L x 0.200" W (12.70mm x 5.08mm) Height - Seated (Max) 0.560" (14.22mm) Thickness (Max) - Lead Spacing 0.400" (10.16mm) Lead Style Straight		Ceramic Capacitors
Capacitance $1.5\mu F$ Tolerance $\pm 10\%$ Voltage - Rated $100V$ Temperature Coefficient $X7R$ Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$ Features-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension 0.500° L x 0.200° W (12.70 mm x 5.08 mm)Height - Seated (Max) 0.560° (14.22 mm)Thickness (Max)-Lead Spacing 0.400° (10.16 mm)Lead StyleStraight	Package	Radial
Tolerance ±10% Voltage - Rated 100V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features Ratings Applications General Purpose Failure Rate Mounting Type Through Hole Package / Case Radial Size / Dimension 0.500" L x 0.200" W (12.70mm x 5.08mm) Height - Seated (Max) 0.560" (14.22mm) Thickness (Max) Lead Spacing 0.400" (10.16mm) Lead Style Straight	Series	SkyCap? SR
Voltage - Rated Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.500" L x 0.200" W (12.70mm x 5.08mm) Height - Seated (Max) Thickness (Max) Lead Spacing 0.400" (10.16mm) Lead Style STRIP ATTEM TO A TO	Capacitance	1.5μF
Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.500" L x 0.200" W (12.70mm x 5.08mm) Height - Seated (Max) Thickness (Max) - Lead Spacing 0.400" (10.16mm) Lead Style	Tolerance	±10%
Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.500" L x 0.200" W (12.70mm x 5.08mm)Height - Seated (Max)0.560" (14.22mm)Thickness (Max)-Lead Spacing0.400" (10.16mm)Lead StyleStraight	Voltage - Rated	100V
Features Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.500" L x 0.200" W (12.70mm x 5.08mm) Height - Seated (Max) 0.560" (14.22mm) Thickness (Max) - Lead Spacing 0.400" (10.16mm) Lead Style Straight	Temperature Coefficient	X7R
Ratings - General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.500" L x 0.200" W (12.70mm x 5.08mm) Height - Seated (Max) 0.560" (14.22mm) Thickness (Max) - Lead Spacing 0.400" (10.16mm) Lead Style Straight	Operating Temperature	-55°C ~ 125°C
Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.500" L x 0.200" W (12.70mm x 5.08mm) Height - Seated (Max) 0.560" (14.22mm) Thickness (Max) - Lead Spacing 0.400" (10.16mm) Lead Style Straight	Features	-
Failure Rate Mounting Type Through Hole Package / Case Radial Size / Dimension 0.500" L x 0.200" W (12.70mm x 5.08mm) Height - Seated (Max) 0.560" (14.22mm) Thickness (Max) - Lead Spacing 0.400" (10.16mm) Lead Style Straight	Ratings	-
Mounting Type Package / Case Radial Size / Dimension 0.500" L x 0.200" W (12.70mm x 5.08mm) Height - Seated (Max) 0.560" (14.22mm) Thickness (Max) - Lead Spacing 0.400" (10.16mm) Lead Style Straight	Applications	General Purpose
Package / Case Radial Size / Dimension 0.500" L x 0.200" W (12.70mm x 5.08mm) Height - Seated (Max) 0.560" (14.22mm) Thickness (Max) - Lead Spacing 0.400" (10.16mm) Lead Style Straight	Failure Rate	-
Size / Dimension 0.500" L x 0.200" W (12.70mm x 5.08mm) Height - Seated (Max) 0.560" (14.22mm) Thickness (Max) - Lead Spacing 0.400" (10.16mm) Lead Style Straight	Mounting Type	Through Hole
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style O.560" (14.22mm) - U.400" (10.16mm) Straight	Package / Case	Radial
Thickness (Max) Lead Spacing O.400" (10.16mm) Lead Style Straight	Size / Dimension	0.500" L x 0.200" W (12.70mm x 5.08mm)
Lead Spacing0.400" (10.16mm)Lead StyleStraight	Height - Seated (Max)	0.560" (14.22mm)
Lead Style Straight	Thickness (Max)	-
	Lead Spacing	0.400" (10.16mm)
Report errors?	Lead Style	Straight
		Report errors?

SR501C155KAR Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SR501C155KAR Payment Methods



















SR501C155KAR Shipping Methods













If you have any question about SR501C155KAR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com