

#### SRL7-523-D018 Information

www.helsener.com

Part Number SRL7-523-D018

Manufacturer TE Connectivity Potter & Brumfield Relays

Category

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE 7PST 6A 18V

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# SRL7-523-D018 Specifications

Manufacturer Part NumberSRL7-523-D018ManufacturerTE Connectivity Potter & Brumfield RelaysCategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesSRL7, SCHRACKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current38.9mACoil Voltage18VDCContact Form7PST (5 Form A, 2 Form B)Contact Rating (Current)6ASwitching Voltage400VAC - MaxTurn On Voltage (Max)13.5 VDCTurn Off Voltage (Min)1.8 VDCOperate Time-Release Time-Features-Mounting TypeThrough HoleTermination StylePC Pin		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesSRL7, SCHRACKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current38.9mACoil Voltage18VDCContact Form7PST (5 Form A, 2 Form B)Contact Rating (Current)6ASwitching Voltage400VAC - MaxTurn On Voltage (Max)13.5 VDCTurn Off Voltage (Min)1.8 VDCOperate Time-Release Time-Features-Mounting TypeThrough Hole	Manufacturer Part Number	SRL7-523-D018
Package         -           Series         SRL7, SCHRACK           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         38.9mA           Coil Voltage         18VDC           Contact Form         7PST (5 Form A, 2 Form B)           Contact Rating (Current)         6A           Switching Voltage         400VAC - Max           Turn On Voltage (Max)         13.5 VDC           Turn Off Voltage (Min)         1.8 VDC           Operate Time         -           Release Time         -           Features         -           Mounting Type         Through Hole	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package-SeriesSRL7, SCHRACKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current38.9mACoil Voltage18VDCContact Form7PST (5 Form A, 2 Form B)Contact Rating (Current)6ASwitching Voltage400VAC - MaxTurn On Voltage (Max)13.5 VDCTurn Off Voltage (Min)1.8 VDCOperate Time-Release Time-Features-Mounting TypeThrough Hole	Category	Relays
SeriesSRL7, SCHRACKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current38.9mACoil Voltage18VDCContact Form7PST (5 Form A, 2 Form B)Contact Rating (Current)6ASwitching Voltage400VAC - MaxTurn On Voltage (Max)13.5 VDCTurn Off Voltage (Min)1.8 VDCOperate Time-Release Time-Features-Mounting TypeThrough Hole		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current38.9mACoil Voltage18VDCContact Form7PST (5 Form A, 2 Form B)Contact Rating (Current)6ASwitching Voltage400VAC - MaxTurn On Voltage (Max)13.5 VDCTurn Off Voltage (Min)1.8 VDCOperate Time-Release Time-Features-Mounting TypeThrough Hole	Package	-
Coil Type Non Latching Coil Current 38.9mA Coil Voltage 18VDC Contact Form 7PST (5 Form A, 2 Form B) Contact Rating (Current) 6A Switching Voltage 400VAC - Max Turn On Voltage (Max) 13.5 VDC Turn Off Voltage (Min) 1.8 VDC Operate Time - Release Time - Features - Mounting Type Through Hole	Series	SRL7, SCHRACK
Coil Current 38.9mA Coil Voltage 18VDC Contact Form 7PST (5 Form A, 2 Form B) Contact Rating (Current) 6A Switching Voltage 400VAC - Max Turn On Voltage (Max) 13.5 VDC Turn Off Voltage (Min) 1.8 VDC Operate Time - Release Time - Features - Mounting Type Through Hole	Relay Type	General Purpose
Coil Voltage 18VDC Contact Form 7PST (5 Form A, 2 Form B) Contact Rating (Current) 6A Switching Voltage 400VAC - Max Turn On Voltage (Max) 13.5 VDC Turn Off Voltage (Min) 1.8 VDC Operate Time - Release Time - Features - Mounting Type Through Hole	Coil Type	Non Latching
Contact Form 7PST (5 Form A, 2 Form B)  Contact Rating (Current) 6A  Switching Voltage 400VAC - Max  Turn On Voltage (Max) 13.5 VDC  Turn Off Voltage (Min) 1.8 VDC  Operate Time -  Release Time -  Features -  Mounting Type Through Hole	Coil Current	38.9mA
Contact Rating (Current)  Switching Voltage  400VAC - Max  Turn On Voltage (Max)  13.5 VDC  Turn Off Voltage (Min)  1.8 VDC  Operate Time  - Release Time  - Wounting Type  Through Hole	Coil Voltage	18VDC
Switching Voltage 400VAC - Max  Turn On Voltage (Max) 13.5 VDC  Turn Off Voltage (Min) 1.8 VDC  Operate Time -  Release Time -  Features -  Mounting Type Through Hole	Contact Form	7PST (5 Form A, 2 Form B)
Turn On Voltage (Max)  13.5 VDC  Turn Off Voltage (Min)  1.8 VDC  Operate Time  - Release Time  - Features  - Mounting Type  Through Hole	Contact Rating (Current)	6A
Turn Off Voltage (Min)  1.8 VDC  Operate Time  - Release Time  - Features  - Mounting Type  Through Hole	Switching Voltage	400VAC - Max
Operate Time - Release Time - Seatures - Mounting Type Through Hole	Turn On Voltage (Max)	13.5 VDC
Release Time - Features - Mounting Type Through Hole	Turn Off Voltage (Min)	1.8 VDC
Features - Through Hole	Operate Time	-
Mounting Type Through Hole	Release Time	-
	Features	-
Termination Style PC Pin	Mounting Type	Through Hole
	Termination Style	PC Pin
Report errors?		Report errors?

#### SRL7-523-D018 Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### SRL7-523-D018 Payment Methods



















## SRL7-523-D018 Shipping Methods













If you have any question about SRL7-523-D018, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com