

**SRN6045TA-101M Information**


For Reference Only

**Part Number** [SRN6045TA-101M](#)  
**Manufacturer** Bourns Inc.  
**Category** Inductors, Coils, Chokes  
[Fixed Inductors](#)  
**Description** FIXED IND 100UH 920MA 456 MOHM  
**Package** Nonstandard  
 For the pricing/inventory/lead time, please contact us  
 Website: <https://www.heisener.com>  
 E-mail: [salesdept@heisener.com](mailto:salesdept@heisener.com)


[Request a Quote](#)
**Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.


**SRN6045TA-101M Specifications**

Manufacturer Part Number	<a href="#">SRN6045TA-101M</a>
Manufacturer	Bourns Inc.
Category	Inductors, Coils, Chokes <a href="#">Fixed Inductors</a>
Package	Nonstandard
Series	SRN6045TA
Type	Wirewound
Material - Core	Ferrite
Inductance	100µH
Tolerance	±20%
Current Rating	920mA
Current - Saturation	1.33A
Shielding	Semi-Shielded
DC Resistance (DCR)	456 mOhm
Q @ Freq	15 @ 1MHz
Frequency - Self Resonant	8.5MHz
Ratings	AEC-Q200
Operating Temperature	-55°C ~ 125°C
Frequency - Test	1MHz
Features	-
Mounting Type	Surface Mount
Package / Case	Nonstandard
Supplier Device Package	-
Size / Dimension	0.236" Dia x 0.236" W (6.00mm x 6.00mm)

Height - Seated (Max)

0.177" (4.50mm)

[Report errors?](#)

## SRN6045TA-101M Guarantees



### Quality Guarantees

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



### Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## SRN6045TA-101M Payment Methods



## SRN6045TA-101M Shipping Methods



If you have any question about SRN6045TA-101M, please do not hesitate to contact us!

Website: <https://www.heisener.com>

E-mail: [salesdept@heisener.com](mailto:salesdept@heisener.com)