



SRR1005-101K Information



For Reference Only

Part Number SRR1005-101K Manufacturer Bourns Inc.

Category Inductors, Coils, Chokes

Fixed Inductors

Description FIXED IND 100UH 680MA 420 MOHM

Package Nonstandard

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SRR1005-101K Specifications

Manufacturer Category Inductors, Coils, Chokes Fixed Inductors Package Nonstandard Series SRR1005 Type Wirewound Material - Core Inductance Inductance Inductance Uurrent Rating Ferrite Current Rating Ferrite Ferrite For Resistance (DCR) Ferrite 420 mOhm Max Q @ Freq Frequency - Self Resonant Ratings Operating Temperature Features Mounting Type Bourns Inc. Inductors, Coils, Chokes Fixed Inductors Freque Minductors Frequency Fixed Inductors Fixed Inducto	
Fixed Inductors	
PackageNonstandardSeriesSRR1005TypeWirewoundMaterial - CoreFerriteInductance100μHTolerance±10%Current Rating680mACurrent - Saturation900mAShieldingShieldedDC Resistance (DCR)420 mOhm MaxQ @ Freq35 @ 796kHzFrequency - Self Resonant7.5MHzRatings-Operating Temperature-40°C ~ 125°CFrequency - Test1kHzFeatures-	
Series SRR1005 Type Wirewound Material - Core Ferrite Inductance 100µH Tolerance ±10% Current Rating 680mA Current - Saturation 900mA Shielding Shielded DC Resistance (DCR) 420 mOhm Max Q @ Freq 35 @ 796kHz Frequency - Self Resonant 7.5MHz Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 1kHz Features -	
Type Wirewound Material - Core Ferrite Inductance $100\mu H$ Tolerance $\pm 10\%$ Current Rating $680mA$ Current - Saturation $900mA$ Shielding Shielded DC Resistance (DCR) $420 mOhm Max$ Q @ Freq $35 @ 796kHz$ Frequency - Self Resonant $7.5MHz$ Ratings - Operating Temperature $-40^{\circ}C \sim 125^{\circ}C$ Frequency - Test $1kHz$ Features $-40^{\circ}C \sim 125^{\circ}C$	
Material - CoreFerriteInductance $100\mu H$ Tolerance $\pm 10\%$ Current Rating $680mA$ Current - Saturation $900mA$ ShieldingShieldedDC Resistance (DCR) $420 mOhm Max$ Q @ Freq $35 @ 796kHz$ Frequency - Self Resonant $7.5MHz$ Ratings-Operating Temperature $-40^{\circ}C \sim 125^{\circ}C$ Frequency - Test $1kHz$ Features-	
Inductance $100\mu H$ Tolerance $\pm 10\%$ Current Rating $680mA$ Current - Saturation $900mA$ ShieldingShieldedDC Resistance (DCR) $420 mOhm Max$ Q @ Freq $35 @ 796kHz$ Frequency - Self Resonant $7.5MHz$ Ratings-Operating Temperature $-40^{\circ}C \sim 125^{\circ}C$ Frequency - Test $1kHz$ Features-	
Tolerance $\pm 10\%$ Current Rating 680mA Current - Saturation 900mA ShieldingShieldedDC Resistance (DCR) 420 mOhm Max Q @ Freq 35 @ 796kHz Frequency - Self Resonant 7.5MHz Ratings-Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Frequency - Test 1kHz Features-	
Current Rating 680mA Current - Saturation 900mA Shielding Shielded DC Resistance (DCR) 420 mOhm Max Q @ Freq 35 @ 796kHz Frequency - Self Resonant 7.5MHz Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 1kHz Features -	
Current - Saturation 900mA Shielding Shielded DC Resistance (DCR) 420 mOhm Max Q @ Freq 35 @ 796kHz Frequency - Self Resonant 7.5MHz Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 1kHz Features -	
Shielding DC Resistance (DCR) 420 mOhm Max Q @ Freq 35 @ 796kHz Frequency - Self Resonant 7.5MHz Ratings Operating Temperature -40°C ~ 125°C Frequency - Test 1kHz Features -	
DC Resistance (DCR) 420 mOhm Max Q @ Freq $35 \text{ @ } 796 \text{kHz}$ Frequency - Self Resonant 7.5MHz Ratings-Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Frequency - Test 1kHz Features-	
Q @ Freq 35 @ 796kHz Frequency - Self Resonant 7.5MHz Ratings - Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Frequency - Test 1kHz Features -	
Ratings - $ -40^{\circ}\text{C} \sim 125^{\circ}\text{C} $ Frequency - Test $ 1\text{kHz} $ Features - $ -40^{\circ}\text{C} \sim 125^{\circ}\text{C} $	
Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Frequency - Test 1kHz Features -	
Frequency - Test 1kHz Features -	
Features -	
Mounting Type Surface Mount	
201100 -71	
Package / Case Nonstandard	
Supplier Device Package -	
Size / Dimension 0.500" L x 0.394" W (12.70mm x 10.00mm)	

Height - Seated (Max) 0.205" (5.20mm) Report errors?

SRR1005-101K Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SRR1005-101K Payment Methods





















SRR1005-101K Shipping Methods













If you have any question about SRR1005-101K, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com