



SRR1240-391K Information



For Reference Only

Part Number SRR1240-391K Manufacturer Bourns Inc.

Category Inductors, Coils, Chokes

Fixed Inductors

Description FIXED IND 390UH 700MA 1.15 OHM

Package Nonstandard

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SRR1240-391K Specifications

Manufacturer Bourns Inc. Category Inductors, Coils, Chokes Fixed Inductors Package Nonstandard Series SRR1240 Type Wirewound Material - Core Ferrite Inductance 390µH Tolerance ±10% Current Rating 700mA Current - Saturation 650mA Shielding Shielded DC Resistance (DCR) 1.15 Ohm Max Q @ Freq 12 @ 796kHz Frequency - Self Resonant 5MHz Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package - Size / Dimension 0.492" L x 0.492" W (12.50mm x 12.50mm)	Manufacturer Part Number	SRR1240-391K
Fixed Inductors Package Nonstandard Series SRR1240 Type Wirewound Material - Core Ferrite Inductance 390µH Tolerance ±10% Current Rating 700mA Current - Saturation 650mA Shielding Shielded DC Resistance (DCR) 1.15 Ohm Max Q @ Freq 12 @ 796kHz Frequency - Self Resonant 5MHz Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package -	Manufacturer	Bourns Inc.
PackageNonstandardSeriesSRR1240TypeWirewoundMaterial - CoreFerriteInductance390μHTolerance±10%Current Rating700mACurrent - Saturation650mAShieldingShieldedDC Resistance (DCR)1.15 Ohm MaxQ @ Freq12 @ 796kHzFrequency - Self Resonant5MHzRatings-Operating Temperature-40°C ~ 125°CFrequency - Test100kHzFeatures-Mounting TypeSurface MountPackage / CaseNonstandardSupplier Device Package-	Category	Inductors, Coils, Chokes
Series SRR1240 Type Wirewound Material - Core Ferrite Inductance 390µH Tolerance ±10% Current Rating 700mA Current - Saturation 650mA Shielding Shielded DC Resistance (DCR) 1.15 Ohm Max Q @ Freq 12 @ 796kHz Frequency - Self Resonant 5MHz Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package -		Fixed Inductors
TypeWirewoundMaterial - CoreFerriteInductance390μHTolerance±10%Current Rating700mACurrent - Saturation650mAShieldingShieldedDC Resistance (DCR)1.15 Ohm MaxQ @ Freq12 @ 796kHzFrequency - Self Resonant5MHzRatings-Operating Temperature-40°C ~ 125°CFrequency - Test100kHzFeatures-Mounting TypeSurface MountPackage / CaseNonstandardSupplier Device Package-	Package	Nonstandard
Material - Core Ferrite Inductance 390µH Tolerance ±10% Current Rating 700mA Current - Saturation 650mA Shielding Shielded DC Resistance (DCR) 1.15 Ohm Max Q @ Freq 12 @ 796kHz Frequency - Self Resonant 5MHz Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package -	Series	SRR1240
Inductance390μHTolerance±10%Current Rating700mACurrent - Saturation650mAShieldingShieldedDC Resistance (DCR)1.15 Ohm MaxQ @ Freq12 @ 796kHzFrequency - Self Resonant5MHzRatings-Operating Temperature-40°C ~ 125°CFrequency - Test100kHzFeatures-Mounting TypeSurface MountPackage / CaseNonstandardSupplier Device Package-	Туре	Wirewound
Tolerance ±10% Current Rating 700mA Current - Saturation 650mA Shielding Shielded DC Resistance (DCR) 1.15 Ohm Max Q @ Freq 12 @ 796kHz Frequency - Self Resonant 5MHz Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 100kHz Features Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package	Material - Core	Ferrite
Current Rating 700mA Current - Saturation 650mA Shielding Shielded DC Resistance (DCR) 1.15 Ohm Max Q @ Freq 12 @ 796kHz Frequency - Self Resonant 5MHz Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package -	Inductance	390μΗ
Current - Saturation 650mA Shielding Shielded DC Resistance (DCR) 1.15 Ohm Max Q @ Freq 12 @ 796kHz Frequency - Self Resonant 5MHz Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package -	Tolerance	±10%
Shielding DC Resistance (DCR) 1.15 Ohm Max Q @ Freq 12 @ 796kHz Frequency - Self Resonant SMHz Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Supplier Device Package -	Current Rating	700mA
DC Resistance (DCR) Q @ Freq 12 @ 796kHz Frequency - Self Resonant SMHz Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Supplier Device Package - 1.15 Ohm Max 1.2 @ 796kHz 5MHz 5MHz - 40°C ~ 125°C Surface Mount Nonstandard Nonstandard	Current - Saturation	650mA
Q @ Freq 12 @ 796kHz Frequency - Self Resonant 5MHz Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package -	Shielding	Shielded
Frequency - Self Resonant Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package -	DC Resistance (DCR)	1.15 Ohm Max
Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package	Q @ Freq	12 @ 796kHz
Operating Temperature -40°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package -	Frequency - Self Resonant	5MHz
Frequency - Test 100kHz Features Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package	Ratings	-
Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package -	Operating Temperature	-40°C ~ 125°C
Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package -	Frequency - Test	100kHz
Package / Case Nonstandard Supplier Device Package -	Features	-
Supplier Device Package -	Mounting Type	Surface Mount
	Package / Case	Nonstandard
Size / Dimension 0.492" L x 0.492" W (12.50mm x 12.50mm)	Supplier Device Package	-
	Size / Dimension	0.492" L x 0.492" W (12.50mm x 12.50mm)

Height - Seated (Max) 0.177" (4.50mm) Report errors?

SRR1240-391K Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SRR1240-391K Payment Methods





















SRR1240-391K Shipping Methods













If you have any question about SRR1240-391K, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com