

SS210LHMHG

SS210LHMHG Information

Heisener.com	Part Number Manufacturer Category Description Package	SS210LHMHG TSC America Inc. Discrete Semiconductor Products Diodes - Rectifiers - Single DIODE, SCHOTTKY, STANDARD, 2A, 1 DO-219AB For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



SS210LHMHG Specifications

Manufacturer Part NumberSS210LHMHGManufacturerTSC America Inc.CategoryDiscrete Semiconductor ProductsDiodes - Rectifiers - SinglePackageDO-219ABSeriesAutomotive, AEC-Q101Diode TypeSchottkyVoltage - DC Reverse (Vr) (Max)100VCurrent - Average Rectified I(o)2AVoltage - Forward (Vf) (Max) @ If850mV @ 2ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr100µA @ 100VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseDo-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C		
CategoryDiscrete Semiconductor Products Diodes - Rectifiers - SinglePackageDO-219ABSeriesAutomotive, AEC-Q101Diode TypeSchottkyVoltage - DC Reverse (Vr) (Max)100VCurrent - Average Rectified (Io)2AVoltage - Forward (Vf) (Max) @ If850mV @ 2ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr100µA @ 100VCurge - Reverse Leakage @ Vr5.00nL @ 00VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Manufacturer Part Number	SS210LHMHG
Diodes - Rectifiers - SinglePackageDO-219ABSeriesAutomotive, AEC-Q101Diode TypeSchottkyVoltage - DC Reverse (Vr) (Max)100VCurrent - Average Rectified (Jo)2AVoltage - Forward (Vf) (Max) @ If850mV @ 2ASpeedFast Recovery =< 500ns, > 200mA (Jo)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr100µA @ 100VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Manufacturer	TSC America Inc.
PackageDO-219ABSeriesAutomotive, AEC-Q101Diode TypeSchottkyVoltage - DC Reverse (Vr) (Max)100VCurrent - Average Rectified (Io)2AVoltage - Forward (Vf) (Max) @ If850mV @ 2ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr100µA @ 100VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Category	Discrete Semiconductor Products
SeriesAutomotive, AEC-Q101Diode TypeSchottkyVoltage - DC Reverse (Vr) (Max)100VCurrent - Average Rectified (Io)2AVoltage - Forward (Vf) (Max) @ If $850mV @ 2A$ SpeedFast Recovery =< $500ms, > 200mA$ (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr $100\muA @ 100V$ Capacitance @ Vr, F.Mounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction $-5°C \sim 150°C$		Diodes - Rectifiers - Single
Diode TypeSchottkyVoltage - DC Reverse (Vr) (Max)100VCurrent - Average Rectified (Io)2AVoltage - Forward (Vf) (Max) @ If850mV @ 2ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr100µA @ 100VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Package	DO-219AB
Voltage - DC Reverse (Vr) (Max)100VCurrent - Average Rectified (Io)2AVoltage - Forward (Vf) (Max) @ If $850mV @ 2A$ SpeedFast Recovery =< $500ns$, > $200mA$ (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr $100\muA @ 100V$ Capacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Series	Automotive, AEC-Q101
Current - Average Rectified (Io)2AVoltage - Forward (Vf) (Max) @ If850mV @ 2ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr100μA @ 100VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Diode Type	Schottky
Voltage - Forward (Vf) (Max) @ If $850mV @ 2A$ SpeedFast Recovery =< $500ns$, > $200mA$ (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr $100\muA @ 100V$ Capacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Voltage - DC Reverse (Vr) (Max)	100V
Speed Fast Recovery = < 500ns, > 200mA (Io) Reverse Recovery Time (trr) - Current - Reverse Leakage @ Vr 100μA @ 100V Capacitance @ Vr, F - Mounting Type Surface Mount Package / Case DO-219AB Supplier Device Package Sub SMA Operating Temperature - Junction -55°C ~ 150°C	Current - Average Rectified (Io)	2A
Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr100μA @ 100VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Voltage - Forward (Vf) (Max) @ If	850mV @ 2A
Current - Reverse Leakage @ Vr100μA @ 100VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Speed	Fast Recovery =< 500ns, > 200mA (Io)
Capacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Reverse Recovery Time (trr)	-
Mounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Current - Reverse Leakage @ Vr	100µA @ 100V
Package / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Capacitance @ Vr, F	-
Supplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Mounting Type	Surface Mount
Operating Temperature - Junction $-55^{\circ}C \sim 150^{\circ}C$	Package / Case	DO-219AB
	Supplier Device Package	Sub SMA
Report errors ⁶	Operating Temperature - Junction	-55°C ~ 150°C
		Report errors?

SS210LHMHG Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

SS210LHMHG Payment Methods





If you have any question about SS210LHMHG, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com