

SS26-M3/52T Information



For Reference Only

Part Number SS26-M3/52T

Manufacturer Vishay Semiconductor Diodes Division

Category Discrete Semiconductor Products

Diodes - Rectifiers - Single

Description DIODE SCHOTTKY 2A 60V DO-214AA

Package DO-214AA, SMB

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SS26-M3/52T Specifications

Manufacturer Part NumberSS26-M3/52TManufacturerVishay Semiconductor Diodes DivisionCategoryDiscrete Semiconductor ProductsDiodes - Rectifiers - SinglePackageDO-214AA, SMBSeries-Diode TypeSchottkyVoltage - DC Reverse (Vr) (Max)60VCurrent - Average Rectified (Io)2AVoltage - Forward (Vf) (Max) @ If700mV @ 2ASpeedFast Recovery = < 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr400μA @ 60VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseDO-214AA, SMBSupplier Device PackageDO-214AA (SMB)Operating Temperature - Junction-65°C ~ 150°CReport errors?	SS20 M20/021 Specifications	
Category Discrete Semiconductor Products Diodes - Rectifiers - Single DO-214AA, SMB Series Diode Type Schottky Voltage - DC Reverse (Vr) (Max) Current - Average Rectified (Io) Voltage - Forward (Vf) (Max) @ If To0mV @ 2A Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) - Current - Reverse Leakage @ Vr Capacitance @ Vr, F Mounting Type Surface Mount Package / Case DO-214AA, SMB Supplier Device Package DO-214AA (SMB) Operating Temperature - Junction	Manufacturer Part Number	SS26-M3/52T
PackageDiodes - Rectifiers - SingleSeries-Diode TypeSchottkyVoltage - DC Reverse (Vr) (Max)60VCurrent - Average Rectified (Io)2AVoltage - Forward (Vf) (Max) @ If700mV @ 2ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr400μA @ 60VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseDO-214AA, SMBSupplier Device PackageDO-214AA (SMB)Operating Temperature - Junction-65°C ~ 150°C	Manufacturer	Vishay Semiconductor Diodes Division
PackageDO-214AA, SMBSeries-Diode TypeSchottkyVoltage - DC Reverse (Vr) (Max)60VCurrent - Average Rectified (Io)2AVoltage - Forward (Vf) (Max) @ If700mV @ 2ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr400μA @ 60VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseDO-214AA, SMBSupplier Device PackageDO-214AA (SMB)Operating Temperature - Junction-65°C ~ 150°C	Category	Discrete Semiconductor Products
Series-Diode TypeSchottkyVoltage - DC Reverse (Vr) (Max)60VCurrent - Average Rectified (Io)2AVoltage - Forward (Vf) (Max) @ If700mV @ 2ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr400μA @ 60VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseDO-214AA, SMBSupplier Device PackageDO-214AA (SMB)Operating Temperature - Junction-65°C ~ 150°C		Diodes - Rectifiers - Single
Diode TypeSchottkyVoltage - DC Reverse (Vr) (Max)60VCurrent - Average Rectified (Io)2AVoltage - Forward (Vf) (Max) @ If700mV @ 2ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr400μA @ 60VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseDO-214AA, SMBSupplier Device PackageDO-214AA (SMB)Operating Temperature - Junction-65°C ~ 150°C	Package	DO-214AA, SMB
Voltage - DC Reverse (Vr) (Max)60VCurrent - Average Rectified (Io)2AVoltage - Forward (Vf) (Max) @ If700mV @ 2ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr400μA @ 60VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseDO-214AA, SMBSupplier Device PackageDO-214AA (SMB)Operating Temperature - Junction-65°C ~ 150°C	Series	-
Current - Average Rectified (Io) Voltage - Forward (Vf) (Max) @ If 700mV @ 2A Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) - Current - Reverse Leakage @ Vr Capacitance @ Vr, F Mounting Type Surface Mount Package / Case DO-214AA, SMB Supplier Device Package Operating Temperature - Junction 2A 700mV @ 2A 700mV @ 2A Fast Recovery =< 500ns, > 200mA (Io) - 500 400µA @ 60V - 500 500 500 500 500 500 500	Diode Type	Schottky
Voltage - Forward (Vf) (Max) @ If Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) - Current - Reverse Leakage @ Vr Capacitance @ Vr, F Mounting Type Surface Mount Package / Case DO-214AA, SMB Supplier Device Package DO-214AA (SMB) Operating Temperature - Junction 700mV @ 2A 700mV @ 2A 700mV @ 2A 700mV @ 2A Fast Recovery =< 500ns, > 200mA (Io) - 000 - 000	Voltage - DC Reverse (Vr) (Max)	60V
SpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr400μA @ 60VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseDO-214AA, SMBSupplier Device PackageDO-214AA (SMB)Operating Temperature - Junction-65°C ~ 150°C	Current - Average Rectified (Io)	2A
Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr400μA @ 60VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseDO-214AA, SMBSupplier Device PackageDO-214AA (SMB)Operating Temperature - Junction-65°C ~ 150°C	Voltage - Forward (Vf) (Max) @ If	700mV @ 2A
Current - Reverse Leakage @ Vr400μA @ 60VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseDO-214AA, SMBSupplier Device PackageDO-214AA (SMB)Operating Temperature - Junction-65°C ~ 150°C	Speed	Fast Recovery =< 500ns, > 200mA (Io)
Capacitance @ Vr, F Mounting Type Surface Mount Package / Case DO-214AA, SMB Supplier Device Package DO-214AA (SMB) Operating Temperature - Junction -65°C ~ 150°C	Reverse Recovery Time (trr)	-
Mounting Type Surface Mount Package / Case DO-214AA, SMB Supplier Device Package DO-214AA (SMB) Operating Temperature - Junction -65°C ~ 150°C	Current - Reverse Leakage @ Vr	400μA @ 60V
Package / Case DO-214AA, SMB Supplier Device Package DO-214AA (SMB) Operating Temperature - Junction -65°C ~ 150°C	Capacitance @ Vr, F	-
Supplier Device Package DO-214AA (SMB) Operating Temperature - Junction -65°C ~ 150°C	Mounting Type	Surface Mount
Operating Temperature - Junction -65°C ~ 150°C	Package / Case	DO-214AA, SMB
	Supplier Device Package	DO-214AA (SMB)
Report errors?	Operating Temperature - Junction	-65°C ~ 150°C
		Report errors?

SS26-M3/52T Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SS26-M3/52T Payment Methods



















SS26-M3/52T Shipping Methods













If you have any question about SS26-M3/52T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com