

SS26L R3G Information

Heisener.com

Part Number SS26L R3G

Manufacturer TSC America Inc.

Category Discrete Semiconductor Products

Diodes - Rectifiers - Single

Description DIODE, SCHOTTKY, STANDARD, 2A, 6

Package DO-219AB

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SS26L R3G Specifications

Manufacturer Part NumberSS26L R3GManufacturerTSC America Inc.CategoryDiscrete Semiconductor ProductsDiodes - Rectifiers - SinglePackageDO-219ABSeries-Diode TypeSchottkyVoltage - DC Reverse (Vr) (Max)60VCurrent - Average Rectified (Io)2AVoltage - Forward (Vf) (Max) @ If700mV @ 2ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr400μA @ 60VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°CReport errors?	SS202 Ite o specifications	
Category Discrete Semiconductor Products Diodes - Rectifiers - Single DO-219AB Series - Diode Type Schottky Voltage - DC Reverse (Vr) (Max) Current - Average Rectified (Io) Voltage - Forward (Vf) (Max) @ If Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) - Current - Reverse Leakage @ Vr 400µA @ 60V Capacitance @ Vr, F Mounting Type Surface Mount Package / Case DO-219AB Supplier Device Package Sub SMA Operating Temperature - Junction DO-219AB Single Do-219AB Sub SMA Operating Temperature - Junction	Manufacturer Part Number	SS26L R3G
Diodes - Rectifiers - SinglePackageDO-219ABSeries-Diode TypeSchottkyVoltage - DC Reverse (Vr) (Max)60VCurrent - Average Rectified (Io)2AVoltage - Forward (Vf) (Max) @ If700mV @ 2ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr400μA @ 60VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Manufacturer	TSC America Inc.
Package DO-219AB Series - Diode Type Schottky Voltage - DC Reverse (Vr) (Max) 60V Current - Average Rectified (Io) 2A Voltage - Forward (Vf) (Max) @ If 700mV @ 2A Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) - Current - Reverse Leakage @ Vr 400µA @ 60V Capacitance @ Vr, F - Mounting Type Surface Mount Package / Case DO-219AB Supplier Device Package Sub SMA Operating Temperature - Junction -55°C ~ 150°C	Category	Discrete Semiconductor Products
Series Diode Type Schottky Voltage - DC Reverse (Vr) (Max) Current - Average Rectified (Io) Voltage - Forward (Vf) (Max) @ If ToomV @ 2A Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) - Current - Reverse Leakage @ Vr Capacitance @ Vr, F Mounting Type Surface Mount Package / Case DO-219AB Supplier Device Package Operating Temperature - Junction - Schottky 60V 2A 700mV @ 2A 700mV @ 2A 700mV @ 2A 800mA (Io) - Sub Sun Golv 400μA @ 60V - Surface Mount DO-219AB Supplier Device Package		Diodes - Rectifiers - Single
Diode TypeSchottkyVoltage - DC Reverse (Vr) (Max)60VCurrent - Average Rectified (Io)2AVoltage - Forward (Vf) (Max) @ If700mV @ 2ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr400μA @ 60VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Package	DO-219AB
Voltage - DC Reverse (Vr) (Max) Current - Average Rectified (Io) 2A Voltage - Forward (Vf) (Max) @ If 700mV @ 2A Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) - Current - Reverse Leakage @ Vr Capacitance @ Vr, F Mounting Type Surface Mount Package / Case DO-219AB Supplier Device Package Operating Temperature - Junction 60V 2A 700mV @ 2A Fast Recovery =< 500ns, > 200mA (Io) - Current - Current - Reverse Leakage @ Vr 400μA @ 60V - DO-219AB Supplier Device Package Operating Temperature - Junction -55°C ~ 150°C	Series	-
Current - Average Rectified (Io) Voltage - Forward (Vf) (Max) @ If 700mV @ 2A Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) - Current - Reverse Leakage @ Vr Capacitance @ Vr, F Mounting Type Surface Mount Package / Case Supplier Device Package Operating Temperature - Junction 2A 700mV @ 2A 700mV @ 2A Fast Recovery =< 500ns, > 200mA (Io) - Surface Mount DO-219AB Supplier Device Package Sub SMA -55°C ~ 150°C	Diode Type	Schottky
Voltage - Forward (Vf) (Max) @ If Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) - Current - Reverse Leakage @ Vr Capacitance @ Vr, F Mounting Type Surface Mount Package / Case DO-219AB Supplier Device Package Sub SMA Operating Temperature - Junction 700mV @ 2A 700mV @ 20 700mV	Voltage - DC Reverse (Vr) (Max)	60V
SpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr400μA @ 60VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Current - Average Rectified (Io)	2A
Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr400μA @ 60VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Voltage - Forward (Vf) (Max) @ If	700mV @ 2A
Current - Reverse Leakage @ Vr400μA @ 60VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Speed	Fast Recovery =< 500ns, > 200mA (Io)
Capacitance @ Vr, F Mounting Type Surface Mount Package / Case DO-219AB Supplier Device Package Sub SMA Operating Temperature - Junction -55°C ~ 150°C	Reverse Recovery Time (trr)	-
Mounting Type Surface Mount Package / Case DO-219AB Supplier Device Package Sub SMA Operating Temperature - Junction -55°C ~ 150°C	Current - Reverse Leakage @ Vr	400μA @ 60V
Package / Case DO-219AB Supplier Device Package Sub SMA Operating Temperature - Junction -55°C ~ 150°C	Capacitance @ Vr, F	-
Supplier Device Package Sub SMA Operating Temperature - Junction -55°C ~ 150°C	Mounting Type	Surface Mount
Operating Temperature - Junction -55°C ~ 150°C	Package / Case	DO-219AB
	Supplier Device Package	Sub SMA
Report errors?	Operating Temperature - Junction	-55°C ~ 150°C
		Report errors?

SS26L R3G Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SS26L R3G Payment Methods



















SS26L R3G Shipping Methods













If you have any question about SS26L R3G, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com