

# SS2FL4-M3/H

#### SS2FL4-M3/H Information

www.hordenet.com	Part Number	SS2FL4-M3/H	
	Manufacturer	Vishay Semiconductor Diodes Division	
	Category	Discrete Semiconductor Products Diodes - Rectifiers - Single	3.9774-94
	Description	DIODE SCHOTTKY 40V 2A DO-219AB	3.3.6.7
	Package	DO-219AB	
		For the pricing/inventory/lead time, please contact us	
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## SS2FL4-M3/H Specifications

Manufacturer Part NumberSS2FL4-M3/HManufacturerVishay Semiconductor Diodes DivisionCategoryDiscrete Semiconductor ProductsPackageDiodes - Rectifiers - SinglePackageDO-219ABSeriesAutomotive, AEC-Q101, eSMP?Diode TypeSchottkyVoltage - DC Reverse (Vr) (Max)40VCurrent - Average Rectified (Io)2ASpeedFast Recovery = < 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr20µA @ 40VCapacitance @ Vr, F125pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageDO-219ABSupplier Device PackageDO-219AB (SMF)Operating Temperature - Junction-55°C ~ 150°C		
CategoryDiscrete Semiconductor ProductsDiodes - Rectifiers - SinglePackageDO-219ABSeriesAutomotive, AEC-Q101, eSMP?Diode TypeSchottkyVoltage - DC Reverse (Vr) (Max)40VCurrent - Average Rectified (Jo)2AVoltage - Forward (Vf) (Max) @ If580mV @ 2ASpeedFast Recovery = <500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr220µA @ 40VCapacitance @ Vr, F125pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageDO-219AB (SMF)Operating Temperature - Junction-55°C ~ 150°C	Manufacturer Part Number	SS2FL4-M3/H
IndexDiodes - Rectifiers - SinglePackageDO-219ABSeriesAutomotive, AEC-Q101, eSMP?Diode TypeSchottkyVoltage - DC Reverse (Vr) (Max)40VCurrent - Average Rectified (Jo)2AVoltage - Forward (Vf) (Max) @ If580mV @ 2ASpeedFast Recovery =< 500ms, > 200mA (Jo)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr220µA @ 40VCapacitance @ Vr, F125pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageDO-219AB (SMF)Operating Temperature - Junction-55°C ~ 150°C	Manufacturer	Vishay Semiconductor Diodes Division
Package DO-219AB   Series Automotive, AEC-Q101, eSMP?   Diode Type Schottky   Voltage - DC Reverse (Vr) (Max) 40V   Current - Average Rectified (Io) 2A   Voltage - Forward (Vf) (Max) @ If 580mV @ 2A   Speed Fast Recovery = < 500ms, > 200mA (Io)   Reverse Recovery Time (trr) -   Current - Reverse Leakage @ Vr 220µA @ 40V   Capacitance @ Vr, F 125pF @ 4V, 1MHz   Mounting Type Surface Mount   Package / Case DO-219AB   Supplier Device Package DO-219AB   Operating Temperature - Junction -	Category	Discrete Semiconductor Products
SeriesAutomotive, AEC-Q101, eSMP?SeriesSchottkyDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)40VCurrent - Average Rectified (Io)2AVoltage - Forward (Vf) (Max) @ If580mV @ 2ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr220 $\mu$ A @ 40VCapacitance @ Vr, F125pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageDO-219AB (SMF)Operating Temperature - Junction-55°C ~ 150°C		Diodes - Rectifiers - Single
Diode TypeSchottkyVoltage - DC Reverse (Vr) (Max) $40V$ Current - Average Rectified (Jo) $2A$ Voltage - Forward (Vf) (Max) @ If $580mV @ 2A$ SpeedFast Recovery =< $500ns$ , > $200mA$ (Jo)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr $220\muA @ 40V$ Capacitance @ Vr, F $125pF @ 4V$ , 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageDO-219AB (SMF)Operating Temperature - Junction $-55^{\circ}C \sim 150^{\circ}C$	Package	DO-219AB
Voltage - DC Reverse (Vr) (Max)40VCurrent - Average Rectified (Io)2AVoltage - Forward (Vf) (Max) @ If580mV @ 2ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr220 $\mu$ A @ 40VCapacitance @ Vr, F125pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageDO-219AB (SMF)Operating Temperature - Junction-55°C ~ 150°C	Series	Automotive, AEC-Q101, eSMP?
Current - Average Rectified (Io) $2A$ Voltage - Forward (Vf) (Max) @ If $580mV @ 2A$ SpeedFast Recovery =< $500ns$ , > $200mA$ (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr $220\muA @ 40V$ Capacitance @ Vr, F $125pF @ 4V$ , $1MHz$ Mounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageDO-219AB (SMF)Operating Temperature - Junction $-55^{\circ}C \sim 150^{\circ}C$	Diode Type	Schottky
Voltage - Forward (Vf) (Max) @ If $580mV @ 2A$ SpeedFast Recovery =< $500ns$ , > $200mA$ (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr $220\muA @ 40V$ Capacitance @ Vr, F $125pF @ 4V$ , $1MHz$ Mounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageDO-219AB (SMF)Operating Temperature - Junction $-55^{\circ}C \sim 150^{\circ}C$	Voltage - DC Reverse (Vr) (Max)	40V
SpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr220µA @ 40VCapacitance @ Vr, F125pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageDO-219AB (SMF)Operating Temperature - Junction-55°C ~ 150°C	Current - Average Rectified (Io)	2A
Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr220μA @ 40VCapacitance @ Vr, F125pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageDO-219AB (SMF)Operating Temperature - Junction-55°C ~ 150°C	Voltage - Forward (Vf) (Max) @ If	580mV @ 2A
Current - Reverse Leakage @ Vr220μA @ 40VCapacitance @ Vr, F125pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageDO-219AB (SMF)Operating Temperature - Junction-55°C ~ 150°C	Speed	Fast Recovery =< 500ns, > 200mA (Io)
Capacitance @ Vr, F125pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageDO-219AB (SMF)Operating Temperature - Junction-55°C ~ 150°C	Reverse Recovery Time (trr)	-
Mounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageDO-219AB (SMF)Operating Temperature - Junction-55°C ~ 150°C	Current - Reverse Leakage @ Vr	220µA @ 40V
Package / CaseDO-219ABSupplier Device PackageDO-219AB (SMF)Operating Temperature - Junction-55°C ~ 150°C	Capacitance @ Vr, F	125pF @ 4V, 1MHz
Supplier Device PackageDO-219AB (SMF)Operating Temperature - Junction-55°C ~ 150°C	Mounting Type	Surface Mount
Operating Temperature - Junction -55°C ~ 150°C	Package / Case	DO-219AB
	Supplier Device Package	DO-219AB (SMF)
Report error	Operating Temperature - Junction	-55°C ~ 150°C
Report the		Report errors?

#### SS2FL4-M3/H Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE GUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

# SS2FL4-M3/H Payment Methods



## SS2FL4-M3/H Shipping Methods



If you have any question about SS2FL4-M3/H, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com