

SS34LHMQG

quest a Quote

SS34LHMQG Information

For Reference Only	Part Number	SS34LHMQG
	Manufacturer	TSC America Inc.
	Category	Discrete Semiconductor Products Diodes - Rectifiers - Single
	Description	DIODE, SCHOTTKY, STANDARD, 3A, 4
	Package	DO-219AB
		For the pricing/inventory/lead time, please contact us
		Website: https://www.heisener.com E-mail: salesdept@heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



SS34LHMQG Specifications

Manufacturer Part NumberSS34LHMQGManufacturerTSC America Inc.CategoryDiscrete Semiconductor ProductsPackageDiodes - Rectifiers - SinglePackageOO-219ABSeriesAutomotive, AEC-Q101Diode TypeSchottkyVoltage - DC Reverse (Vr) (Max)40VCurrent - Average Rectified (Jo)3ASpeedFast Recovery =< 500ns, > 200mA (Jo)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr500µA @ 40VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseDo-219ABSupplier Device PackageSurface MountOperating Temperature - Junction-Store To CaseSub SMAOperating Temperature - Supplier Device PackageSub SMAOperating Temperature - Supplier Device PackageSupplier Device PackageOperating Temperature - Supplier Device Pack		
CategoryDiscrete Semiconductor ProductsDiodes - Rectifiers - SinglePackageDO-219ABSeriesAutomotive, AEC-Q101Diode TypeSchottkyVoltage - DC Reverse (Vr) (Max)40VCurrent - Average Rectified (Io)3AVoltage - Forward (Vf) (Max) @ If500mV @ 3ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr500µA @ 40VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 125°C	Manufacturer Part Number	SS34LHMQG
Index serverDiodes - Rectifiers - SinglePackageDO-219ABSeriesAutomotive, AEC-Q101Diode TypeSchottkyVoltage - DC Reverse (Vr) (Max)40VCurrent - Average Rectified (Jo)3AVoltage - Forward (Vf) (Max) @ If500mV @ 3ASpeedFast Recovery =< 500ns, > 200mA (Jo)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr500μA @ 40VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 125°C	Manufacturer	TSC America Inc.
PackageDO-219ABSeriesAutomotive, AEC-Q101Diode TypeSchottkyVoltage - DC Reverse (Vr) (Max)40VCurrent - Average Rectified (Io)3AVoltage - Forward (Vf) (Max) @ If500mV @ 3ASpeedFast Recovery =< 500ms, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr500µA @ 40VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 125°C	Category	Discrete Semiconductor Products
SeriesAutomotive, AEC-Q101Diode TypeSchottkyVoltage - DC Reverse (Vr) (Max)40VCurrent - Average Rectified (Io)3AVoltage - Forward (Vf) (Max) @ If500mV @ 3ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr500µA @ 40VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 125°C		Diodes - Rectifiers - Single
Diode TypeSchottkyVoltage - DC Reverse (Vr) (Max) $40V$ Current - Average Rectified (Io) $3A$ Voltage - Forward (Vf) (Max) @ If $500mV @ 3A$ SpeedFast Recovery =< $500ns$, > $200mA$ (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr $500\muA @ 40V$ Capacitance @ Vr, F $500\muA @ 40V$ Mounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction $-55°C ~ 125°C$	Package	DO-219AB
Voltage - DC Reverse (Vr) (Max)40VCurrent - Average Rectified (Io) $3A$ Voltage - Forward (Vf) (Max) @ If $500mV @ 3A$ SpeedFast Recovery =< $500ns, > 200mA$ (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr $500\muA @ 40V$ Capacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction $-55°C ~ 125°C$	Series	Automotive, AEC-Q101
Current - Average Rectified (Io)3AVoltage - Forward (Vf) (Max) @ If500mV @ 3ASpeedFast Recovery = < 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr500µA @ 40VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 125°C	Diode Type	Schottky
Voltage - Forward (Vf) (Max) @ If $500mV @ 3A$ SpeedFast Recovery =< $500ns$, > $200mA$ (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr $500\muA @ 40V$ Capacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction -55° C ~ 125° C	Voltage - DC Reverse (Vr) (Max)	40V
SpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr500µA @ 40VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 125°C	Current - Average Rectified (Io)	3A
Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr500µA @ 40VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 125°C	Voltage - Forward (Vf) (Max) @ If	500mV @ 3A
Current - Reverse Leakage @ Vr500µA @ 40VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 125°C	Speed	Fast Recovery =< 500ns, > 200mA (Io)
Capacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 125°C	Reverse Recovery Time (trr)	-
Mounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 125°C	Current - Reverse Leakage @ Vr	500µA @ 40V
Package / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 125°C	Capacitance @ Vr, F	-
Supplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 125°C	Mounting Type	Surface Mount
Operating Temperature - Junction -55°C ~ 125°C	Package / Case	DO-219AB
	Supplier Device Package	Sub SMA
Report error	Operating Temperature - Junction	-55°C ~ 125°C
		Report errors?

SS34LHMQG Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

SS34LHMQG Payment Methods



SS34LHMQG Shipping Methods



If you have any question about SS34LHMQG, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com