

SS3P3-M3/85A Information



For Reference Only

Part Number SS3P3-M3/85A

Manufacturer Vishay Semiconductor Diodes Division

Category Discrete Semiconductor Products

Diodes - Rectifiers - Single

Description DIODE SCHOTTKY 30V 3A TO277A

Package TO-277, 3-PowerDFN

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SS3P3-M3/85A Specifications

Manufacturer Part NumberSS3P3-M3/85AManufacturerVishay Semiconductor Diodes DivisionCategoryDiscrete Semiconductor ProductsDiodes - Rectifiers - SinglePackageTO-277, 3-PowerDFNSerieseSMP?Diode TypeSchottkyVoltage - DC Reverse (Vr) (Max)30VCurrent - Average Rectified (Io)3AVoltage - Forward (Vf) (Max) @ If580mV @ 3ASpeedFast Recovery = < 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr200μA @ 30VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-277, 3-PowerDFNSupplier Device PackageTO-277A (SMPC)Operating Temperature - Junction-55°C ~ 150°CReport errors?	SSCI C 1/20/0011 Specifications	
Category Discrete Semiconductor Products Diodes - Rectifiers - Single TO-277, 3-PowerDFN Series ESMP? Diode Type Schottky Voltage - DC Reverse (Vr) (Max) Current - Average Rectified (Io) Voltage - Forward (Vf) (Max) @ If S80mV @ 3A Speed Fast Recovery = < 500ns, > 200mA (Io) Reverse Recovery Time (trr) - Current - Reverse Leakage @ Vr Capacitance @ Vr, F Mounting Type Surface Mount Package / Case TO-277, 3-PowerDFN Supplier Device Package TO-277A (SMPC) Operating Temperature - Junction	Manufacturer Part Number	SS3P3-M3/85A
PackageDiodes - Rectifiers - SinglePackageTO-277, 3-PowerDFNSerieseSMP?Diode TypeSchottkyVoltage - DC Reverse (Vr) (Max)30VCurrent - Average Rectified (Io)3AVoltage - Forward (Vf) (Max) @ If580mV @ 3ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr200μA @ 30VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-277, 3-PowerDFNSupplier Device PackageTO-277A (SMPC)Operating Temperature - Junction-55°C ~ 150°C	Manufacturer	Vishay Semiconductor Diodes Division
Package TO-277, 3-PowerDFN Series eSMP? Diode Type Schottky Voltage - DC Reverse (Vr) (Max) 30V Current - Average Rectified (Io) 3A Voltage - Forward (Vf) (Max) @ If 580mV @ 3A Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) - Current - Reverse Leakage @ Vr 200µA @ 30V Capacitance @ Vr, F - Mounting Type Surface Mount Package / Case TO-277, 3-PowerDFN Supplier Device Package TO-277A (SMPC) Operating Temperature - Junction -55°C ~ 150°C	Category	Discrete Semiconductor Products
SerieseSMP?Diode TypeSchottkyVoltage - DC Reverse (Vr) (Max)30VCurrent - Average Rectified (Io)3AVoltage - Forward (Vf) (Max) @ If580mV @ 3ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr200μA @ 30VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-277, 3-PowerDFNSupplier Device PackageTO-277A (SMPC)Operating Temperature - Junction-55°C ~ 150°C		Diodes - Rectifiers - Single
Diode TypeSchottkyVoltage - DC Reverse (Vr) (Max)30VCurrent - Average Rectified (Io)3AVoltage - Forward (Vf) (Max) @ If580mV @ 3ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr200μA @ 30VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-277, 3-PowerDFNSupplier Device PackageTO-277A (SMPC)Operating Temperature - Junction-55°C ~ 150°C	Package	TO-277, 3-PowerDFN
Voltage - DC Reverse (Vr) (Max) Current - Average Rectified (Io) 3A Voltage - Forward (Vf) (Max) @ If 580mV @ 3A Speed Fast Recovery = < 500ns, > 200mA (Io) Reverse Recovery Time (trr) - Current - Reverse Leakage @ Vr 200μA @ 30V Capacitance @ Vr, F Mounting Type Surface Mount Package / Case TO-277, 3-PowerDFN Supplier Device Package TO-277A (SMPC) Operating Temperature - Junction 30V 30V 580mV @ 3A Fast Recovery = < 500ns, > 200mA (Io) - 580mV @ 3A Fast Recovery = < 500ns, > 200mA (Io) - 570mA (Io) - 570mA (Io) 570mA (Io)	Series	eSMP?
Current - Average Rectified (Io) Voltage - Forward (Vf) (Max) @ If 580mV @ 3A Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) - Current - Reverse Leakage @ Vr Capacitance @ Vr, F Mounting Type Surface Mount Package / Case TO-277, 3-PowerDFN Supplier Device Package TO-277A (SMPC) Operating Temperature - Junction	Diode Type	Schottky
Voltage - Forward (Vf) (Max) @ If Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) - Current - Reverse Leakage @ Vr 200µA @ 30V Capacitance @ Vr, F Mounting Type Surface Mount Package / Case TO-277, 3-PowerDFN Supplier Device Package TO-277A (SMPC) Operating Temperature - Junction 580mV @ 3A 580mV @ 3A Fast Recovery =< 500ns, > 200mA (Io) - TO-277A (SMPC) -55°C ~ 150°C	Voltage - DC Reverse (Vr) (Max)	30V
SpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr200μA @ 30VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-277, 3-PowerDFNSupplier Device PackageTO-277A (SMPC)Operating Temperature - Junction-55°C ~ 150°C	Current - Average Rectified (Io)	3A
Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr200μA @ 30VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-277, 3-PowerDFNSupplier Device PackageTO-277A (SMPC)Operating Temperature - Junction-55°C ~ 150°C	Voltage - Forward (Vf) (Max) @ If	580mV @ 3A
Current - Reverse Leakage @ Vr Capacitance @ Vr, F Mounting Type Surface Mount Package / Case TO-277, 3-PowerDFN Supplier Device Package TO-277A (SMPC) Operating Temperature - Junction 200µA @ 30V -55°C ~ 150°C	Speed	Fast Recovery =< 500ns, > 200mA (Io)
Capacitance @ Vr, F Mounting Type Surface Mount Package / Case TO-277, 3-PowerDFN Supplier Device Package TO-277A (SMPC) Operating Temperature - Junction -55°C ~ 150°C	Reverse Recovery Time (trr)	-
Mounting Type Surface Mount Package / Case TO-277, 3-PowerDFN Supplier Device Package TO-277A (SMPC) Operating Temperature - Junction -55°C ~ 150°C	Current - Reverse Leakage @ Vr	200μA @ 30V
Package / Case TO-277, 3-PowerDFN Supplier Device Package TO-277A (SMPC) Operating Temperature - Junction -55°C ~ 150°C	Capacitance @ Vr, F	-
Supplier Device Package TO-277A (SMPC) Operating Temperature - Junction -55°C ~ 150°C	Mounting Type	Surface Mount
Operating Temperature - Junction -55°C ~ 150°C	Package / Case	TO-277, 3-PowerDFN
	Supplier Device Package	TO-277A (SMPC)
Report errors?	Operating Temperature - Junction	-55°C ~ 150°C
		Report errors?

SS3P3-M3/85A Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SS3P3-M3/85A Payment Methods





















SS3P3-M3/85A Shipping Methods













If you have any question about SS3P3-M3/85A, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com