

SS3P4-M3/85A

SS3P4-M3/85A Information

www.heisener.com	Part Number Manufacturer Category Description	SS3P4-M3/85A Vishay Semiconductor Diodes Division Discrete Semiconductor Products Diodes - Rectifiers - Single DIODE SCHOTTKY 40V 3A DO220AA	
	Package	DO-220AA For the pricing/inventory/lead time, please contact us	
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



SS3P4-M3/85A Specifications

Manufacturer Part NumberSS3P4-M3/85AManufacturerVishay Semiconductor Diodes DivisionCategoryDiscrete Semiconductor ProductsDiodes - Rectifiers - SingleDiodes - Rectifiers - SinglePackageDO-220AASerieseSMP?Diodar TypeSchottkyVoltage - DC Reverse (Vr) (Max)40VCurrent - Average Rectified I(o)3AVoltage - Forward (Vf) (Max) @ If600mV @ 3ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr150µA @ 40VCapacitance @ Vr, F130pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-220AASupplier Device PackageDO-220AA (SMP)Operating Temperature - Junction-S5°C ~ 150°C		
CategoryDiscrete Semiconductor ProductsDiodes - Rectifiers - SinglePackageDO-220AASerieseSMP?Diode TypeSchottkyVoltage - DC Reverse (Vr) (Max)40VCurrent - Average Rectified (Io)3AVoltage - Forward (Vf) (Max) @ If600mV @ 3ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr150µA @ 40VCurrent - Reverse Leakage @ Vr130pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-220AASupplier Device PackageDO-220AA (SMP)Operating Temperature - Junction-55°C ~ 150°C	Manufacturer Part Number	SS3P4-M3/85A
Diodes - Rectifiers - SinglePackageDO-220AASerieseSMP?Diode TypeSchottkyVoltage - DC Reverse (Vr) (Max)40VCurrent - Average Rectified (Jo)3AVoltage - Forward (Vf) (Max) @ If600mV @ 3ASpeedFast Recovery =< 500ns, > 200mA (Jo)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr150µA @ 40VCurrent - Reverse Leakage @ Vr130pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-220AASupplier Device PackageDO-220AA (SMP)Operating Temperature - Junction-55°C ~ 150°C	Manufacturer	Vishay Semiconductor Diodes Division
PackageDO-220AASerieseSMP?Diode TypeSchottkyVoltage - DC Reverse (Vr) (Max)40VCurrent - Average Rectified (Io)3AVoltage - Forward (Vf) (Max) @ If600mV @ 3ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr150µA @ 40VCapacitance @ Vr, F130pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-220AASupplier Device PackageDO-220AA (SMP)Operating Temperature - Junction-55°C ~ 150°C	Category	Discrete Semiconductor Products
Series eSMP? Diode Type Schottky Voltage - DC Reverse (Vr) (Max) 40V Current - Average Rectified (Jo) 3A Voltage - Forward (Vf) (Max) @ If 600mV @ 3A Speed Fast Recovery =< 500ns, > 200mA (Jo) Reverse Recovery Time (trr) - Current - Reverse Leakage @ Vr 150µA @ 40V Capacitance @ Vr, F 130pF @ 4V, 1MHz Mounting Type Surface Mount Package / Case DO-220AA Supplier Device Package DO-220AA (SMP)		Diodes - Rectifiers - Single
Diode TypeSchottkyVoltage - DC Reverse (Vr) (Max)40VCurrent - Average Rectified (Jo)3AVoltage - Forward (Vf) (Max) @ If600mV @ 3ASpeedFast Recovery =< 500ns, > 200mA (Jo)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr150µA @ 40VCapacitance @ Vr, F130pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-220AASupplier Device PackageDO-220AA (SMP)Operating Temperature - Junction-55°C ~ 150°C	Package	DO-220AA
Voltage - DC Reverse (Vr) (Max)40VCurrent - Average Rectified (Io) $3A$ Current - Average Rectified (Io) $600mV @ 3A$ Voltage - Forward (Vf) (Max) @ If $600mV @ 3A$ SpeedFast Recovery =< $500ns$, > $200mA$ (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr $150\muA @ 40V$ Capacitance @ Vr, F $130pF @ 4V$, $1MHz$ Mounting TypeSurface MountPackage / CaseDO-220AASupplier Device PackageDO-220AA (SMP)Operating Temperature - Junction $-55°C ~ 150°C$	Series	eSMP?
Current - Average Rectified (Io) $3A$ Voltage - Forward (Vf) (Max) @ If $600mV @ 3A$ SpeedFast Recovery $= 500ns, > 200mA$ (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr $150\muA @ 40V$ Capacitance @ Vr, F $130pF @ 4V, 1MHz$ Mounting TypeSurface MountPackage / CaseDO-220AASupplier Device PackageDO-220AA (SMP)Operating Temperature - Junction $-55^\circC \sim 150^\circC$	Diode Type	Schottky
Voltage - Forward (Vf) (Max) @ If $600mV @ 3A$ SpeedFast Recovery =< $500ns$, > $200mA$ (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr $150\muA @ 40V$ Capacitance @ Vr, F $130pF @ 4V$, $1MHz$ Mounting TypeSurface MountPackage / CaseDO-220AASupplier Device PackageDO-220AA (SMP)Operating Temperature - Junction $-55^\circ C \sim 150^\circ C$	Voltage - DC Reverse (Vr) (Max)	40V
SpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr150µA @ 40VCapacitance @ Vr, F130pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-220AASupplier Device PackageDO-220AA (SMP)Operating Temperature - Junction-55°C ~ 150°C	Current - Average Rectified (Io)	3A
Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr150µA @ 40VCapacitance @ Vr, F130pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-220AASupplier Device PackageDO-220AA (SMP)Operating Temperature - Junction-55°C ~ 150°C	Voltage - Forward (Vf) (Max) @ If	600mV @ 3A
Current - Reverse Leakage @ Vr150µA @ 40VCapacitance @ Vr, F130pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-220AASupplier Device PackageDO-220AA (SMP)Operating Temperature - Junction-55°C ~ 150°C	Speed	Fast Recovery =< 500ns, > 200mA (Io)
Capacitance @ Vr, F130pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-220AASupplier Device PackageDO-220AA (SMP)Operating Temperature - Junction-55°C ~ 150°C	Reverse Recovery Time (trr)	-
Mounting TypeSurface MountPackage / CaseDO-220AASupplier Device PackageDO-220AA (SMP)Operating Temperature - Junction-55°C ~ 150°C	Current - Reverse Leakage @ Vr	150µA @ 40V
Package / CaseDO-220AASupplier Device PackageDO-220AA (SMP)Operating Temperature - Junction-55°C ~ 150°C	Capacitance @ Vr, F	130pF @ 4V, 1MHz
Supplier Device PackageDO-220AA (SMP)Operating Temperature - Junction-55°C ~ 150°C	Mounting Type	Surface Mount
Operating Temperature - Junction $-55^{\circ}C \sim 150^{\circ}C$	Package / Case	DO-220AA
	Supplier Device Package	DO-220AA (SMP)
Report errors?	Operating Temperature - Junction	-55°C ~ 150°C
		Report errors?

SS3P4-M3/85A Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE SUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DISCOVER

SS3P4-M3/85A Payment Methods WIRE transfer PayPal Western Of MoneyGram Alipay: VISA Money SS3P4-M3/85A Shipping Methods



If you have any question about SS3P4-M3/85A, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com