

SSCDANN250MGAA3

SSCDANN250MGAA3 Information



For Reference Only

Part Number SSCDANN250MGAA3

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

DescriptionBRD MNT PRESSURE SENSORSPackage8-DIP (0.524", 13.30mm), Top Port

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SSCDANN250MGAA3 Specifications

Manufacturer Part NumberSSCDANN250MGAA3ManufacturerHoneywell Sensing and Productivity SolutionsCategorySensors, TransducersPressure Sensors, TransducersPackage8-DIP (0.524", 13.30mm), Top PortSeriesTruStability? SSCPressure TypeVented GaugeOperating Pressure3.63 PSI (25 kPa)Output TypeAnalog VoltageOutput0.33 V ~ 2.97 V
Category Sensors, Transducers Pressure Sensors, Transducers Package 8-DIP (0.524", 13.30mm), Top Port Series TruStability? SSC Pressure Type Vented Gauge Operating Pressure 3.63 PSI (25 kPa) Output Type Analog Voltage Output 0.33 V ~ 2.97 V
Pressure Sensors, Transducers Package 8-DIP (0.524", 13.30mm), Top Port Series TruStability? SSC Pressure Type Vented Gauge Operating Pressure 3.63 PSI (25 kPa) Output Type Analog Voltage Output 0.33 V ~ 2.97 V
Package8-DIP $(0.524", 13.30 mm)$, Top PortSeriesTruStability? SSCPressure TypeVented GaugeOperating Pressure $3.63 \text{ PSI } (25 \text{ kPa})$ Output TypeAnalog VoltageOutput $0.33 \text{ V} \sim 2.97 \text{ V}$
SeriesTruStability? SSCPressure TypeVented GaugeOperating Pressure 3.63 PSI $(25$ kPa)Output TypeAnalog VoltageOutput 0.33 V ~ 2.97 V
Pressure TypeVented GaugeOperating Pressure $3.63 \text{ PSI } (25 \text{ kPa})$ Output TypeAnalog VoltageOutput $0.33 \text{ V} \sim 2.97 \text{ V}$
Operating Pressure $3.63 \text{ PSI } (25 \text{ kPa})$ Output Type Analog Voltage Output $0.33 \text{ V} \sim 2.97 \text{ V}$
Output Type Analog Voltage Output $0.33 \text{ V} \sim 2.97 \text{ V}$
Output 0.33 V ~ 2.97 V
Accuracy $\pm 0.25\%$
Voltage - Supply $3 \text{ V} \sim 3.6 \text{ V}$
Port Size Male - 0.19" (4.93mm) Tube
Port Style Barbed
Features Amplified Output, Temperature Compensated
Termination Style PC Pin
Maximum Pressure 20.31 PSI (140 kPa)
Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$
Package / Case 8-DIP (0.524", 13.30mm), Top Port
Supplier Device Package 8-DIP
Report error

SSCDANN250MGAA3 Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SSCDANN250MGAA3 Payment Methods



















SSCDANN250MGAA3 Shipping Methods













If you have any question about SSCDANN250MGAA3, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com