

# SSCDJJN040MDAA5

### SSCDJJN040MDAA5 Information

Heisener.com

Part Number SSCDJJN040MDAA5

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

**Description** BRD MNT PRESSURE SENSORS

Package 8-DIP (0.524", 13.30mm), Dual Ports, Same Side

For the pricing/inventory/lead time, please contact

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# SSCDJJN040MDAA5 Specifications

Manufacturer Part Number       SSCDJJN040MDAA5         Manufacturer       Honeywell Sensing and Productivity Solutions         Category       Sensors, Transducers         Package       8-DIP (0.524", 13.30mm), Dual Ports, Same Side         Series       TruStability? SSC         Pressure Type       Differential         Operating Pressure       ±0.58 PSI (±4 kPa)         Output Type       Analog Voltage         Output       0.5 V ~ 4.5 V         Accuracy       ±0.25%         Voltage - Supply       4.95 V ~ 5.05 V         Port Size       Male - 0.09" (2.34mm) Tube, Dual         Port Style       Barbless         Features       Amplified Output, Temperature Compensated         Termination Style       PC Pin         Maximum Pressure       ±12.33 PSI (±85 kPa)         Operating Temperature       -40°C ~ 85°C         Package / Case       8-DIP (0.524", 13.30mm), Dual Ports, Same Side         Supplier Device Package       8-DIP			
CategorySensors, TransducersPackage8-DIP (0.524", 13.30mm), Dual Ports, Same SideSeriesTruStability? SSCPressure TypeDifferentialOperating Pressure±0.58 PSI (±4 kPa)Output TypeAnalog VoltageOutput0.5 V ~ 4.5 VAccuracy±0.25%Voltage - Supply4.95 V ~ 5.05 VPort SizeMale - 0.09" (2.34mm) Tube, DualPort StyleBarblessFeaturesAmplified Output, Temperature CompensatedTermination StylePC PinMaximum Pressure±12.33 PSI (±85 kPa)Operating Temperature-40°C ~ 85°CPackage / Case8-DIP (0.524", 13.30mm), Dual Ports, Same SideSupplier Device Package8-DIP	Manufacturer Part Number	SSCDJJN040MDAA5	
Package 8-DIP (0.524", 13.30mm), Dual Ports, Same Side  Series TruStability? SSC  Pressure Type Differential  Operating Pressure  Output Type Analog Voltage  Output 0.5 V ~ 4.5 V  Accuracy ±0.25%  Voltage - Supply 4.95 V ~ 5.05 V  Port Size Male - 0.09" (2.34mm) Tube, Dual  Port Style Barbless  Features Amplified Output, Temperature Compensated  Termination Style PC Pin  Maximum Pressure ±12.33 PSI (±85 kPa)  Operating Temperature - 40°C ~ 85°C  Package / Case 8-DIP (0.524", 13.30mm), Dual Ports, Same Side  Supplier Device Package	Manufacturer	Honeywell Sensing and Productivity Solutions	
Package8-DIP (0.524", 13.30mm), Dual Ports, Same SideSeriesTruStability? SSCPressure TypeDifferentialOperating Pressure±0.58 PSI (±4 kPa)Output TypeAnalog VoltageOutput0.5 V ~ 4.5 VAccuracy±0.25%Voltage - Supply4.95 V ~ 5.05 VPort SizeMale - 0.09" (2.34mm) Tube, DualPort StyleBarblessFeaturesAmplified Output, Temperature CompensatedTermination StylePC PinMaximum Pressure±12.33 PSI (±85 kPa)Operating Temperature-40°C ~ 85°CPackage / Case8-DIP (0.524", 13.30mm), Dual Ports, Same SideSupplier Device Package8-DIP	Category	Sensors, Transducers	
SeriesTruStability? SSCPressure TypeDifferentialOperating Pressure±0.58 PSI (±4 kPa)Output TypeAnalog VoltageOutput0.5 V ~ 4.5 VAccuracy±0.25%Voltage - Supply4.95 V ~ 5.05 VPort SizeMale - 0.09" (2.34mm) Tube, DualPort StyleBarblessFeaturesAmplified Output, Temperature CompensatedTermination StylePC PinMaximum Pressure±12.33 PSI (±85 kPa)Operating Temperature-40°C ~ 85°CPackage / Case8-DIP (0.524", 13.30mm), Dual Ports, Same SideSupplier Device Package8-DIP		Pressure Sensors, Transducers	
Pressure TypeDifferentialOperating Pressure±0.58 PSI (±4 kPa)Output TypeAnalog VoltageOutput0.5 V ~ 4.5 VAccuracy±0.25%Voltage - Supply4.95 V ~ 5.05 VPort SizeMale - 0.09" (2.34mm) Tube, DualPort StyleBarblessFeaturesAmplified Output, Temperature CompensatedTermination StylePC PinMaximum Pressure±12.33 PSI (±85 kPa)Operating Temperature-40°C ~ 85°CPackage / Case8-DIP (0.524", 13.30mm), Dual Ports, Same SideSupplier Device Package8-DIP	Package	8-DIP (0.524", 13.30mm), Dual Ports, Same Side	
Operating Pressure ±0.58 PSI (±4 kPa)  Output Type Analog Voltage  Output 0.5 V ~ 4.5 V  Accuracy ±0.25%  Voltage - Supply 4.95 V ~ 5.05 V  Port Size Male - 0.09" (2.34mm) Tube, Dual  Port Style Barbless  Features Amplified Output, Temperature Compensated  Termination Style PC Pin  Maximum Pressure ±12.33 PSI (±85 kPa)  Operating Temperature -40°C ~ 85°C  Package / Case 8-DIP (0.524", 13.30mm), Dual Ports, Same Side  Supplier Device Package 8-DIP	Series	TruStability? SSC	
Output TypeAnalog VoltageOutput $0.5 \text{ V} \sim 4.5 \text{ V}$ Accuracy $\pm 0.25\%$ Voltage - Supply $4.95 \text{ V} \sim 5.05 \text{ V}$ Port SizeMale - $0.09$ " ( $2.34\text{mm}$ ) Tube, DualPort StyleBarblessFeaturesAmplified Output, Temperature CompensatedTermination StylePC PinMaximum Pressure $\pm 12.33 \text{ PSI } (\pm 85 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case $8-\text{DIP}$ ( $0.524^{\circ}$ , $13.30\text{mm}$ ), Dual Ports, Same SideSupplier Device Package $8-\text{DIP}$	Pressure Type	Differential	
Output $0.5 \text{ V} \sim 4.5 \text{ V}$ Accuracy $\pm 0.25\%$ Voltage - Supply $4.95 \text{ V} \sim 5.05 \text{ V}$ Port Size $Male - 0.09'' (2.34mm)$ Tube, Dual  Port Style $Barbless$ Features $Amplified$ Output, Temperature Compensated  Termination Style $PC Pin$ Maximum Pressure $\pm 12.33 \text{ PSI } (\pm 85 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case $8-DIP (0.524'', 13.30mm)$ , Dual Ports, Same Side  Supplier Device Package $8-DIP$	Operating Pressure	±0.58 PSI (±4 kPa)	
Accuracy ±0.25%  Voltage - Supply 4.95 V ~ 5.05 V  Port Size Male - 0.09" (2.34mm) Tube, Dual  Port Style Barbless  Features Amplified Output, Temperature Compensated  Termination Style PC Pin  Maximum Pressure ±12.33 PSI (±85 kPa)  Operating Temperature -40°C ~ 85°C  Package / Case 8-DIP (0.524", 13.30mm), Dual Ports, Same Side  Supplier Device Package 8-DIP	Output Type	Analog Voltage	
Voltage - Supply  4.95 V ~ 5.05 V  Port Size  Male - 0.09" (2.34mm) Tube, Dual  Port Style  Barbless  Features  Amplified Output, Temperature Compensated  Termination Style  PC Pin  Maximum Pressure  ±12.33 PSI (±85 kPa)  Operating Temperature  -40°C ~ 85°C  Package / Case  8-DIP (0.524", 13.30mm), Dual Ports, Same Side  Supplier Device Package	Output	0.5 V ~ 4.5 V	
Port Size Male - 0.09" (2.34mm) Tube, Dual  Port Style Barbless  Features Amplified Output, Temperature Compensated  Termination Style PC Pin  Maximum Pressure ±12.33 PSI (±85 kPa)  Operating Temperature -40°C ~ 85°C  Package / Case 8-DIP (0.524", 13.30mm), Dual Ports, Same Side  Supplier Device Package 8-DIP	Accuracy	±0.25%	
Port Style  Barbless  Features  Amplified Output, Temperature Compensated  Termination Style  PC Pin  Maximum Pressure  ±12.33 PSI (±85 kPa)  Operating Temperature  -40°C ~ 85°C  Package / Case  8-DIP (0.524", 13.30mm), Dual Ports, Same Side  Supplier Device Package  8-DIP	Voltage - Supply	4.95 V ~ 5.05 V	
Features  Amplified Output, Temperature Compensated  PC Pin  Maximum Pressure  ±12.33 PSI (±85 kPa)  Operating Temperature  -40°C ~ 85°C  Package / Case  8-DIP (0.524", 13.30mm), Dual Ports, Same Side  Supplier Device Package  8-DIP	Port Size	Male - 0.09" (2.34mm) Tube, Dual	
Termination Style PC Pin  Maximum Pressure ±12.33 PSI (±85 kPa)  Operating Temperature -40°C ~ 85°C  Package / Case 8-DIP (0.524", 13.30mm), Dual Ports, Same Side  Supplier Device Package 8-DIP	Port Style	Barbless	
Maximum Pressure $\pm 12.33$ PSI ( $\pm 85$ kPa)Operating Temperature $-40^{\circ}$ C ~ $85^{\circ}$ CPackage / Case8-DIP (0.524", 13.30mm), Dual Ports, Same SideSupplier Device Package8-DIP	Features	Amplified Output, Temperature Compensated	
Operating Temperature -40°C ~ 85°C  Package / Case 8-DIP (0.524", 13.30mm), Dual Ports, Same Side  Supplier Device Package 8-DIP	Termination Style	PC Pin	
Package / Case 8-DIP (0.524", 13.30mm), Dual Ports, Same Side Supplier Device Package 8-DIP	Maximum Pressure	±12.33 PSI (±85 kPa)	
Supplier Device Package 8-DIP	Operating Temperature	-40°C ~ 85°C	
	Package / Case	8-DIP (0.524", 13.30mm), Dual Ports, Same Side	
Report errors?	Supplier Device Package	8-DIP	
			Report errors?

#### SSCDJJN040MDAA5 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### SSCDJJN040MDAA5 Payment Methods



















## SSCDJJN040MDAA5 Shipping Methods













If you have any question about SSCDJJN040MDAA5, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com