



SSCMANV2.5BGSA3 Information



For Reference Only

Part Number SSCMANV2.5BGSA3

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

Description BRD MNT PRESSURE SENSORS

Package 8-SMD, J-Lead, Top Port

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SSCMANV2.5BGSA3 Specifications

Manufacturer Part Number SSCMANV2.5BGSA3 Manufacturer Honeywell Sensing and Productivity Solutions Category Sensors, Transducers Package 8-SMD, J-Lead, Top Port Series TruStability? SSC Pressure Type Vented Gauge Operating Pressure 36.26 PSI (250 kPa) Output Type SPI Output 12 b Accuracy ±0.25% Voltage - Supply 3 V ~ 3.6 V Port Size Male - 0.19" (4.93mm) Tube Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style Surface Mount Maximum Pressure 0.12 PSI (0.8 kPa) Operating Temperature -40°C ~ 85°C Package / Case 8-SMD, J-Lead, Top Port Supplier Device Package 8-SMT		
CategorySensors, TransducersPressure Sensors, TransducersPackage8-SMD, J-Lead, Top PortSeriesTruStability? SSCPressure TypeVented GaugeOperating Pressure36.26 PSI (250 kPa)Output TypeSPIOutput12 bAccuracy±0.25%Voltage - Supply3 V ~ 3.6 VPort SizeMale - 0.19" (4.93mm) TubePort StyleBarbedFeaturesAmplified Output, Temperature CompensatedTermination StyleSurface MountMaximum Pressure0.12 PSI (0.8 kPa)Operating Temperature-40°C ~ 85°CPackage / Case8-SMD, J-Lead, Top PortSupplier Device Package8-SMT	Manufacturer Part Number	SSCMANV2.5BGSA3
Package 8-SMD, J-Lead, Top Port Series TruStability? SSC Pressure Type Vented Gauge Operating Pressure 36.26 PSI (250 kPa) Output Type SPI Output 12 b Accuracy ±0.25% Voltage - Supply 3 V ~ 3.6 V Port Size Male - 0.19" (4.93mm) Tube Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style Surface Mount Maximum Pressure 0.12 PSI (0.8 kPa) Operating Temperature - 40°C ~ 85°C Package / Case 8-SMD, J-Lead, Top Port Surface Mount Surface Mount Surface Mount Supplier Device Package	Manufacturer	Honeywell Sensing and Productivity Solutions
Package 8-SMD, J-Lead, Top Port Series TruStability? SSC Pressure Type Vented Gauge Operating Pressure 36.26 PSI (250 kPa) Output Type SPI Output 12 b Accuracy ±0.25% Voltage - Supply 3 V ~ 3.6 V Port Size Male - 0.19" (4.93mm) Tube Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style Surface Mount Maximum Pressure 0.12 PSI (0.8 kPa) Operating Temperature -40°C ~ 85°C Package / Case 8-SMD, J-Lead, Top Port Supplier Device Package 8-SMT	Category	Sensors, Transducers
SeriesTruStability? SSCPressure TypeVented GaugeOperating Pressure36.26 PSI (250 kPa)Output TypeSPIOutput12 bAccuracy±0.25%Voltage - Supply3 V ~ 3.6 VPort SizeMale - 0.19" (4.93mm) TubePort StyleBarbedFeaturesAmplified Output, Temperature CompensatedTermination StyleSurface MountMaximum Pressure0.12 PSI (0.8 kPa)Operating Temperature-40°C ~ 85°CPackage / Case8-SMD, J-Lead, Top PortSupplier Device Package8-SMT		Pressure Sensors, Transducers
Pressure TypeVented GaugeOperating Pressure $36.26 \text{ PSI } (250 \text{ kPa})$ Output TypeSPIOutput 12 b Accuracy $\pm 0.25\%$ Voltage - Supply $3 \text{ V} \sim 3.6 \text{ V}$ Port SizeMale - 0.19 " (4.93mm) TubePort StyleBarbedFeaturesAmplified Output, Temperature CompensatedTermination StyleSurface MountMaximum Pressure $0.12 \text{ PSI } (0.8 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case $8-\text{SMD}$, J-Lead, Top PortSupplier Device Package $8-\text{SMT}$	Package	8-SMD, J-Lead, Top Port
Operating Pressure Output Type SPI Output 12 b Accuracy ±0.25% Voltage - Supply Port Size Male - 0.19" (4.93mm) Tube Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style Surface Mount Maximum Pressure O1.12 PSI (0.8 kPa) Operating Temperature -40°C ~ 85°C Package / Case Supplier Device Package 8-SMD, J-Lead, Top Port	Series	TruStability? SSC
Output TypeSPIOutput12 bAccuracy±0.25%Voltage - Supply3 V ~ 3.6 VPort SizeMale - 0.19" (4.93mm) TubePort StyleBarbedFeaturesAmplified Output, Temperature CompensatedTermination StyleSurface MountMaximum Pressure0.12 PSI (0.8 kPa)Operating Temperature-40°C ~ 85°CPackage / Case8-SMD, J-Lead, Top PortSupplier Device Package8-SMT	Pressure Type	Vented Gauge
Output Accuracy ±0.25% Voltage - Supply Port Size Male - 0.19" (4.93mm) Tube Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style Surface Mount Maximum Pressure 0.12 PSI (0.8 kPa) Operating Temperature -40°C ~ 85°C Package / Case 8-SMD, J-Lead, Top Port Supplier Device Package 8-SMT	Operating Pressure	36.26 PSI (250 kPa)
Accuracy ±0.25% Voltage - Supply 3 V ~ 3.6 V Port Size Male - 0.19" (4.93mm) Tube Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style Surface Mount Maximum Pressure 0.12 PSI (0.8 kPa) Operating Temperature -40°C ~ 85°C Package / Case 8-SMD, J-Lead, Top Port Supplier Device Package 8-SMT	Output Type	SPI
Voltage - Supply 3 V ~ 3.6 V Port Size Male - 0.19" (4.93mm) Tube Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style Surface Mount Maximum Pressure 0.12 PSI (0.8 kPa) Operating Temperature -40°C ~ 85°C Package / Case 8-SMD, J-Lead, Top Port Supplier Device Package 8-SMT	Output	12 b
Port Size Male - 0.19" (4.93mm) Tube Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style Surface Mount Maximum Pressure 0.12 PSI (0.8 kPa) Operating Temperature -40°C ~ 85°C Package / Case 8-SMD, J-Lead, Top Port Supplier Device Package 8-SMT	Accuracy	±0.25%
Port Style Features Amplified Output, Temperature Compensated Termination Style Surface Mount Maximum Pressure 0.12 PSI (0.8 kPa) Operating Temperature -40°C ~ 85°C Package / Case 8-SMD, J-Lead, Top Port Supplier Device Package 8-SMT	Voltage - Supply	3 V ~ 3.6 V
Features Amplified Output, Temperature Compensated Surface Mount Maximum Pressure 0.12 PSI (0.8 kPa) Operating Temperature -40°C ~ 85°C Package / Case 8-SMD, J-Lead, Top Port Supplier Device Package 8-SMT	Port Size	Male - 0.19" (4.93mm) Tube
Termination Style Surface Mount Maximum Pressure 0.12 PSI (0.8 kPa) Operating Temperature -40°C ~ 85°C Package / Case 8-SMD, J-Lead, Top Port Supplier Device Package 8-SMT	Port Style	Barbed
Maximum Pressure $0.12 \text{ PSI } (0.8 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case8-SMD, J-Lead, Top PortSupplier Device Package8-SMT	Features	Amplified Output, Temperature Compensated
Operating Temperature -40°C ~ 85°C Package / Case 8-SMD, J-Lead, Top Port Supplier Device Package 8-SMT	Termination Style	Surface Mount
Package / Case 8-SMD, J-Lead, Top Port Supplier Device Package 8-SMT	Maximum Pressure	0.12 PSI (0.8 kPa)
Supplier Device Package 8-SMT	Operating Temperature	-40°C ~ 85°C
	Package / Case	8-SMD, J-Lead, Top Port
Report errors?	Supplier Device Package	8-SMT
		Report errors?

SSCMANV2.5BGSA3 Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SSCMANV2.5BGSA3 Payment Methods



















SSCMANV2.5BGSA3 Shipping Methods













If you have any question about SSCMANV2.5BGSA3, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com