

SSCMRRN002NDAA3

SSCMRRN002NDAA3 Information



For Reference Only

Part Number SSCMRRN002NDAA3

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

DescriptionBRD MNT PRESSURE SENSORS**Package**8-SMD, J-Lead, Dual Ports, Same Side

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SSCMRRN002NDAA3 Specifications

Manufacturer Part Number SSCMRRN002NDAA3 Manufacturer Honeywell Sensing and Productivity Solutions Category Sensors, Transducers Package 8-SMD, J-Lead, Dual Ports, Same Side Series TruStability? SSC Pressure Type Differential Operating Pressure ±0.07 PSI (±0.5 kPa) Output Type Analog Voltage Output 0.33 V ~ 2.97 V Accuracy ±0.25% Voltage - Supply 3.27 V ~ 3.33 V Port Size Male - 0.08" (1.93mm) Tube, Dual Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style Surface Mount Maximum Pressure ±9.76 PSI (±67.27 kPa) Operating Temperature -40°C ~ 85°C Package / Case 8-SMD, J-Lead, Dual Ports, Same Side Supplier Device Package 8-SMT			
Sensors, Transducers Pressure Sensors, Transducers Package 8-SMD, J-Lead, Dual Ports, Same Side Series TruStability? SSC Pressure Type Differential Operating Pressure ±0.07 PSI (±0.5 kPa) Output Type Analog Voltage Output 0.33 V ~ 2.97 V Accuracy ±0.25% Voltage - Supply 3.27 V ~ 3.33 V Port Size Male - 0.08" (1.93mm) Tube, Dual Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style Maximum Pressure ±9.76 PSI (±67.27 kPa) Operating Temperature -40°C ~ 85°C Package / Case 8-SMD, J-Lead, Dual Ports, Same Side Supplier Device Package	Manufacturer Part Number	SSCMRRN002NDAA3	
Pressure Sensors, Transducers 8-SMD, J-Lead, Dual Ports, Same Side Series TruStability? SSC Pressure Type Differential Operating Pressure ±0.07 PSI (±0.5 kPa) Output Type Analog Voltage Output 0.33 V ~ 2.97 V Accuracy ±0.25% Voltage - Supply 3.27 V ~ 3.33 V Port Size Male - 0.08" (1.93mm) Tube, Dual Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style Maximum Pressure ±9.76 PSI (±67.27 kPa) Operating Temperature -40°C ~ 85°C Package / Case 8-SMD, J-Lead, Dual Ports, Same Side Supplier Device Package	Manufacturer	Honeywell Sensing and Productivity Solutions	
Package8-SMD, J-Lead, Dual Ports, Same SideSeriesTruStability? SSCPressure TypeDifferentialOperating Pressure±0.07 PSI (±0.5 kPa)Output TypeAnalog VoltageOutput0.33 V ~ 2.97 VAccuracy±0.25%Voltage - Supply3.27 V ~ 3.33 VPort SizeMale - 0.08" (1.93mm) Tube, DualPort StyleBarbedFeaturesAmplified Output, Temperature CompensatedTermination StyleSurface MountMaximum Pressure±9.76 PSI (±67.27 kPa)Operating Temperature-40°C ~ 85°CPackage / Case8-SMD, J-Lead, Dual Ports, Same SideSupplier Device Package8-SMT	Category	Sensors, Transducers	
Series Trustability? SSC Pressure Type Differential Operating Pressure ±0.07 PSI (±0.5 kPa) Output Type Analog Voltage Output 0.33 V ~ 2.97 V Accuracy ±0.25% Voltage - Supply 3.27 V ~ 3.33 V Port Size Male - 0.08" (1.93mm) Tube, Dual Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style Surface Mount Maximum Pressure ±9.76 PSI (±67.27 kPa) Operating Temperature -40°C ~ 85°C Package / Case 8-SMD, J-Lead, Dual Ports, Same Side Supplier Device Package		Pressure Sensors, Transducers	
Pressure Type Differential 40.07 PSI (±0.5 kPa) Output Type Analog Voltage Output Accuracy 40.25% Voltage - Supply Port Size Male - 0.08" (1.93mm) Tube, Dual Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style Maximum Pressure 49.76 PSI (±67.27 kPa) Operating Temperature 40°C ~ 85°C Package / Case 8-SMD, J-Lead, Dual Ports, Same Side Supplier Device Package	Package	8-SMD, J-Lead, Dual Ports, Same Side	
Operating Pressure Dutput Type Analog Voltage Output Output Accuracy Voltage - Supply Port Size Male - 0.08" (1.93mm) Tube, Dual Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style Surface Mount Maximum Pressure Departing Temperature 40°C ~ 85°C Package / Case Supplier Device Package ### Analog Voltage ### 40.07 PSI (±0.5 kPa) ### Analog Voltage ### 40.07 PSI (±0.5 kPa) ### Analog Voltage ### 40.08 ### Analog Voltage ### 40.25 ### ### Analog Voltage ### 40.25 ### Analog Voltage ### 40.25 ### ### Analog Voltage ### Analog Voltage ### 40.25 ### ### 4	Series	TruStability? SSC	
Output Type	Pressure Type	Differential	
Output 0.33 V ~ 2.97 V Accuracy $\pm 0.25\%$ Voltage - Supply 3.27 V ~ 3.33 V Port Size Male - 0.08" (1.93mm) Tube, Dual Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style Surface Mount Maximum Pressure ± 9.76 PSI (± 67.27 kPa) Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case 8-SMD, J-Lead, Dual Ports, Same Side Supplier Device Package 8-SMT	Operating Pressure	±0.07 PSI (±0.5 kPa)	
Accuracy ±0.25% Voltage - Supply 3.27 V ~ 3.33 V Port Size Male - 0.08" (1.93mm) Tube, Dual Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style Surface Mount Maximum Pressure ±9.76 PSI (±67.27 kPa) Operating Temperature -40°C ~ 85°C Package / Case 8-SMD, J-Lead, Dual Ports, Same Side Supplier Device Package 8-SMT	Output Type	Analog Voltage	
Voltage - Supply 3.27 V ~ 3.33 V Port Size Male - 0.08" (1.93mm) Tube, Dual Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style Surface Mount Maximum Pressure ±9.76 PSI (±67.27 kPa) Operating Temperature -40°C ~ 85°C Package / Case 8-SMD, J-Lead, Dual Ports, Same Side Supplier Device Package 8-SMT	Output	0.33 V ~ 2.97 V	
Port Size Male - 0.08" (1.93mm) Tube, Dual Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style Surface Mount Maximum Pressure ±9.76 PSI (±67.27 kPa) Operating Temperature -40°C ~ 85°C Package / Case 8-SMD, J-Lead, Dual Ports, Same Side Supplier Device Package 8-SMT	Accuracy	±0.25%	
Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style Surface Mount Maximum Pressure ±9.76 PSI (±67.27 kPa) Operating Temperature -40°C ~ 85°C Package / Case 8-SMD, J-Lead, Dual Ports, Same Side Supplier Device Package 8-SMT	Voltage - Supply	3.27 V ~ 3.33 V	
Features Amplified Output, Temperature Compensated Surface Mount Maximum Pressure ±9.76 PSI (±67.27 kPa) Operating Temperature -40°C ~ 85°C Package / Case 8-SMD, J-Lead, Dual Ports, Same Side Supplier Device Package 8-SMT	Port Size	Male - 0.08" (1.93mm) Tube, Dual	
Termination Style Surface Mount Maximum Pressure ± 9.76 PSI (± 67.27 kPa) Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case 8-SMD, J-Lead, Dual Ports, Same Side Supplier Device Package 8-SMT	Port Style	Barbed	
Maximum Pressure ±9.76 PSI (±67.27 kPa) Operating Temperature -40°C ~ 85°C Package / Case 8-SMD, J-Lead, Dual Ports, Same Side Supplier Device Package 8-SMT	Features	Amplified Output, Temperature Compensated	
Operating Temperature -40°C ~ 85°C Package / Case 8-SMD, J-Lead, Dual Ports, Same Side Supplier Device Package 8-SMT	Termination Style	Surface Mount	
Package / Case 8-SMD, J-Lead, Dual Ports, Same Side Supplier Device Package 8-SMT	Maximum Pressure	±9.76 PSI (±67.27 kPa)	
Supplier Device Package 8-SMT	Operating Temperature	-40°C ~ 85°C	
	Package / Case	8-SMD, J-Lead, Dual Ports, Same Side	
Report errors?	Supplier Device Package	8-SMT	
		Report error	ors?

SSCMRRN002NDAA3 Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SSCMRRN002NDAA3 Payment Methods



















SSCMRRN002NDAA3 Shipping Methods













If you have any question about SSCMRRN002NDAA3, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com