

SSCSAAN015PDAA3

SSCSAAN015PDAA3 Information



For Reference Only

Part Number SSCSAAN015PDAA3

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

DescriptionSENSOR PRES 15PSI DIFF 3.3V SIPPackage4-SIP, Dual Ports, Opposite Sides

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SSCSAAN015PDAA3 Specifications

Manufacturer Part NumberSSCSAAN015PDAA3ManufacturerHoneywell Sensing and Productivity SolutionsCategorySensors, TransducersPackage4-SIP, Dual Ports, Opposite SidesSeriesTruStability? SSCPressure TypeDifferentialOperating Pressure±15 PSI (±103.42 kPa)Output TypeAnalog VoltageOutput0.33 V ~ 2.97 VAccuracy±0.25%Voltage - Supply3 V ~ 3.6 VPort SizeMale - 0.19" (4.93mm) Tube, DualPort StyleBarbedFeaturesAmplified Output, Temperature CompensatedTermination StylePC PinMaximum Pressure±60 PSI (±413.69 kPa)Operating Temperature-40°C ~ 85°CPackage / Case4-SIP, Dual Ports, Opposite Sides			
Category Sensors, Transducers Pressure Sensors, Transducers Package 4-SIP, Dual Ports, Opposite Sides Series TruStability? SSC Pressure Type Differential Operating Pressure ±15 PSI (±103.42 kPa) Output Type Analog Voltage Output 0.33 V ~ 2.97 V Accuracy ±0.25% Voltage - Supply 3 V ~ 3.6 V Port Size Male - 0.19" (4.93mm) Tube, Dual Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style PC Pin Maximum Pressure ±60 PSI (±413.69 kPa) Operating Temperature -40°C ~ 85°C	Manufacturer Part Number	SSCSAAN015PDAA3	
Pressure Sensors, Transducers 4-SIP, Dual Ports, Opposite Sides Series TruStability? SSC Pressure Type Differential Operating Pressure Output Type Analog Voltage Output Output Type Analog Voltage Output Accuracy ±0.25% Voltage - Supply 3 V ~ 3.6 V Port Size Male - 0.19" (4.93mm) Tube, Dual Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style PC Pin Maximum Pressure ±60 PSI (±413.69 kPa) Operating Temperature	Manufacturer	Honeywell Sensing and Productivity Solutions	
Package4-SIP, Dual Ports, Opposite SidesSeriesTruStability? SSCPressure TypeDifferentialOperating Pressure±15 PSI (±103.42 kPa)Output TypeAnalog VoltageOutput0.33 V ~ 2.97 VAccuracy±0.25%Voltage - Supply3 V ~ 3.6 VPort SizeMale - 0.19" (4.93mm) Tube, DualPort StyleBarbedFeaturesAmplified Output, Temperature CompensatedTermination StylePC PinMaximum Pressure±60 PSI (±413.69 kPa)Operating Temperature-40°C ~ 85°C	Category	Sensors, Transducers	
SeriesTruStability? SSCPressure TypeDifferentialOperating Pressure ± 15 PSI (± 103.42 kPa)Output TypeAnalog VoltageOutput $0.33 \text{ V} \sim 2.97 \text{ V}$ Accuracy $\pm 0.25\%$ Voltage - Supply $3 \text{ V} \sim 3.6 \text{ V}$ Port SizeMale - 0.19 " (4.93mm) Tube, DualPort StyleBarbedFeaturesAmplified Output, Temperature CompensatedTermination StylePC PinMaximum Pressure ± 60 PSI (± 413.69 kPa)Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$		Pressure Sensors, Transducers	
Pressure Type Differential Operating Pressure $\pm 15 \text{ PSI } (\pm 103.42 \text{ kPa})$ Output Type Analog Voltage Output $\pm 0.33 \text{ V} \sim 2.97 \text{ V}$ Accuracy $\pm 0.25\%$ Voltage - Supply $\pm 0.25\%$ Voltage - Supply ± 0.19 "	Package	4-SIP, Dual Ports, Opposite Sides	
Operating Pressure $\pm 15 \text{ PSI } (\pm 103.42 \text{ kPa})$ Output Type Analog Voltage Output 0.33 V ~ 2.97 V Accuracy $\pm 0.25\%$ Voltage - Supply 3 V ~ 3.6 V Port Size Male - 0.19" (4.93mm) Tube, Dual Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style PC Pin Maximum Pressure $\pm 60 \text{ PSI } (\pm 413.69 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Series	TruStability? SSC	
Output TypeAnalog VoltageOutput $0.33 \text{ V} \sim 2.97 \text{ V}$ Accuracy $\pm 0.25\%$ Voltage - Supply $3 \text{ V} \sim 3.6 \text{ V}$ Port SizeMale - 0.19 " (4.93mm) Tube, DualPort StyleBarbedFeaturesAmplified Output, Temperature CompensatedTermination StylePC PinMaximum Pressure $\pm 60 \text{ PSI } (\pm 413.69 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Pressure Type	Differential	
Output $0.33 \text{ V} \sim 2.97 \text{ V}$ Accuracy $\pm 0.25\%$ Voltage - Supply $3 \text{ V} \sim 3.6 \text{ V}$ Port SizeMale - 0.19 " (4.93mm) Tube, DualPort StyleBarbedFeaturesAmplified Output, Temperature CompensatedTermination StylePC PinMaximum Pressure $\pm 60 \text{ PSI } (\pm 413.69 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Operating Pressure	±15 PSI (±103.42 kPa)	
Accuracy $\pm 0.25\%$ Voltage - Supply $3 \text{ V} \sim 3.6 \text{ V}$ Port Size $\text{Male} - 0.19'' (4.93\text{mm}) \text{ Tube}, \text{ Dual}$ Port Style Barbed Features $\text{Amplified Output}, \text{ Temperature Compensated}$ Termination Style PC Pin Maximum Pressure $\pm 60 \text{ PSI } (\pm 413.69 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Output Type	Analog Voltage	
Voltage - Supply $3 \text{ V} \sim 3.6 \text{ V}$ Port Size $\text{Male - 0.19" (4.93 mm) Tube, Dual}$ Port Style Barbed Features $\text{Amplified Output, Temperature Compensated}$ Termination Style PC Pin Maximum Pressure $\pm 60 \text{ PSI } (\pm 413.69 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Output	0.33 V ~ 2.97 V	
Port Size Male - 0.19 " (4.93 mm) Tube, Dual Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style PC Pin Maximum Pressure ± 60 PSI (± 413.69 kPa) Operating Temperature ± 60 PSI (± 413.69 kPa)	Accuracy	±0.25%	
Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style PC Pin Maximum Pressure ± 60 PSI (± 413.69 kPa) Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Voltage - Supply	3 V ~ 3.6 V	
Features Amplified Output, Temperature Compensated Termination Style PC Pin Maximum Pressure ± 60 PSI (± 413.69 kPa) Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Port Size	Male - 0.19" (4.93mm) Tube, Dual	
Termination Style PC Pin Maximum Pressure ± 60 PSI (± 413.69 kPa) Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Port Style	Barbed	
Maximum Pressure $\pm 60 \text{ PSI } (\pm 413.69 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Features	Amplified Output, Temperature Compensated	
Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Termination Style	PC Pin	
	Maximum Pressure	±60 PSI (±413.69 kPa)	
Package / Case 4-SIP, Dual Ports, Opposite Sides	Operating Temperature	-40°C ~ 85°C	
	Package / Case	4-SIP, Dual Ports, Opposite Sides	
Supplier Device Package 4-SIP	Supplier Device Package	4-SIP	
Report errors?			Report errors?

SSCSAAN015PDAA3 Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SSCSAAN015PDAA3 Payment Methods



















SSCSAAN015PDAA3 Shipping Methods













If you have any question about SSCSAAN015PDAA3, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com