

SSD16 Information

Part Number SSD16
Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

DescriptionFUSE CRTRDGE 16A 240VAC CYLINDR**Package**Cylindrical, Blade Terminal (Alternating)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SSD16 Specifications

Manufacturer Part NumberSSD16ManufacturerEatonCategoryCircuit ProtectionPackageCylindrical, Specialty FusesPackageCylindrical, Blade Terminal (Alternating)SeriesSSDFuse TypeCartridgeCurrent Rating16AVoltage Rating - AC240VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage33kAMounting TypeHolderPackage / CaseCylindrical, Blade Terminal (Alternating)Size / Dimension0.472" Dia x 0.906" L (12.00mm x 23.00mm)		
CategoryCircuit Protection Electrical, Specialty FusesPackageCylindrical, Blade Terminal (Alternating)SeriesSSDFuse TypeCartridgeCurrent Rating16AVoltage Rating - AC240VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage33kAMounting TypeHolderPackage / CaseCylindrical, Blade Terminal (Alternating)Size / Dimension0.472" Dia x 0.906" L (12.00mm x 23.00mm)	Manufacturer Part Number	SSD16
PackageElectrical, Specialty FusesSeriesSSDFuse TypeCartridgeCurrent Rating16AVoltage Rating - AC240VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage33kAMounting TypeHolderPackage / CaseCylindrical, Blade Terminal (Alternating)Size / Dimension0.472" Dia x 0.906" L (12.00mm x 23.00mm)	Manufacturer	Eaton
PackageCylindrical, Blade Terminal (Alternating)SeriesSSDFuse TypeCartridgeCurrent Rating16AVoltage Rating - AC240VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage33kAMounting TypeHolderPackage / CaseCylindrical, Blade Terminal (Alternating)Size / Dimension0.472" Dia x 0.906" L (12.00mm x 23.00mm)	Category	Circuit Protection
SeriesSSDFuse TypeCartridgeCurrent Rating16AVoltage Rating - AC240VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage33kAMounting TypeHolderPackage / CaseCylindrical, Blade Terminal (Alternating)Size / Dimension0.472" Dia x 0.906" L (12.00mm x 23.00mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 16A Voltage Rating - AC Voltage Rating - DC Response Time - Applications Electrical, Industrial Features - Class - Approvals - Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cylindrical, Blade Terminal (Alternating) Size / Dimension Cartridge 2drafted Eartridge 16A 240V - Electrical, Industrial	Package	Cylindrical, Blade Terminal (Alternating)
Current Rating Voltage Rating - AC 240V Voltage Rating - DC Response Time - Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 16A 240V 240V -	Series	SSD
Voltage Rating - AC Voltage Rating - DC Response Time Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 240V 240V 240V 240V 240V - 40 Formating Temperature - Class - Cylindrical, Blade Terminal (Alternating)	Fuse Type	Cartridge
Voltage Rating - DC Response Time - Applications Electrical, Industrial Features - Class - Approvals - Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension - Class Class - Cl	Current Rating	16A
Response Time Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cylindrical, Blade Terminal (Alternating) Size / Dimension - Class - Class - Class Cylindrical, Blade Terminal (Alternating) Size / Dimension - Class Cylindrical, Blade Terminal (Alternating) Capacity @ Rated Voltage Capacity @ Rated Voltage Cylindrical, Blade Terminal (Alternating) Capacity @ Capacity Output Cylindrical, Blade Terminal (Alternating) Cylindrical, Blade Terminal (Alternating)	Voltage Rating - AC	240V
Applications Electrical, Industrial Features - Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 33kA Mounting Type Holder Package / Case Cylindrical, Blade Terminal (Alternating) Size / Dimension 0.472" Dia x 0.906" L (12.00mm x 23.00mm)	Voltage Rating - DC	-
Features - Class - Approvals - Coperating Temperature - Seraking Capacity @ Rated Voltage 33kA Mounting Type Holder Holder Package / Case Cylindrical, Blade Terminal (Alternating) Size / Dimension 0.472" Dia x 0.906" L (12.00mm x 23.00mm)	Response Time	-
Class - Approvals - Coperating Temperature - Streaking Capacity @ Rated Voltage 33kA Holder Holder Package / Case Cylindrical, Blade Terminal (Alternating) Size / Dimension 0.472" Dia x 0.906" L (12.00mm x 23.00mm)	Applications	Electrical, Industrial
Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cylindrical, Blade Terminal (Alternating) Size / Dimension 0.472" Dia x 0.906" L (12.00mm x 23.00mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 33kA Mounting Type Holder Package / Case Cylindrical, Blade Terminal (Alternating) Size / Dimension 0.472" Dia x 0.906" L (12.00mm x 23.00mm)	Class	-
Breaking Capacity @ Rated Voltage 33kA Mounting Type Holder Package / Case Cylindrical, Blade Terminal (Alternating) Size / Dimension 0.472" Dia x 0.906" L (12.00mm x 23.00mm)	Approvals	-
Mounting Type Holder Package / Case Cylindrical, Blade Terminal (Alternating) Size / Dimension 0.472" Dia x 0.906" L (12.00mm x 23.00mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Alternating) Size / Dimension 0.472" Dia x 0.906" L (12.00mm x 23.00mm)	Breaking Capacity @ Rated Voltage	33kA
Size / Dimension 0.472" Dia x 0.906" L (12.00mm x 23.00mm)	Mounting Type	Holder
` '	Package / Case	Cylindrical, Blade Terminal (Alternating)
Report errors?	Size / Dimension	0.472" Dia x 0.906" L (12.00mm x 23.00mm)
		Report errors?

SSD16 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SSD16 Payment Methods



















SSD16 Shipping Methods













If you have any question about SSD16, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com