

SSD16 Information

www.tielsener.com

Part Number SSD16 Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

DescriptionFUSE CRTRDGE 16A 240VAC CYLINDR**Package**Cylindrical, Blade Terminal (Alternating)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SSD16	Specific	ations
OSDIO	Specific	auons

Manufacturer Part NumberSSD16ManufacturerEatonCategoryCircuit ProtectionPackageCylindrical, Specialty FusesPackageCylindrical, Blade Terminal (Alternating)SeriesSSDFuse TypeCartridgeCurrent Rating16AVoltage Rating - AC240VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage33kAMounting TypeHolderPackage / CaseCylindrical, Blade Terminal (Alternating)Size / Dimension0.472" Dia x 0.906" L (12.00mm x 23.00mm)			
CategoryCircuit Protection Electrical, Specialty FusesPackageCylindrical, Blade Terminal (Alternating)SeriesSSDFuse TypeCartridgeCurrent Rating16AVoltage Rating - AC240VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage33kAMounting TypeHolderPackage / CaseCylindrical, Blade Terminal (Alternating)Size / Dimension0.472" Dia x 0.906" L (12.00mm x 23.00mm)	Manufacturer Part Number	SSD16	
Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Alternating) Series SSD Fuse Type Cartridge Current Rating 16A Voltage Rating - AC Voltage Rating - DC Response Time	Manufacturer	Eaton	
PackageCylindrical, Blade Terminal (Alternating)SeriesSSDFuse TypeCartridgeCurrent Rating16AVoltage Rating - AC240VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage33kAMounting TypeHolderPackage / CaseCylindrical, Blade Terminal (Alternating)Size / Dimension0.472" Dia x 0.906" L (12.00mm x 23.00mm)	Category	Circuit Protection	
SeriesSSDFuse TypeCartridgeCurrent Rating16AVoltage Rating - AC240VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage33kAMounting TypeHolderPackage / CaseCylindrical, Blade Terminal (Alternating)Size / Dimension0.472" Dia x 0.906" L (12.00mm x 23.00mm)		Electrical, Specialty Fuses	
Fuse Type Current Rating 16A Voltage Rating - AC Voltage Rating - DC Response Time - Applications Electrical, Industrial Features - Class - Approvals - Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Cartridge Cartridge Cartridge Cartridge Cartridge Cartridge Cartridge Cartridge Cartridge Cartridge Cartridge Cartridge Cartridge Cartridge Cartridge Cartridge Cartridge Cartridge Cartridge Cartridge Cartridge Cartridge Cartridge Cartridge Cartridge Cartridge Cartridge Cartridge Cartridge Cartridge Cartridge Cartridge Cartridge Cartridge Cartridge Cartridge Cartridge Cartridge Cartridge Cartridge Cartridge Call Cartridge Cartridae Cart	Package	Cylindrical, Blade Terminal (Alternating)	
Current Rating Voltage Rating - AC 240V Voltage Rating - DC Response Time - Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 16A 240V 240V 240V - Class - Approvals - Class - Approvals - Class - Cl	Series	SSD	
Voltage Rating - AC Voltage Rating - DC Response Time Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 240V 240V 240V 240V 240V 40V - 140 - 150 Electrical, Industrial - 160 - 170 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 - 180 -	Fuse Type	Cartridge	
Voltage Rating - DC Response Time - Applications Electrical, Industrial Features - Class - Approvals - Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cylindrical, Blade Terminal (Alternating) Size / Dimension - Overating Temperature Overat	Current Rating	16A	
Response Time Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cylindrical, Blade Terminal (Alternating) Size / Dimension - Overating Temperature - O	Voltage Rating - AC	240V	
Applications Electrical, Industrial Features - Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 33kA Mounting Type Holder Package / Case Cylindrical, Blade Terminal (Alternating) Size / Dimension 0.472" Dia x 0.906" L (12.00mm x 23.00mm)	Voltage Rating - DC	-	
Features - Class - Class - Coperating Temperature - Streaking Capacity @ Rated Voltage 33kA Mounting Type Holder Holder Package / Case Cylindrical, Blade Terminal (Alternating) Size / Dimension 0.472" Dia x 0.906" L (12.00mm x 23.00mm)	Response Time	-	
Class - Approvals - Class - Cylindrical, Blade Terminal (Alternating) Size / Dimension - Class - Cylindrical, Blade Terminal (Alternating) O.472" Dia x 0.906" L (12.00mm x 23.00mm)	Applications	Electrical, Industrial	
Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cylindrical, Blade Terminal (Alternating) Size / Dimension 0.472" Dia x 0.906" L (12.00mm x 23.00mm)	Features	-	
Operating Temperature Breaking Capacity @ Rated Voltage 33kA Mounting Type Holder Package / Case Cylindrical, Blade Terminal (Alternating) Size / Dimension 0.472" Dia x 0.906" L (12.00mm x 23.00mm)	Class	-	
Breaking Capacity @ Rated Voltage 33kA Mounting Type Holder Package / Case Cylindrical, Blade Terminal (Alternating) Size / Dimension 0.472" Dia x 0.906" L (12.00mm x 23.00mm)	Approvals	-	
Mounting Type Holder Package / Case Cylindrical, Blade Terminal (Alternating) Size / Dimension 0.472" Dia x 0.906" L (12.00mm x 23.00mm)	Operating Temperature	-	
Package / Case Cylindrical, Blade Terminal (Alternating) Size / Dimension 0.472" Dia x 0.906" L (12.00mm x 23.00mm)	Breaking Capacity @ Rated Voltage	33kA	
Size / Dimension 0.472" Dia x 0.906" L (12.00mm x 23.00mm)	Mounting Type	Holder	
· · ·	Package / Case	Cylindrical, Blade Terminal (Alternating)	
Report errors?	Size / Dimension	0.472" Dia x 0.906" L (12.00mm x 23.00mm)	
		Report errors?	

SSD16 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SSD16 Payment Methods



















SSD16 Shipping Methods













If you have any question about SSD16, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com