

SSL-DSP5093SIC

SSL-DSP5093SIC Information



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



SSL-DSP5093SIC Specifications

ManufacturerLumex Opto/Components Inc.CategoryOptoelectronicsELED Indication - DiscretePackageRadialSeries-ColorRedColorfiguration-ColorfigurationColorlessLens StolorColorelsMillicandela Rating2500mcdVoltage - Forward (Vf) (Typ)2VCurrent - Test20mAViewing Angle30°Mounting TypeSionel HoleWavelength - Peak636nmFeatures-Package / CaseRadialSupplier Device Package7-1 3/4Size / Dimension-Size / Dimension- <trt< th=""><th></th><th></th></trt<>		
Category Optoeleronics LED Indication - Discrete Package Radial Package Red Color Red Configuration - Configuration Colorless Lens Stoler Rating 2500mcd Villicandela Rating 2500mcd Voltage - Forward (Vf) (Typ) 2V Current - Test 20mA Viewing Angle 30° Wavelength - Poak 636nm Features - Package / Case Radial Supplier Device Package Fail Supplier Device Package Fail Size / Dimension 5.60mm	Manufacturer Part Number	SSL-DSP5093SIC
LED Indication - DiscretePackageRadialSeries-ColorRedConfiguration-Lens ColorColorlessLens TransparencyClearWillicandela Rating2500mcdLens Style/SizeRound with Domed Top, 5mm (T-1 3/4), 5.00mmVoltage - Forward (Vf) (Typ)2VCurrent - Test20mAWinning Type30°Mounting TypeThrough HoleWavelength - Dominant-Features-Package / CaseRadialSupplier Device PackageT-1 3/4Size / Dimension-Height (Max)8.60mm	Manufacturer	Lumex Opto/Components Inc.
PackageRadialSeries-ColorRedConfiguration-Lens ColorColorlessLens TransparencyClearMillicandela Rating2500mcdVoltage - Forward (Vf) (Typ)2VCurrent - Test20mAViveing Angle30°Worlength - Dominant-Wavelength - Peak636nmFeatures-Package / CaseRidialSupplier Device Package7.13/4Size / Dimension-Kaight (Max)8.60mm	Category	Optoelectronics
Series - Series Red Color Red Configuration - Lens Color Colorless Lens Color Colorless Lens Transparency Clear Millicandela Rating 2500mcd Lens Style/Size Round with Domed Top, 5mm (T-1 3/4), 5.00mm Voltage - Forward (Vf) (Typ) 2V Current - Test 20mA Yolewing Angle 30° Mounting Type Through Hole Wavelength - Dominant - Features - Package / Case Radial Supplier Device Package T-1 3/4 Supplier Device Package -1 3/4 Size / Dimension - Height (Max) 8.60mm		LED Indication - Discrete
ColorRedConfiguration-ConfigurationColorlessLens ColorColorlessLens TransparencyClearWillicandela Rating2500mcdLens Style/SizeRound with Domed Top, 5mm (T-1 3/4), 5.00mmVoltage - Forward (Vf) (Typ)2VCurrent - Test20mAViewing Angle30°Mounting TypeThrough HoleWavelength - Dominant-Features636nmPackage / CaseRadialSupplier Device PackageT-1 3/4Size / Dimension-Height (Max)8.60mm	Package	Radial
Configuration-ConfigurationColorlessLens ColorClearMillicandela Rating2500mcdLens Style/SizeRound with Domed Top, 5mm (T-1 3/4), 5.00mmVoltage - Forward (Vf) (Typ)2VCurrent - Test20mAViewing Angle30°Mounting Type1hrough HoleWavelength - Dominant-Features-Package / CaseRadialSupplier Device Package-Size / Dimension-Size / Dimension	Series	-
Lens ColorColorlessLens TransparencyClearMillicandela Rating2500mcdLens Style/SizeRound with Domed Top, 5mm (T-1 3/4), 5.00mmVoltage - Forward (Vf) (Typ)2VCurrent - Test20mACurrent - Test30°Viewing Angle-Wavelength - Dominant-Features-Package / CaseRadialSupplier Device PackageT-1 3/4Supplier Device Package-Height (Max)8.60mm	Color	Red
Lens TransparencyClearMillicandela Rating2500mcdLens Style/SizeRound with Domed Top, 5mm (T-1 3/4), 5.00mmVoltage - Forward (Vf) (Typ)2VCurrent - Test20mAViewing Angle30°Mounting TypeThrough HoleWavelength - Dominant-Features-Package / CaseRadialSupplier Device PackageT-1 3/4Size / Dimension-Height (Max)8.60mm	Configuration	-
Millicandela Rating2500mcdLens Style/SizeRound with Domed Top, 5mm (T-1 3/4), 5.00mmVoltage - Forward (Vf) (Typ)2VCurrent - Test20mACurrent - Test30°Mounting TypeThrough HoleWavelength - Dominant-Wavelength - Peak636nmFeatures-Package / CaseRadialSupplier Device PackageT-1 3/4Ster / Dimension-Height (Max)8.60mm	Lens Color	Colorless
Lens Style/SizeRound with Domed Top, 5mm (T-1 3/4), 5.00mmVoltage - Forward (Vf) (Typ)2VCurrent - Test0mACurrent - Test30°Viewing Angle30°Mounting TypeThrough HoleWavelength - Dominant-Wavelength - Peak636nmFeatures-Package / CaseRadialSupplier Device PackageT-1 3/4Size / Dimension-Height (Max)8.60mm	Lens Transparency	Clear
Voltage - Forward (Vf) (Typ)2VCurrent - Test20mAViewing Angle30°Mounting TypeThrough HoleWavelength - Dominant-Wavelength - Peak636nmFeatures-Package / CaseRadialSupplier Device PackageT-1 3/4Size / Dimension-Height (Max)8.60mm	Millicandela Rating	2500mcd
Current - Test20mAViewing Angle30°Mounting TypeThrough HoleWavelength - Dominant-Wavelength - Peak636nmFeatures-Package / CaseRadialSupplier Device PackageT-1 3/4Size / Dimension-Height (Max)8.60mm	Lens Style/Size	Round with Domed Top, 5mm (T-1 3/4), 5.00mm
Viewing Angle30°Mounting TypeThrough HoleWavelength - Dominant-Wavelength - Peak636nmFeatures-Package / CaseRadialSupplier Device PackageT-1 3/4Size / Dimension-Height (Max)8.60mm	Voltage - Forward (Vf) (Typ)	2V
Nounting TypeThrough HoleWavelength - Dominant-Wavelength - Peak636nmFeatures-Package / CaseRadialSupplier Device PackageT-1 3/4Size / Dimension-Height (Max)8.60mm	Current - Test	20mA
Wavelength - Dominant-Wavelength - Peak636nmFeatures-Package / CaseRadialSupplier Device PackageT-1 3/4Size / Dimension-Height (Max)8.60mm	Viewing Angle	30°
Wavelength - Peak636nmFeatures-Package / CaseRadialSupplier Device PackageT-1 3/4Size / Dimension-Height (Max)8.60mm	Mounting Type	Through Hole
Features-Package / CaseRadialSupplier Device PackageT-1 3/4Size / Dimension-Height (Max)8.60mm	Wavelength - Dominant	-
Package / CaseRadialSupplier Device PackageT-1 3/4Size / Dimension-Height (Max)8.60mm	Wavelength - Peak	636nm
Supplier Device PackageT-1 3/4Size / Dimension-Height (Max)8.60mm	Features	-
Size / Dimension - Height (Max) 8.60mm	Package / Case	Radial
Height (Max) 8.60mm	Supplier Device Package	T-1 3/4
	Size / Dimension	-
Report errors?	Height (Max)	8.60mm
		Report errors?

SSL-DSP5093SIC Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

SSL-DSP5093SIC Payment Methods



SSL-DSP5093SIC Shipping Methods



If you have any question about SSL-DSP5093SIC, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com