



SSL-LX3044PGD Information



Part Number SSL-LX3044PGD

Manufacturer Lumex Opto/Components Inc.

Category Optoelectronics

LED Indication - Discrete

Description LED GRN DIFF 3MM ROUND T/H

Package Radia

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SSL-LX3044PGD Specifications

Manufacturer Part Number SSL-LX3044PGD Manufacturer Lumex Opto/Components Inc. Category Optoelectronics Package Radial Series - Color Green Lens Color Green Lens Transparency Diffused Millicandela Rating 20mcd Lens Style/Size Round with Domed Top, 3mm (T-1), 2.90mm Voltage - Forward (Vf) (Typ) 2.2V Current - Test 20mA Viewing Angle 60° Mounting Type Through Hole Wavelength - Dominant - Wavelength - Peak 555m Features - Package / Case Radial Supplier Device Package T-1 Size / Dimension - Height (Max) 4.60mm	•	
Category Optoelectronics LED Indication - Discrete Package Radial Series - Color Green Configuration - Lens Color Green Lens Transparency Diffused Millicandela Rating 20mcd Lens Style/Size Round with Domed Top, 3mm (T-1), 2.90mm Voltage - Forward (Vf) (Typ) 2.2V Current - Test 20mA Viewing Angle 60° Mounting Type Through Hole Wavelength - Dominant - Wavelength - Peak 555nm Features - Package / Case Radial Supplier Device Package T-1 Size / Dimension - Height (Max) 4.60mm	Manufacturer Part Number	SSL-LX3044PGD
PackageRadialSeries-ColorGreenConfiguration-Lens ColorGreenLens TransparencyDiffusedMillicandela Rating20mcdLens Style/SizeRound with Domed Top, 3mm (T-1), 2.90mmVoltage - Forward (Vf) (Typ)2.2VCurrent - Test20mAViewing Angle60°Mounting TypeThrough HoleWavelength - Dominant-Wavelength - Peak555nmFeatures-Package / CaseRadialSupplier Device PackageT-1Size / Dimension-Height (Max)4.60mm	Manufacturer	Lumex Opto/Components Inc.
Package Radial Series - Color Green Configuration - Lens Color Green Lens Transparency Diffused Millicandela Rating 20mcd Lens Style/Size Round with Domed Top, 3mm (T-1), 2.90mm Voltage - Forward (Vf) (Typ) 2.2V Current - Test 20mA Viewing Angle 60° Mounting Type Through Hole Wavelength - Dominant - Wavelength - Peak 555nm Features - Package / Case Radial Supplier Device Package T-1 Size / Dimension - Height (Max) 4.60mm	Category	Optoelectronics
Series - Color Green Configuration - Lens Color Green Lens Transparency Diffused Millicandela Rating 20mcd Lens Style/Size Round with Domed Top, 3mm (T-1), 2.90mm Voltage - Forward (Vf) (Typ) 2.2V Current - Test 20mA Viewing Angle 60° Mounting Type Through Hole Wavelength - Dominant - Wavelength - Peak 555nm Features - Package / Case Radial Supplier Device Package T-1 Size / Dimension - Height (Max) 4.60mm		LED Indication - Discrete
Color Green Configuration - Lens Color Green Lens Transparency Diffused Millicandela Rating 20mcd Lens Style/Size Round with Domed Top, 3mm (T-1), 2.90mm Voltage - Forward (Vf) (Typ) 2.2V Current - Test 20mA Viewing Angle 60° Mounting Type Through Hole Wavelength - Dominant - Wavelength - Peak 555nm Features - Package / Case Radial Supplier Device Package T-1 Size / Dimension - Height (Max) 4.60mm	Package	Radial
Configuration Lens Color Green Lens Transparency Diffused Millicandela Rating 20mcd Lens Style/Size Round with Domed Top, 3mm (T-1), 2.90mm Voltage - Forward (Vf) (Typ) 2.2V Current - Test 20mA Viewing Angle 60° Mounting Type Through Hole Wavelength - Dominant - Wavelength - Peak 555nm Features Package / Case Radial Supplier Device Package T-1 Size / Dimension - Height (Max) Amount Green Green Diffused And Carlon Features - Radial And Carlon Features - Height (Max) 4.60mm	Series	-
Lens ColorGreenLens TransparencyDiffusedMillicandela Rating20mcdLens Style/SizeRound with Domed Top, 3mm (T-1), 2.90mmVoltage - Forward (Vf) (Typ)2.2VCurrent - Test20mAViewing Angle60°Mounting TypeThrough HoleWavelength - Dominant-Vavelength - Peak555nmFeatures-Package / CaseRadialSupplier Device PackageT-1Size / Dimension-Height (Max)4.60mm	Color	Green
Lens Transparency Millicandela Rating 20mcd Lens Style/Size Round with Domed Top, 3mm (T-1), 2.90mm Voltage - Forward (Vf) (Typ) 2.2V Current - Test 20mA Viewing Angle 60° Mounting Type Through Hole Wavelength - Dominant - Wavelength - Peak 555nm Features - Package / Case Radial Supplier Device Package T-1 Size / Dimension - Height (Max) A sound with Domed Top, 3mm (T-1), 2.90mm T-1), 2.90mm T-1, 2	Configuration	-
Millicandela Rating Lens Style/Size Round with Domed Top, 3mm (T-1), 2.90mm Voltage - Forward (Vf) (Typ) 2.2V Current - Test 20mA Viewing Angle 60° Mounting Type Through Hole Wavelength - Dominant - Wavelength - Peak 555nm Features - Package / Case Radial Supplier Device Package T-1 Size / Dimension Height (Max) A cound with Domed Top, 3mm (T-1), 2.90mm Through Hole 2.2V Current - Test 20mA 50° Forward (Vf) (Typ) 2.2V Current - Test 20mA 50° Forward (Vf) (Typ) 5.25V Forward (Vf) (Typ) 5.25V Forward (Vf) (Typ) 5.25V Forward (Vf) (Typ) 5.26V Forward (Vf) (Typ) 6.26V Forward (Vf) (Typ) 6.27V Forward (Vf) (Typ) 6.27	Lens Color	Green
Lens Style/SizeRound with Domed Top, 3mm (T-1), 2.90mmVoltage - Forward (Vf) (Typ)2.2VCurrent - Test20mAViewing Angle60°Mounting TypeThrough HoleWavelength - Dominant-Wavelength - Peak555nmFeatures-Package / CaseRadialSupplier Device PackageT-1Size / Dimension-Height (Max)4.60mm	Lens Transparency	Diffused
Voltage - Forward (Vf) (Typ) Current - Test 20mA Viewing Angle 60° Mounting Type Through Hole Wavelength - Dominant - Wavelength - Peak 555nm Features - Package / Case Radial Supplier Device Package T-1 Size / Dimension Height (Max) 2.2V 20mA 60° Through Hole Through Hole - 1 - 1 - 1 - 1 - 1 - 1 - 1 -	Millicandela Rating	20mcd
Current - Test 20mA Viewing Angle 60° Mounting Type Through Hole Wavelength - Dominant - Wavelength - Peak 555nm Features - Package / Case Radial Supplier Device Package T-1 Size / Dimension - Height (Max) 4.60mm	Lens Style/Size	Round with Domed Top, 3mm (T-1), 2.90mm
Viewing Angle60°Mounting TypeThrough HoleWavelength - Dominant-Wavelength - Peak555nmFeatures-Package / CaseRadialSupplier Device PackageT-1Size / Dimension-Height (Max)4.60mm	Voltage - Forward (Vf) (Typ)	2.2V
Mounting Type Through Hole Wavelength - Dominant - Wavelength - Peak 555nm Features - Package / Case Radial Supplier Device Package T-1 Size / Dimension - Height (Max) 4.60mm	Current - Test	20mA
Wavelength - Dominant-Wavelength - Peak555nmFeatures-Package / CaseRadialSupplier Device PackageT-1Size / Dimension-Height (Max)4.60mm	Viewing Angle	60°
Wavelength - Peak 555nm Features - Package / Case Radial Supplier Device Package T-1 Size / Dimension - Height (Max) 4.60mm	Mounting Type	Through Hole
Features - Case Radial Supplier Device Package T-1 Size / Dimension - Height (Max) 4.60mm	Wavelength - Dominant	-
Package / Case Radial Supplier Device Package T-1 Size / Dimension - Height (Max) 4.60mm	Wavelength - Peak	555nm
Supplier Device Package T-1 Size / Dimension - Height (Max) 4.60mm	Features	-
Size / Dimension - Height (Max) 4.60mm	Package / Case	Radial
Height (Max) 4.60mm	Supplier Device Package	T-1
	Size / Dimension	-
Report errors?	Height (Max)	4.60mm
		Report errors?

SSL-LX3044PGD Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SSL-LX3044PGD Payment Methods





















SSL-LX3044PGD Shipping Methods













If you have any question about SSL-LX3044PGD, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com