



SSL-LX5063SYD Information

Heisener.com

Part Number SSL-LX5063SYD

Manufacturer Lumex Opto/Components Inc.

Category Optoelectronics

LED Indication - Discrete

Description LED YELLOW DIFF 5MM ROUND T/H

Package Radial

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SSL-LX5063SYD Specifications

Manufacturer Part Number SSL-LX5063SYD Manufacturer Lumex Opto/Components Inc. Category Optoelectronics LED Indication - Discrete Package Radial Series - Color Yellow Configuration - Lens Color Yellow Lens Transparency Diffused Millicandela Rating 200med Lens Style/Size Round with Domed Top, 5mm (T-1 3/4), 5.00mm Voltage - Forward (Vf) (Typ) 2.1V Current - Test 20mA Viewing Angle 60° Mounting Type Through Hole Wavelength - Dominant - Wavelength - Peak 590nm Features - Package / Case Radial Supplier Device Package T-1 3/4 Size / Dimension -	•	
Category Optoelectronics LED Indication - Discrete Package Radial Series - Color Yellow Configuration - Lens Color Yellow Lens Transparency Diffused Millicandela Rating 200mcd Lens Style/Size Round with Domed Top, 5mm (T-1 3/4), 5.00mm Voltage - Forward (Vf) (Typ) 2.1V Current - Test 20mA Viewing Angle 60° Mounting Type Through Hole Wavelength - Dominant - Wavelength - Peak 590nm Features - Package / Case Radial Supplier Device Package T-1 3/4 Size / Dimension -	Manufacturer Part Number	SSL-LX5063SYD
PackageRadialSeries-ColorYellowConfiguration-Lens ColorYellowLens TransparencyDiffusedMillicandela Rating200mcdLens Style/SizeRound with Domed Top, 5mm (T-1 3/4), 5.00mmVoltage - Forward (Vf) (Typ)2.1VCurrent - Test20mAViewing Angle60°Mounting TypeThrough HoleWavelength - Dominant-Wavelength - Peak590nmFeatures-Package / CaseRadialSupplier Device PackageT-1 3/4Size / Dimension-	Manufacturer	Lumex Opto/Components Inc.
Package Radial Series - Color Yellow Configuration - Lens Color Yellow Lens Transparency Diffused Millicandela Rating 200mcd Lens Style/Size Round with Domed Top, 5mm (T-1 3/4), 5.00mm Voltage - Forward (Vf) (Typ) 2.1V Current - Test 20mA Viewing Angle 60° Mounting Type Through Hole Wavelength - Dominant - Wavelength - Peak 590nm Features - Package / Case Radial Supplier Device Package T-1 3/4 Size / Dimension -	Category	Optoelectronics
Series - Color Yellow Configuration - Lens Color Yellow Lens Transparency Diffused Millicandela Rating 200mcd Lens Style/Size Round with Domed Top, 5mm (T-1 3/4), 5.00mm Voltage - Forward (Vf) (Typ) 2.1 V Current - Test 20mA Viewing Angle 60° Mounting Type Through Hole Wavelength - Dominant - Wavelength - Peak 590nm Features - Package / Case Radial Supplier Device Package T-1 3/4 Size / Dimension -		LED Indication - Discrete
ColorYellowConfiguration-Lens ColorYellowLens TransparencyDiffusedMillicandela Rating200mcdLens Style/SizeRound with Domed Top, 5mm (T-1 3/4), 5.00mmVoltage - Forward (Vf) (Typ)2.1VCurrent - Test20mAViewing Angle60°Mounting TypeThrough HoleWavelength - Dominant-Wavelength - Peak590nmFeatures-Package / CaseRadialSupplier Device PackageT-1 3/4Size / Dimension-	Package	Radial
Configuration-Lens ColorYellowLens TransparencyDiffusedMillicandela Rating200mcdLens Style/SizeRound with Domed Top, 5mm (T-1 3/4), 5.00mmVoltage - Forward (Vf) (Typ)2.1VCurrent - Test20mAViewing Angle60°Mounting TypeThrough HoleWavelength - Dominant-Wavelength - Peak590nmFeatures-Package / CaseRadialSupplier Device PackageT-1 3/4Size / Dimension-	Series	-
Lens ColorYellowLens TransparencyDiffusedMillicandela Rating200mcdLens Style/SizeRound with Domed Top, 5mm (T-1 3/4), 5.00mmVoltage - Forward (Vf) (Typ)2.1VCurrent - Test20mAViewing Angle60°Mounting TypeThrough HoleWavelength - Dominant-Wavelength - Peak590nmFeatures-Package / CaseRadialSupplier Device PackageT-1 3/4Size / Dimension-	Color	Yellow
Lens TransparencyDiffusedMillicandela Rating200mcdLens Style/SizeRound with Domed Top, 5mm (T-1 3/4), 5.00mmVoltage - Forward (Vf) (Typ)2.1VCurrent - Test20mAViewing Angle60°Mounting TypeThrough HoleWavelength - Dominant-Wavelength - Peak590nmFeatures-Package / CaseRadialSupplier Device PackageT-1 3/4Size / Dimension-	Configuration	-
Millicandela Rating Lens Style/Size Round with Domed Top, 5mm (T-1 3/4), 5.00mm Voltage - Forward (Vf) (Typ) 2.1V Current - Test 20mA Viewing Angle 60° Mounting Type Through Hole Wavelength - Dominant - Wavelength - Peak 590nm Features - Package / Case Radial Supplier Device Package T-1 3/4 Size / Dimension 200mcd Round with Domed Top, 5mm (T-1 3/4), 5.00mm T-1 3/4 Size / Dimension	Lens Color	Yellow
Lens Style/SizeRound with Domed Top, 5mm (T-1 3/4), 5.00mmVoltage - Forward (Vf) (Typ)2.1VCurrent - Test20mAViewing Angle60°Mounting TypeThrough HoleWavelength - Dominant-Wavelength - Peak590nmFeatures-Package / CaseRadialSupplier Device PackageT-1 3/4Size / Dimension-	Lens Transparency	Diffused
Voltage - Forward (Vf) (Typ) Current - Test 20mA Viewing Angle 60° Mounting Type Through Hole Wavelength - Dominant - Wavelength - Peak 590nm Features - Package / Case Radial Supplier Device Package T-1 3/4 Size / Dimension 2.1V 2.1V 2.0mA 60° Rowa 60° Through Hole 7- 7- 8- 8- 8- 8- 8- 8- 8- 8-	Millicandela Rating	200mcd
Current - Test 20mA Viewing Angle 60° Mounting Type Through Hole Wavelength - Dominant - Wavelength - Peak 590nm Features - Package / Case Radial Supplier Device Package T-1 3/4 Size / Dimension -	Lens Style/Size	Round with Domed Top, 5mm (T-1 3/4), 5.00mm
Viewing Angle60°Mounting TypeThrough HoleWavelength - Dominant-Wavelength - Peak590nmFeatures-Package / CaseRadialSupplier Device PackageT-1 3/4Size / Dimension-	Voltage - Forward (Vf) (Typ)	2.1V
Mounting Type Through Hole Wavelength - Dominant - Wavelength - Peak 590nm Features - Package / Case Radial Supplier Device Package T-1 3/4 Size / Dimension -	Current - Test	20mA
Wavelength - Dominant - Wavelength - Peak 590nm Features - Package / Case Radial Supplier Device Package T-1 3/4 Size / Dimension -	Viewing Angle	60°
Wavelength - Peak 590nm Features - Package / Case Radial Supplier Device Package T-1 3/4 Size / Dimension -	Mounting Type	Through Hole
Features - Case Radial Supplier Device Package T-1 3/4 Size / Dimension - Case Table	Wavelength - Dominant	-
Package / Case Radial Supplier Device Package T-1 3/4 Size / Dimension -	Wavelength - Peak	590nm
Supplier Device Package T-1 3/4 Size / Dimension -	Features	-
Size / Dimension -	Package / Case	Radial
	Supplier Device Package	T-1 3/4
H : 1, 04	Size / Dimension	-
Height (Max) 6.00mm	Height (Max)	6.00mm
Report errors?		Report errors?

SSL-LX5063SYD Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SSL-LX5063SYD Payment Methods



















SSL-LX5063SYD Shipping Methods













If you have any question about SSL-LX5063SYD, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com