



### SSL-LX5093SOD Information

Heisener.com

Part Number SSL-LX5093SOD

Manufacturer Lumex Opto/Components Inc.

**Category** Optoelectronics

LED Indication - Discrete

**Description** LED ORANGE DIFF 5MM ROUND T/H

Package Radial

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# SSL-LX5093SOD Specifications

Manufacturer Part Number         SSL-LX5093SOD           Manufacturer         Lumex Opto/Components Inc.           Category         Optoelectronics           LED Indication - Discrete           Package         Radial           Series         -           Color         Orange           Configuration         -           Lens Color         Orange           Lens Transparency         Diffused           Millicandela Rating         850mcd           Lens Style/Size         Round with Domed Top, 5mm (T-1 3/4), 5.00mm           Voltage - Forward (Vf) (Typ)         2V           Current - Test         20mA           Viewing Angle         60°           Mounting Type         Through Hole           Wavelength - Dominant         -           Wavelength - Peak         610nm           Features         -           Package / Case         Radial           Supplier Device Package         T-1 3/4           Size / Dimension         -           Height (Max)         8.60mm	•	
Category         Optoelectronics           LED Indication - Discrete           Package         Radial           Series         -           Color         Orange           Configuration         -           Lens Color         Orange           Lens Transparency         Diffused           Millicandela Rating         850mcd           Lens Style/Size         Round with Domed Top, 5mm (T-1 3/4), 5.00mm           Voltage - Forward (Vf) (Typ)         2V           Current - Test         20mA           Viewing Angle         60°           Mounting Type         Through Hole           Wavelength - Dominant         -           Wavelength - Peak         610nm           Features         -           Package / Case         Radial           Supplier Device Package         T-1 3/4           Size / Dimension         -           Height (Max)         8.60mm	Manufacturer Part Number	SSL-LX5093SOD
Package         Radial           Series         -           Color         Orange           Configuration         -           Lens Color         Orange           Lens Transparency         Diffused           Millicandela Rating         850mcd           Lens Style/Size         Round with Domed Top, 5mm (T-1 3/4), 5.00mm           Voltage - Forward (Vf) (Typ)         2V           Current - Test         20mA           Viewing Angle         60°           Mounting Type         Through Hole           Wavelength - Dominant         -           Wavelength - Peak         610nm           Features         -           Package / Case         Radial           Supplier Device Package         T-1 3/4           Size / Dimension         -           Height (Max)         8.60mm	Manufacturer	Lumex Opto/Components Inc.
Package         Radial           Series         -           Color         Orange           Configuration         -           Lens Color         Orange           Lens Transparency         Diffused           Millicandela Rating         850mcd           Lens Style/Size         Round with Domed Top, 5mm (T-1 3/4), 5.00mm           Voltage - Forward (Vf) (Typ)         2V           Current - Test         20mA           Viewing Angle         60°           Mounting Type         Through Hole           Wavelength - Dominant         -           Wavelength - Peak         610nm           Features         -           Package / Case         Radial           Supplier Device Package         T-1 3/4           Size / Dimension         -           Height (Max)         8.60mm	Category	Optoelectronics
Series         -           Color         Orange           Configuration         -           Lens Color         Orange           Lens Transparency         Diffused           Millicandela Rating         850mcd           Lens Style/Size         Round with Domed Top, 5mm (T-1 3/4), 5.00mm           Voltage - Forward (Vf) (Typ)         2V           Current - Test         20mA           Viewing Angle         60°           Mounting Type         Through Hole           Wavelength - Dominant         -           Wavelength - Peak         610nm           Features         -           Package / Case         Radial           Supplier Device Package         T-1 3/4           Size / Dimension         -           Height (Max)         8.60mm		LED Indication - Discrete
Color         Orange           Configuration         -           Lens Color         Orange           Lens Transparency         Diffused           Millicandela Rating         850mcd           Lens Style/Size         Round with Domed Top, 5mm (T-1 3/4), 5.00mm           Voltage - Forward (Vf) (Typ)         2V           Current - Test         20mA           Viewing Angle         60°           Mounting Type         Through Hole           Wavelength - Dominant         -           Wavelength - Peak         610nm           Features         -           Package / Case         Radial           Supplier Device Package         T-1 3/4           Size / Dimension         -           Height (Max)         8.60mm	Package	Radial
Configuration - Lens Color Orange Lens Transparency Diffused Millicandela Rating 850mcd Lens Style/Size Round with Domed Top, 5mm (T-1 3/4), 5.00mm Voltage - Forward (Vf) (Typ) 2V Current - Test 20mA Viewing Angle 60° Mounting Type Through Hole Wavelength - Dominant - Wavelength - Peak 610nm Features - Package / Case Radial Supplier Device Package T-1 3/4 Size / Dimension - Height (Max) 8.60mm	Series	-
Lens ColorOrangeLens TransparencyDiffusedMillicandela Rating850mcdLens Style/SizeRound with Domed Top, 5mm (T-1 3/4), 5.00mmVoltage - Forward (Vf) (Typ)2VCurrent - Test20mAViewing Angle60°Mounting TypeThrough HoleWavelength - Dominant-Wavelength - Peak610nmFeatures-Package / CaseRadialSupplier Device PackageT-1 3/4Size / Dimension-Height (Max)8.60mm	Color	Orange
Lens Transparency Millicandela Rating Lens Style/Size Round with Domed Top, 5mm (T-1 3/4), 5.00mm  Voltage - Forward (Vf) (Typ) 2V Current - Test 20mA Viewing Angle 60° Mounting Type Through Hole Wavelength - Dominant - Wavelength - Peak 610nm Features - Package / Case Radial Supplier Device Package T-1 3/4 Size / Dimension - Height (Max)  Bond  850mcd  850mcd 850	Configuration	-
Millicandela Rating Lens Style/Size Round with Domed Top, 5mm (T-1 3/4), 5.00mm  Voltage - Forward (Vf) (Typ) 2V Current - Test 20mA Viewing Angle 60° Mounting Type Through Hole Wavelength - Dominant - Wavelength - Peak 610nm Features - Package / Case Radial Supplier Device Package T-1 3/4 Size / Dimension - Height (Max) 8.60mm	Lens Color	Orange
Lens Style/SizeRound with Domed Top, 5mm (T-1 3/4), 5.00mmVoltage - Forward (Vf) (Typ)2VCurrent - Test20mAViewing Angle60°Mounting TypeThrough HoleWavelength - Dominant-Wavelength - Peak610nmFeatures-Package / CaseRadialSupplier Device PackageT-1 3/4Size / Dimension-Height (Max)8.60mm	Lens Transparency	Diffused
Voltage - Forward (Vf) (Typ)  Current - Test  20mA  Viewing Angle  60°  Mounting Type  Through Hole  Wavelength - Dominant  -  Wavelength - Peak  610nm  Features  -  Package / Case  Radial  Supplier Device Package  T-1 3/4  Size / Dimension  -  Height (Max)  2V  20mA  60°  Rhound  60°  Through Hole  860°  Through Hole  Thr	Millicandela Rating	850mcd
Current - Test 20mA  Viewing Angle 60°  Mounting Type Through Hole  Wavelength - Dominant -  Wavelength - Peak 610nm  Features -  Package / Case Radial  Supplier Device Package T-1 3/4  Size / Dimension -  Height (Max) 8.60mm	Lens Style/Size	Round with Domed Top, 5mm (T-1 3/4), 5.00mm
Viewing Angle60°Mounting TypeThrough HoleWavelength - Dominant-Wavelength - Peak610nmFeatures-Package / CaseRadialSupplier Device PackageT-1 3/4Size / Dimension-Height (Max)8.60mm	Voltage - Forward (Vf) (Typ)	2V
Mounting Type Through Hole  Wavelength - Dominant -  Wavelength - Peak 610nm  Features -  Package / Case Radial  Supplier Device Package T-1 3/4  Size / Dimension -  Height (Max) 8.60mm	Current - Test	20mA
Wavelength - Dominant - Wavelength - Peak 610nm Features - Package / Case Radial Supplier Device Package T-1 3/4 Size / Dimension - Height (Max) 8.60mm	Viewing Angle	60°
Wavelength - Peak 610nm  Features - Package / Case Radial Supplier Device Package T-1 3/4 Size / Dimension - Height (Max) 8.60mm	Mounting Type	Through Hole
Features - Case Radial Supplier Device Package T-1 3/4 Size / Dimension - Height (Max) 8.60mm	Wavelength - Dominant	-
Package / Case Radial Supplier Device Package T-1 3/4 Size / Dimension - Height (Max) 8.60mm	Wavelength - Peak	610nm
Supplier Device Package T-1 3/4 Size / Dimension - Height (Max) 8.60mm	Features	-
Size / Dimension - Height (Max) 8.60mm	Package / Case	Radial
Height (Max) 8.60mm	Supplier Device Package	T-1 3/4
	Size / Dimension	-
Report errors?	Height (Max)	8.60mm
		Report errors?

#### SSL-LX5093SOD Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### SSL-LX5093SOD Payment Methods



















## SSL-LX5093SOD Shipping Methods













If you have any question about SSL-LX5093SOD, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com