



SSL-LX5093XAC Information



For Reference Only

Part Number SSL-LX5093XAC

Manufacturer Lumex Opto/Components Inc.

Category Optoelectronics

LED Indication - Discrete

Description LED AMBER CLEAR 5MM ROUND T/H

Package Radia

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SSL-LX5093XAC Specifications

Manufacturer Part Number SSL-Lx5093XAC Manufacturer Lumex Opto/Components Inc. Category Optoelectronies Package Radial Series - Color Amber Lens Color Colorless Lens Transparency Clear Millicandela Rating 600mcd Lens Style/Size Round with Domed Top, 5mm (T-1 3/4), 4.70mm Voltage - Forward (Vf) (Typ) 2V Current - Test 20mA Viewing Angle 20° Mounting Type Through Hole Wavelength - Dominant - Wavelength - Peak 610nm Peakage / Case Radial Supplier Device Package T-1 3/4 Size / Dimension - Height (Max) 8.60mm	*	
Category Optoelectronics LED Indication - Discrete Package Radial Series - Color Amber Configuration - Lens Color Colorless Lens Transparency Clear Millicandela Rating 600mcd Lens Style/Size Round with Domed Top, 5mm (T-1 3/4), 4.70mm Voltage - Forward (Vf) (Typ) 2V Current - Test 20mA Viewing Angle 20° Mounting Type Through Hole Wavelength - Dominant - Wavelength - Peak 610nm Features - Package / Case Radial Supplier Device Package T-1 3/4 Size / Dimension - Height (Max) 8.60mm	Manufacturer Part Number	SSL-LX5093XAC
Package Radial Series - Color Amber Configuration - Lens Color Colorless Lens Transparency Clear Millicandela Rating 600mcd Lens Style/Size Round with Domed Top, 5mm (T-1 3/4), 4.70mm Voltage - Forward (Vf) (Typ) 2V Current - Test 20mA Viewing Angle 20° Mounting Type Through Hole Wavelength - Dominant - Wavelength - Peak 610nm Features - Package / Case Radial Supplier Device Package T-1 3/4 Size / Dimension - Height (Max) 8.60mm	Manufacturer	Lumex Opto/Components Inc.
Package Radial Series - Color Amber Configuration - Lens Color Colorless Lens Transparency Clear Millicandela Rating 600mcd Lens Style/Size Round with Domed Top, 5mm (T-1 3/4), 4.70mm Voltage - Forward (Vf) (Typ) 2V Current - Test 20mA Viewing Angle 20° Mounting Type Through Hole Wavelength - Dominant - Wavelength - Peak 610nm Features - Package / Case Radial Supplier Device Package T-1 3/4 Size / Dimension - Height (Max) 8.60mm	Category	Optoelectronics
Series - Color Amber Configuration - Lens Color Colorless Lens Transparency Clear Millicandela Rating 600mcd Lens Style/Size Round with Domed Top, 5mm (T-1 3/4), 4.70mm Voltage - Forward (Vf) (Typ) 2V Current - Test 20mA Viewing Angle 20° Mounting Type Through Hole Wavelength - Dominant - Wavelength - Peak 610nm Features - Package / Case Radial Supplier Device Package T-1 3/4 Size / Dimension - Height (Max) 8.60mm		LED Indication - Discrete
ColorAmberConfiguration-Lens ColorColorlessLens TransparencyClearMillicandela Rating600mcdLens Style/SizeRound with Domed Top, 5mm (T-1 3/4), 4.70mmVoltage - Forward (Vf) (Typ)2VCurrent - Test20mAViewing Angle20°Mounting TypeThrough HoleWavelength - Dominant-Features-Package / CaseRadialSupplier Device PackageT-1 3/4Size / Dimension-Height (Max)8.60mm	Package	Radial
Configuration-Lens ColorColorlessLens TransparencyClearMillicandela Rating600mcdLens Style/SizeRound with Domed Top, 5mm (T-1 3/4), 4.70mmVoltage - Forward (Vf) (Typ)2VCurrent - Test20mAViewing Angle20°Mounting TypeThrough HoleWavelength - Dominant-Features-Package / CaseRadialSupplier Device PackageT-1 3/4Size / Dimension-Height (Max)8.60mm	Series	-
Lens ColorColorlessLens TransparencyClearMillicandela Rating600mcdLens Style/SizeRound with Domed Top, 5mm (T-1 3/4), 4.70mmVoltage - Forward (Vf) (Typ)2VCurrent - Test20mAViewing Angle20°Mounting TypeThrough HoleWavelength - Dominant-Features-Package / CaseRadialSupplier Device PackageT-1 3/4Size / Dimension-Height (Max)8.60mm	Color	Amber
Lens TransparencyClearMillicandela Rating600mcdLens Style/SizeRound with Domed Top, 5mm (T-1 3/4), 4.70mmVoltage - Forward (Vf) (Typ)2VCurrent - Test20mAViewing Angle20°Mounting TypeThrough HoleWavelength - Dominant-Features-Package / CaseRadialSupplier Device PackageT-1 3/4Size / Dimension-Height (Max)8.60mm	Configuration	-
Millicandela Rating 600mcd Lens Style/Size Round with Domed Top, 5mm (T-1 3/4), 4.70mm Voltage - Forward (Vf) (Typ) 2V Current - Test 20mA Viewing Angle 20° Mounting Type Through Hole Wavelength - Dominant - Wavelength - Peak 610nm Features - Package / Case Radial Supplier Device Package T-1 3/4 Size / Dimension - Height (Max) 8.60mm	Lens Color	Colorless
Lens Style/SizeRound with Domed Top, 5mm (T-1 3/4), 4.70mmVoltage - Forward (Vf) (Typ)2VCurrent - Test20mAViewing Angle20°Mounting TypeThrough HoleWavelength - Dominant-Wavelength - Peak610nmFeatures-Package / CaseRadialSupplier Device PackageT-1 3/4Size / Dimension-Height (Max)8.60mm	Lens Transparency	Clear
Voltage - Forward (Vf) (Typ) Current - Test 20mA Viewing Angle 20° Mounting Type Through Hole Wavelength - Dominant - Wavelength - Peak 610nm Features Package / Case Radial Supplier Device Package T-1 3/4 Size / Dimension Height (Max) 2V 20mA Characteristics Analysis 20° Through Hole Analysis Analysis Analysis Analysis Analysis Analysis T-1 3/4 Size / Dimension Analysis Analysis	Millicandela Rating	600mcd
Current - Test 20mA Viewing Angle 20° Mounting Type Through Hole Wavelength - Dominant - Wavelength - Peak 610nm Features - Package / Case Radial Supplier Device Package T-1 3/4 Size / Dimension - Height (Max) 8.60mm	Lens Style/Size	Round with Domed Top, 5mm (T-1 3/4), 4.70mm
Viewing Angle20°Mounting TypeThrough HoleWavelength - Dominant-Wavelength - Peak610nmFeatures-Package / CaseRadialSupplier Device PackageT-1 3/4Size / Dimension-Height (Max)8.60mm	Voltage - Forward (Vf) (Typ)	2V
Mounting TypeThrough HoleWavelength - Dominant-Wavelength - Peak610nmFeatures-Package / CaseRadialSupplier Device PackageT-1 3/4Size / Dimension-Height (Max)8.60mm	Current - Test	20mA
Wavelength - Dominant - Wavelength - Peak 610nm Features - Package / Case Radial Supplier Device Package T-1 3/4 Size / Dimension - Height (Max) 8.60mm	Viewing Angle	20°
Wavelength - Peak 610nm Features - Package / Case Radial Supplier Device Package T-1 3/4 Size / Dimension - Height (Max) 8.60mm	Mounting Type	Through Hole
Features - Package / Case Radial Supplier Device Package T-1 3/4 Size / Dimension - Height (Max) 8.60mm	Wavelength - Dominant	-
Package / Case Radial Supplier Device Package T-1 3/4 Size / Dimension - Height (Max) 8.60mm	Wavelength - Peak	610nm
Supplier Device Package T-1 3/4 Size / Dimension - Height (Max) 8.60mm	Features	-
Size / Dimension - Height (Max) 8.60mm	Package / Case	Radial
Height (Max) 8.60mm	Supplier Device Package	T-1 3/4
	Size / Dimension	-
Report errors?	Height (Max)	8.60mm
		Report errors?

SSL-LX5093XAC Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SSL-LX5093XAC Payment Methods



















SSL-LX5093XAC Shipping Methods













If you have any question about SSL-LX5093XAC, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com