



SSL-LXA228SGC Information

www.gelsener.com

For Reference Only

Part Number SSL-LXA228SGC

Manufacturer Lumex Opto/Components Inc.

Category Optoelectronics

LED Indication - Discrete

Description LED GREEN 565NM AXIAL

Package Axial, Flat Leads

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SSL-LXA228SGC Specifications

Manufacturer Part Number SSL-LXA228SGC Manufacturer Lumex Opto/Components Inc. Category Optoelectronics LED Indication - Discrete Package Axial, Flat Leads Series - Color Green Configuration - Lens Color Colorless Lens Transparency Clear Millicandela Rating 50mcd Lens Style/Size Round with Domed Top, 1.90mm Voltage - Forward (Vf) (Typ) 2.2V Current - Test 20mA Viewing Angle 25° Mounting Type Through Hole, Axial Wavelength - Dominant - Wavelength - Peak 565mm Features - Package / Case Axial, Flat Leads Supplier Device Package Axial Size / Dimension 2.50mm L x 2.00mm W Height (Max) 2.80mm	*	
Category Optoelectronics LED Indication - Discrete Package Axial, Flat Leads Series - Color Green Configuration - Lens Color Colorless Lens Transparency Clear Millicandela Rating 50mcd Lens Style/Size Round with Domed Top, 1.90mm Voltage - Forward (Vf) (Typ) 2.2V Current - Test 20mA Viewing Angle 25° Mounting Type Through Hole, Axial Wavelength - Dominant - Wavelength - Peak 565nm Features - Package / Case Axial, Flat Leads Supplier Device Package Axial Size / Dimension 2.50mm L x 2.00mm W Height (Max) 2.80mm	Manufacturer Part Number	SSL-LXA228SGC
Package Axial, Flat Leads Series - Color Green Configuration - Lens Color Colorless Lens Transparency Clear Millicandela Rating 50mcd Lens Style/Size Round with Domed Top, 1.90mm Voltage - Forward (Vf) (Typ) 2.2V Current - Test 20mA Viewing Angle 25° Mounting Type Through Hole, Axial Wavelength - Dominant - Wavelength - Peak 565nm Features - Package / Case Axial, Flat Leads Supplier Device Package Axial Size / Dimension 2.50mm L x 2.00mm W Height (Max) 2.80mm	Manufacturer	Lumex Opto/Components Inc.
Package Axial, Flat Leads Series - Color Green Configuration - Lens Color Colorless Lens Transparency Clear Millicandela Rating 50mcd Lens Style/Size Round with Domed Top, 1.90mm Voltage - Forward (Vf) (Typ) 2.2V Current - Test 20mA Viewing Angle 25° Mounting Type Through Hole, Axial Wavelength - Dominant - Wavelength - Peak 565nm Features - Package / Case Axial, Flat Leads Supplier Device Package Axial Size / Dimension 2.50mm L x 2.00mm W Height (Max) 2.80mm	Category	Optoelectronics
Series - Color Green Configuration - Lens Color Colorless Lens Transparency Clear Millicandela Rating 50mcd Lens Style/Size Round with Domed Top, 1.90mm Voltage - Forward (Vf) (Typ) 2.2V Current - Test 20mA Viewing Angle 25° Mounting Type Through Hole, Axial Wavelength - Dominant - Wavelength - Peak 565nm Features - Package / Case Axial, Flat Leads Supplier Device Package Axial Size / Dimension 2.50mm L x 2.00mm W Height (Max) 2.80mm		LED Indication - Discrete
Color Green Configuration - Lens Color Colorless Lens Transparency Clear Millicandela Rating 50mcd Lens Style/Size Round with Domed Top, 1.90mm Voltage - Forward (Vf) (Typ) 2.2V Current - Test 20mA Viewing Angle 25° Mounting Type Through Hole, Axial Wavelength - Dominant - Wavelength - Peak 565nm Features - Package / Case Axial, Flat Leads Supplier Device Package Axial Size / Dimension 2.50mm L x 2.00mm W Height (Max) 2.80mm	Package	Axial, Flat Leads
Configuration - Lens Color Colorless Lens Transparency Clear Millicandela Rating 50mcd Lens Style/Size Round with Domed Top, 1.90mm Voltage - Forward (Vf) (Typ) 2.2V Current - Test 20mA Viewing Angle 25° Mounting Type Through Hole, Axial Wavelength - Dominant - Wavelength - Peak 565nm Features - Package / Case Axial, Flat Leads Supplier Device Package Axial Size / Dimension 2.50mm L x 2.00mm W Height (Max) 2.80mm	Series	-
Lens ColorColorlessLens TransparencyClearMillicandela Rating50mcdLens Style/SizeRound with Domed Top, 1.90mmVoltage - Forward (Vf) (Typ)2.2VCurrent - Test20mAViewing Angle25°Mounting TypeThrough Hole, AxialWavelength - Dominant-Features-Package / CaseAxial, Flat LeadsSupplier Device PackageAxialSize / Dimension2.50mm L x 2.00mm WHeight (Max)2.80mm	Color	Green
Lens TransparencyClearMillicandela Rating50mcdLens Style/SizeRound with Domed Top, 1.90mmVoltage - Forward (Vf) (Typ)2.2VCurrent - Test20mAViewing Angle25°Mounting TypeThrough Hole, AxialWavelength - Dominant-Vavelength - Peak565nmFeatures-Package / CaseAxial, Flat LeadsSupplier Device PackageAxialSize / Dimension2.50mm L x 2.00mm WHeight (Max)2.80mm	Configuration	-
Millicandela Rating Lens Style/Size Round with Domed Top, 1.90mm Voltage - Forward (Vf) (Typ) 2.2V Current - Test 20mA Viewing Angle Yiewing Angle Through Hole, Axial Wavelength - Dominant - Wavelength - Peak Features - Package / Case Axial, Flat Leads Supplier Device Package Size / Dimension Height (Max) 50mcd Round with Domed Top, 1.90mm 2.2V 2.2V 2.0mA - Through Hole, Axial - - - - - - - - - - - - -	Lens Color	Colorless
Lens Style/SizeRound with Domed Top, 1.90mmVoltage - Forward (Vf) (Typ)2.2VCurrent - Test20mAViewing Angle25°Mounting TypeThrough Hole, AxialWavelength - Dominant-Wavelength - Peak565nmFeatures-Package / CaseAxial, Flat LeadsSupplier Device PackageAxialSize / Dimension2.50mm L x 2.00mm WHeight (Max)2.80mm	Lens Transparency	Clear
Voltage - Forward (Vf) (Typ) Current - Test 20mA Viewing Angle 25° Mounting Type Through Hole, Axial Wavelength - Dominant - Wavelength - Peak 565nm Features - Package / Case Axial, Flat Leads Supplier Device Package Size / Dimension Height (Max) 2.20mA 25° Aksial	Millicandela Rating	50mcd
Current - Test 20mA Viewing Angle 25° Mounting Type Through Hole, Axial Wavelength - Dominant - Wavelength - Peak 565nm Features - Package / Case Axial, Flat Leads Supplier Device Package Axial Size / Dimension 2.50mm L x 2.00mm W Height (Max) 2.80mm	Lens Style/Size	Round with Domed Top, 1.90mm
Viewing Angle25°Mounting TypeThrough Hole, AxialWavelength - Dominant-Wavelength - Peak565nmFeatures-Package / CaseAxial, Flat LeadsSupplier Device PackageAxialSize / Dimension2.50mm L x 2.00mm WHeight (Max)2.80mm	Voltage - Forward (Vf) (Typ)	2.2V
Mounting Type Through Hole, Axial Wavelength - Dominant - Wavelength - Peak 565nm Features - Package / Case Axial, Flat Leads Supplier Device Package Axial Size / Dimension 2.50mm L x 2.00mm W Height (Max) 2.80mm	Current - Test	20mA
Wavelength - Dominant Wavelength - Peak 565nm Features - Package / Case Axial, Flat Leads Supplier Device Package Axial Size / Dimension 2.50mm L x 2.00mm W Height (Max) 2.80mm	Viewing Angle	25°
Wavelength - Peak 565nm Features	Mounting Type	Through Hole, Axial
Features - Package / Case Axial, Flat Leads Supplier Device Package Axial Size / Dimension 2.50mm L x 2.00mm W Height (Max) 2.80mm	Wavelength - Dominant	-
Package / Case Axial, Flat Leads Supplier Device Package Axial Size / Dimension 2.50mm L x 2.00mm W Height (Max) 2.80mm	Wavelength - Peak	565nm
Supplier Device Package Axial Size / Dimension 2.50mm L x 2.00mm W Height (Max) 2.80mm	Features	-
Size / Dimension 2.50mm L x 2.00mm W Height (Max) 2.80mm	Package / Case	Axial, Flat Leads
Height (Max) 2.80mm	Supplier Device Package	Axial
	Size / Dimension	2.50mm L x 2.00mm W
Report errors?	Height (Max)	2.80mm
		Report errors?

SSL-LXA228SGC Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SSL-LXA228SGC Payment Methods



















SSL-LXA228SGC Shipping Methods













If you have any question about SSL-LXA228SGC, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com