

SSQ-132-02-G-S

SSQ-132-02-G-S Information





Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



SSQ-132-02-G-S Specifications

ManufacturerSamee Inc.CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesSSQConnector TypeReceptacleConnector TypeReceptacleContact TypeBoard to Board or CableStyleBoard to Board or CableNumber of Positions32Number of Positions LoadedINumber of Rows1Number of Rows1Number of RowsSolderFreminationSolderContact TypeGoldFastening TypeGoldContact Finish - MatingGoldContact Finish - MatingBack				
CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesSSQConnector TypeRecptacleContact TypeForkedStyleBoard to Board or CableNumber of Positions32Number of Positions Loaded1Pich - Mating100° (2.54mm)Number of Rows1Number of Rows50Number of Positing50StyleSolderNumber of Rows1Row Spacing - Mating50StyleSolderFerninationSolderForting TypeSolderContact Finish - MatingGoldContact Finish - MatingSolderInsulation ColorBiack	Manufacturer Part Number	SSQ-132-02-G-S		
Indext of the standard of the	Manufacturer	Samtec Inc.		
Package-SeriesSSQConnector TypeReceptacleContact TypeForkedStyleBoard to Board or CableNumber of Positions32Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleFastening TypeSolderFastening TypeGoldContact Finish - MatingGoldInsulation ColorBlack	Category	Connectors, Interconnects		
SeriesSSQConnector TypeReceptacleContact TypeForkedStyleBoard to Board or CableNumber of Positions32Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleFastening TypeSolderContact Finish - MatingGoldContact Finish - MatingGoldInsulation ColorBlack		Rectangular Connectors - Headers, Receptacles, Female Sockets		
Connector TypeReceptacleContact TypeForkedStyleBoard to Board or CableNumber of Positions32Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleFastening TypeSolderContact Finish - MatingGoldContact Finish Thickness - MatingJuin (0.51µm)Insulation ColorBlack	Package	-		
Contact TypeForkedStyleBoard to Board or CableNumber of Positions32Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldIonatt Finish Thickness - MatingBlack	Series	SSQ		
StyleBoard to Board or CableNumber of Positions32Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldIonator Finish Thickness - MatingBlack	Connector Type	Receptacle		
Number of Positions32Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlack	Contact Type	Forked		
Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingBlack	Style	Board to Board or Cable		
Pitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingOqin (0.51µm)Isulation ColorBlack	Number of Positions	32		
Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlack	Number of Positions Loaded	All		
Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingJupin (0.51µm)Isulation ColorBlack	Pitch - Mating	0.100" (2.54mm)		
Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlack	Number of Rows	1		
TerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlack	Row Spacing - Mating	-		
Fastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlack	Mounting Type	Through Hole		
Contact Finish - MatingGoldContact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlack	Termination	Solder		
Contact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlack	Fastening Type	Push-Pull		
Insulation Color Black	Contact Finish - Mating	Gold		
	Contact Finish Thickness - Mating	20µin (0.51µm)		
Insulation Height 0.335" (8.51mm)	Insulation Color	Black		
	Insulation Height	0.335" (8.51mm)		
Contact Length - Post 0.194" (4.93mm)	Contact Length - Post	0.194" (4.93mm)		
Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$	Operating Temperature	-55°C ~ 125°C		
Material Flammability Rating UL94 V-0	Material Flammability Rating	UL94 V-0		

Contact Finish - Post	Gold	
Mated Stacking Heights	-	
Ingress Protection	-	
Features	-	
		Report errors?

SSQ-132-02-G-S Guarantees




Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about SSQ-132-02-G-S, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com