

ST-5-10 Information



For Reference Only

Part Number ST-5-10

Manufacturer Signal Transformer Category Transformers

Power Transformers

Description XFRMR LAMINATED 12VA THRU HOLE

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ST-5-10 Specifications

Manufacturer Part Number ST-5-10 Manufacturer Signal Transformer Category Transformers Package - Series ST Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Parallel 2.4A, Series 1.2A Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max 12 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 47.80mm L x 39.60mm W Height - Seated (Max) 36.90mm Voltage - Isolation 2500Vrms Weight 0.7 lb (317.51g)		
Category Transformers Power Transformers Package - Series ST Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Parallel 2.4A, Series 1.2A Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max 12 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 47.80mm L x 39.60mm W Height - Seated (Max) 36.90mm Voltage - Isolation 2500Vrms Weight 0.7 lb (317.51g)	Manufacturer Part Number	ST-5-10
Package Series ST Type Laminated Core Voltage - Primary Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Primary Winding(s) Secondary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max 12 VA Mounting Type Through Hole Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Weight Power Transformers ST A By Bower Transformers A ST Bower Transformers A NO Through Core Parallel 2.4A, Series 1.2A Primary Winding(s) Single Single Dual Center Tap No Power - Max 12 VA Mounting Type Through Hole For Pin Size / Dimension 47.80mm L x 39.60mm W Voltage - Isolation 2500Vrms Weight	Manufacturer	Signal Transformer
Package - Series ST Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Parallel 2.4A, Series 1.2A Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max 12 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 47.80mm L x 39.60mm W Height - Seated (Max) 36.90mm Voltage - Isolation 57.1b (317.51g)	Category	Transformers
Series ST Type Laminated Core Voltage - Primary 115 V Voltage - Secondary (Full Load) Parallel 5 V, Series 10 V Current - Output (Max) Parallel 2.4A, Series 1.2A Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max 12 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 47.80mm L x 39.60mm W Height - Seated (Max) 36.90mm Voltage - Isolation 2500 Vrms Weight		Power Transformers
Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Parallel 2.4A, Series 1.2A Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max 12 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 47.80mm L x 39.60mm W Height - Seated (Max) 36.90mm Voltage - Isolation 2500Vrms Weight	Package	-
Voltage - Primary Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Primary Winding(s) Secondary Winding(s) Secondary Winding(s) Center Tap No Power - Max 12 VA Mounting Type Through Hole Termination Style Size / Dimension 47.80mm L x 39.60mm W Height - Seated (Max) Voltage - Isolation Weight 115V Parallel 5V, Series 10V Parallel 2.4A, Series 1.2A Parallel 2.4A, Series 1.2A Parallel 5V, Series 10V Parallel 2.4A, Series 1.2A Primary Winding(s) Single Secondary Winding(s) Single Secondary Winding(s) Single Single Secondary Winding(s) Single Single Solution Single Single Single Single Single Single Single Single Single Single Single Single Single S	Series	ST
Voltage - Secondary (Full Load) Current - Output (Max) Parallel 5V, Series 10V Parallel 2.4A, Series 1.2A Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max 12 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 47.80mm L x 39.60mm W Height - Seated (Max) Voltage - Isolation Voltage - Isolation Weight	Type	Laminated Core
Current - Output (Max) Primary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max 12 VA Mounting Type Through Hole Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Weight Parallel 2.4A, Series 1.2A Parallel 2.4A, Series 1.2A Parallel 2.4A, Series 1.2A Parallel 2.4A, Series 1.2A Pount Parallel 2.4A, Series 1.2A Pount Pount No 12 VA No 12 VA 47.80mm L x 39.60mm W 2500Vrms Voltage - Isolation 0.7 lb (317.51g)	Voltage - Primary	115V
Primary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max 12 VA Mounting Type Through Hole Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Weight Single Single Single Single Single Single Single Available No No 12 VA Through Hole PC Pin 47.80mm L x 39.60mm W 36.90mm Voltage - Isolation 2500Vrms 0.7 lb (317.51g)	Voltage - Secondary (Full Load)	Parallel 5V, Series 10V
Secondary Winding(s)DualCenter TapNoPower - Max12 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension47.80mm L x 39.60mm WHeight - Seated (Max)36.90mmVoltage - Isolation2500VrmsWeight0.7 lb (317.51g)	Current - Output (Max)	Parallel 2.4A, Series 1.2A
Center Tap No Power - Max 12 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 47.80mm L x 39.60mm W Height - Seated (Max) 36.90mm Voltage - Isolation 2500Vrms Weight 0.7 lb (317.51g)	Primary Winding(s)	Single
Power - Max Mounting Type Through Hole Termination Style PC Pin Size / Dimension 47.80mm L x 39.60mm W Height - Seated (Max) Voltage - Isolation Voltage - Isolation Weight 12 VA 12 VA 16 VA 17 VA 18 VA 18 VA 19 VA 19 VO Pin 47.80mm L x 39.60mm W 36.90mm 47.80mm L x 39.60mm W 36.90mm Voltage - Isolation 2500Vrms 0.7 lb (317.51g)	Secondary Winding(s)	Dual
Mounting TypeThrough HoleTermination StylePC PinSize / Dimension47.80mm L x 39.60mm WHeight - Seated (Max)36.90mmVoltage - Isolation2500VrmsWeight0.7 lb (317.51g)	Center Tap	No
Termination Style PC Pin Size / Dimension 47.80mm L x 39.60mm W Height - Seated (Max) 36.90mm Voltage - Isolation 2500Vrms Weight 0.7 lb (317.51g)	Power - Max	12 VA
Size / Dimension47.80mm L x 39.60mm WHeight - Seated (Max)36.90mmVoltage - Isolation2500VrmsWeight0.7 lb (317.51g)	Mounting Type	Through Hole
Height - Seated (Max) Voltage - Isolation Weight 36.90mm 2500Vrms 0.7 lb (317.51g)	Termination Style	PC Pin
Voltage - Isolation 2500Vrms Weight 0.7 lb (317.51g)	Size / Dimension	47.80mm L x 39.60mm W
Weight 0.7 lb (317.51g)	Height - Seated (Max)	36.90mm
	Voltage - Isolation	2500Vrms
Report errors?	Weight	0.7 lb (317.51g)
		Report errors?

ST-5-10 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ST-5-10 Payment Methods





















ST-5-10 Shipping Methods













If you have any question about ST-5-10, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com