

ST-6-12 Information



For Reference Only

Part Number ST-6-12

ManufacturerSignal TransformerCategoryTransformers

Power Transformers
XFRMR LAMINATED 20VA THRU HOLE

Description XFR **Package** -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ST-6-12 Specifications

Manufacturer ST-6-12 Manufacturer Signal Transformer Category Transformers Power Transformers Power Transformers Package - Series ST Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) Parallel 6.3V, Series 12.6V Current - Output (Max) Parallel 3.2A, Series 1.6A Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max 20 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 57.20mm L x 47.60mm W Height - Seated (Max) 36.90mm Voltage - Isolation 2500Vrms Weight 0.8 lb (362.87g)		
Category Transformers Package - Series ST Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) Parallel 6.3V, Series 12.6V Current - Output (Max) Parallel 3.2A, Series 1.6A Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max 20 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 57.20mm L x 47.60mm W Height - Seated (Max) 36.90mm Voltage - Isolation 2500Vrms Weight 0.8 lb (362.87g)	Manufacturer Part Number	ST-6-12
Package - Series ST Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) Parallel 6.3V, Series 12.6V Current - Output (Max) Parallel 3.2A, Series 1.6A Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max 20 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 57.20mm L x 47.60mm W Height - Seated (Max) 36.90mm Voltage - Isolation 2500Vrms Weight 0.8 lb (362.87g)	Manufacturer	Signal Transformer
Package - Series ST Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) Parallel 6.3V, Series 12.6V Current - Output (Max) Parallel 3.2A, Series 1.6A Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max 20 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 57.20mm L x 47.60mm W Height - Seated (Max) 36.90mm Voltage - Isolation 2500Vrms Weight 0.8 lb (362.87g)	Category	Transformers
SeriesSTTypeLaminated CoreVoltage - Primary115 VVoltage - Secondary (Full Load)Parallel 6.3 V, Series 12.6 VCurrent - Output (Max)Parallel 3.2 A, Series 1.6 APrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max20 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension57.20mm L x 47.60mm WHeight - Seated (Max)36.90mmVoltage - Isolation2500VrmsWeight0.8 lb (362.87g)		Power Transformers
Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) Parallel 6.3V, Series 12.6V Current - Output (Max) Parallel 3.2A, Series 1.6A Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max 20 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 57.20mm L x 47.60mm W Height - Seated (Max) 36.90mm Voltage - Isolation 2500Vrms Weight	Package	-
Voltage - Primary Voltage - Secondary (Full Load) Parallel 6.3V, Series 12.6V Current - Output (Max) Parallel 3.2A, Series 1.6A Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max 20 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension Finance (Max) Single PC Pin Size / Dimension 57.20mm L x 47.60mm W Height - Seated (Max) Voltage - Isolation Voltage - Isolation Weight No 2500Vrms 0.8 lb (362.87g)	Series	ST
Voltage - Secondary (Full Load) Current - Output (Max) Parallel 3.2A, Series 1.6A Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max 20 VA Mounting Type Through Hole Termination Style Size / Dimension For 20 mm L x 47.60mm W Height - Seated (Max) Voltage - Isolation Voltage - Isolation Weight Parallel 6.3V, Series 12.6V Single Single No 20 VA Mounting Type Through Hole PC Pin Size / Dimension 57.20mm L x 47.60mm W 36.90mm Voltage - Isolation 0.8 lb (362.87g)	Туре	Laminated Core
Current - Output (Max)Parallel 3.2A, Series 1.6APrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max20 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension57.20mm L x 47.60mm WHeight - Seated (Max)36.90mmVoltage - Isolation2500VrmsWeight0.8 lb (362.87g)	Voltage - Primary	115V
Primary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max 20 VA Mounting Type Through Hole Termination Style Size / Dimension Size / Dimension Height - Seated (Max) Voltage - Isolation Weight Single Single Single No Poul No Poul No Po No Pow Po No	Voltage - Secondary (Full Load)	Parallel 6.3V, Series 12.6V
Secondary Winding(s)DualCenter TapNoPower - Max20 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension57.20mm L x 47.60mm WHeight - Seated (Max)36.90mmVoltage - Isolation2500VrmsWeight0.8 lb (362.87g)	Current - Output (Max)	Parallel 3.2A, Series 1.6A
Center TapNoPower - Max20 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension57.20mm L x 47.60mm WHeight - Seated (Max)36.90mmVoltage - Isolation2500VrmsWeight0.8 lb (362.87g)	Primary Winding(s)	Single
Power - Max Mounting Type Through Hole Termination Style PC Pin Size / Dimension 57.20mm L x 47.60mm W Height - Seated (Max) Voltage - Isolation 2500Vrms Weight 0.8 lb (362.87g)	Secondary Winding(s)	Dual
Mounting TypeThrough HoleTermination StylePC PinSize / Dimension57.20mm L x 47.60mm WHeight - Seated (Max)36.90mmVoltage - Isolation2500VrmsWeight0.8 lb (362.87g)	Center Tap	No
Termination Style PC Pin Size / Dimension 57.20mm L x 47.60mm W Height - Seated (Max) 36.90mm Voltage - Isolation 2500Vrms Weight 0.8 lb (362.87g)	Power - Max	20 VA
Size / Dimension 57.20mm L x 47.60mm W Height - Seated (Max) 36.90mm Voltage - Isolation 2500Vrms Weight 0.8 lb (362.87g)	Mounting Type	Through Hole
Height - Seated (Max) Voltage - Isolation Veight 36.90mm 2500Vrms 0.8 lb (362.87g)	Termination Style	PC Pin
Voltage - Isolation 2500Vrms Weight 0.8 lb (362.87g)	Size / Dimension	57.20mm L x 47.60mm W
Weight 0.8 lb (362.87g)	Height - Seated (Max)	36.90mm
	Voltage - Isolation	2500Vrms
Report errors?	Weight	0.8 lb (362.87g)
		Report errors?

ST-6-12 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ST-6-12 Payment Methods



















ST-6-12 Shipping Methods













If you have any question about ST-6-12, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com