



ST1-L2-DC9V Information

Heisener.com

Part Number ST1-L2-DC9V

Manufacturer Panasonic Electric Works

Category Relays

Power Relays, Over 2 Amps

Description RELAY GENERAL PURPOSE DPST 8A 9V

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ST1-L2-DC9V Specifications

Manufacturer Part NumberST1-L2-DC9VManufacturerPanasonic Electric WorksCategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesSTRelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current25mACoil Voltage9VDCContact FormDPST-NO/NC (1 Form A and B)Contact Rating (Current)8ASwitching Voltage380VAC, 250VDC - MaxTurn On Voltage (Max)7.2 VDCTurn Off Voltage (Min)-Operate Time10msRelease Time10ms		
CategoryRelays Power Relays, Over 2 AmpsPackage-SeriesSTRelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current25mACoil Voltage9VDCContact FormDPST-NO/NC (1 Form A and B)Contact Rating (Current)8ASwitching Voltage380VAC, 250VDC - MaxTurn On Voltage (Max)7.2 VDCTurn Off Voltage (Min)-Operate Time10ms	Manufacturer Part Number	ST1-L2-DC9V
Package - Series ST Relay Type General Purpose Coil Type Latching, Dual Coil Coil Current 25mA Coil Voltage 9VDC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 8A Switching Voltage Max) 7.2 VDC Turn Off Voltage (Min) - Operate Time 10 Power Relays, Over 2 Amps Power Series Power Relays, Over 2 Amps Power Relays, Over 2 Amps Power Series Power Relays, Over 2 Amps Power Relays, Over 2 Amps Power Series Power Relays, Over 2 Amps Power Relays, Over 2 Amps Power Series Power Relays, Over 2 Amps Power Relays, Over 2 Amp	Manufacturer	Panasonic Electric Works
Package - Series ST Relay Type General Purpose Coil Type Latching, Dual Coil Coil Current 25mA Coil Voltage 9VDC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 8A Switching Voltage Max) 7.2 VDC Turn Off Voltage (Min) Operate Time 10ms	Category	Relays
Series ST Relay Type General Purpose Coil Type Latching, Dual Coil Coil Current 25mA Coil Voltage 9VDC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 8A Switching Voltage 380VAC, 250VDC - Max Turn On Voltage (Max) 7.2 VDC Turn Off Voltage (Min) - Operate Time 10ms		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Latching, Dual Coil Coil Current 25mA Coil Voltage 9VDC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 8A Switching Voltage 380VAC, 250VDC - Max Turn On Voltage (Max) 7.2 VDC Turn Off Voltage (Min) - Operate Time 10ms	Package	-
Coil Type Latching, Dual Coil Coil Current 25mA Coil Voltage 9VDC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 8A Switching Voltage 380VAC, 250VDC - Max Turn On Voltage (Max) 7.2 VDC Turn Off Voltage (Min) - Operate Time 10ms	Series	ST
Coil Current 25mA Coil Voltage 9VDC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 8A Switching Voltage 380VAC, 250VDC - Max Turn On Voltage (Max) 7.2 VDC Turn Off Voltage (Min) - Operate Time 10ms	Relay Type	General Purpose
Coil Voltage 9VDC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 8A Switching Voltage 380VAC, 250VDC - Max Turn On Voltage (Max) 7.2 VDC Turn Off Voltage (Min) - Operate Time 10ms	Coil Type	Latching, Dual Coil
Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 8A Switching Voltage 380VAC, 250VDC - Max Turn On Voltage (Max) 7.2 VDC Turn Off Voltage (Min) - Operate Time 10ms	Coil Current	25mA
Contact Rating (Current) Switching Voltage 380VAC, 250VDC - Max Turn On Voltage (Max) 7.2 VDC Turn Off Voltage (Min) Operate Time 10ms	Coil Voltage	9VDC
Switching Voltage 380VAC, 250VDC - Max Turn On Voltage (Max) 7.2 VDC Turn Off Voltage (Min) - Operate Time 10ms	Contact Form	DPST-NO/NC (1 Form A and B)
Turn On Voltage (Max) 7.2 VDC Turn Off Voltage (Min) Operate Time 10ms	Contact Rating (Current)	8A
Turn Off Voltage (Min) Operate Time - 10ms	Switching Voltage	380VAC, 250VDC - Max
Operate Time 10ms	Turn On Voltage (Max)	7.2 VDC
	Turn Off Voltage (Min)	-
Release Time 10ms	Operate Time	10ms
	Release Time	10ms
Features Sealed - Fully	Features	Sealed - Fully
Mounting Type Through Hole	Mounting Type	Through Hole
Termination Style PC Pin	Termination Style	PC Pin
Report errors?		Report errors?

ST1-L2-DC9V Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ST1-L2-DC9V Payment Methods





















ST1-L2-DC9V Shipping Methods













If you have any question about ST1-L2-DC9V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com