

ST10F273M-4QR3

ST10F273M-4QR3 Information

www.betsener.som	ST10F273M-4QR3 STMicroelectronics Integrated Circuits (ICs) Embedded - Microcontrollers IC MCU 16BIT 512KB FLASH 144QFP 144-BQFP For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ST10F273M-4QR3 Specifications

Anufacturer STMicroelectronics Anufacturer Integrated Circuits (ICs) Embedded - Microcontrollers Embedded - Microcontrollers ackage 144-BQFP circe Processor ST10 fore Processor ST0 fore Size 16-Bit peed 40MHz connectivity ASC, CAN, EBI/EMI, 12C, SSC, UART/USART rogram Memory Size 512KB (512K x 8) rogram Memory Size 512KB (512K x 8) rogram Memory Type FLASH AM Size 36K x 8 voltage - Supply (Vcc/Vdd) 4.5 V ~ 5.5 V Aud Size A/D 24x10b voltage - Supply (Vcc/Vdd) 4.0 °C ~ 125°C (TA) voltage / Case 44-BQFP		
Integrated Circuits (ICs) Embedded - Microcontrollers ackage 144-BQFP ore Processor ST10 ore Processor ST0 ore Processor 6-Bit ore ore Size 40MHz orenectivity ASC, CAN, EBI/EMI, I2C, SSC, UART/USART ore ore size POR, PWM, WDT orener of I/O 111 ore organ Memory Size 512KB (512K x 8) organ Memory Type FLASH Voltage - Supply (Vcc/Vdd) 36K x 8 Voltage - Supply (Vcc/Vdd) AD24x10b Voltage - Supply (Vcc/Vdd) Internal Voltage - Supply (Vcc/Vdd) AD24x10b Voltage - Supply (Vcc/Vdd) AD24x10b Voltage - Supply (Vcc/Vdd) Internal Autor AD24x10b Voltage - Supply (Vcc/Vdd) Internal Autor AUC Voltage - Supply (Vcc/Vdd) Internal Autor AUC Voltage - Supply (Vcc/Vdd) Internal Voltage - Supply (Vcc/Vdd) Internal Voltage - Supply (Vcc/Vdd)	Manufacturer Part Number	ST10F273M-4QR3
Embedded - Microcontrollers ackage 144-BQFP strio Strio bore Processor Strio bore Size 16-Bit bore of Vice Size 40MHz borne of Vice Size 40MHz borne of Vice Size POR, PWM, WDT brance of Vice Size 512KB (512K x 8) rogram Memory Size 512KB (512K x 8) congram Memory Type FLASH EPROM Size - AM Size 36K x 8 voltage - Supply (Vcc/Vdd) 4.5 V ~ 5.5 V Aval Converters AvD 24x10b bascillator Type - operating Temperature -40°C ~ 125°C (TA) douting Type -	Manufacturer	STMicroelectronics
ackage144-BQFPeriesST10bore ProcessorST10bore ProcessorI6-Bitbore Size16-Bitpeed40MHzbornectivityASC, CAN, EBI/EMI, 12C, SSC, UART/USARTbornectivityPOR, PWM, WDTbornectivity111borgram Memory Size512KB (512K x 8)corgram Memory TypeFLASHEPROM Size-AM Size36K x 8bord Size Supply (Vcc/Vdd)4.5 V ~ 5.5 Vbord Size Supply (Vcc/Vdd)Internalbord Size Supply (Vcc/Vdd)-40°C ~ 125°C (TA)bord Size Case144-BQFP	Category	Integrated Circuits (ICs)
res ST10 fore Processor ST10 fore Size 16-Bit peed 40MHz fornectivity ASC, CAN, EBI/EMI, I2C, SSC, UART/USART eripherals POR, PWM, WDT funder of I/O 111 rogram Memory Size 512KB (512K x 8) rogram Memory Type FLASH EPROM Size - AM Size 36K x 8 Yoltage - Supply (Vcc/Vdd) 4.5 V ~ 5.5 V Akat Converters A/D 24x10b bettaff Type Internal operating Temperature -40°C ~ 125°C (TA) funding Type - ackage / Case 144-BQFP		Embedded - Microcontrollers
Yore ProcessorST10Yore Size16-Bitped40MHzYonnectivityASC, CAN, EBI/EMI, 12C, SSC, UART/USARTYonnectivityPOR, PWM, WDTYumber of I/O111Yorgam Memory Size512KB (512K x 8)Yorgam Memory TypeFLASHEPROM Size-Yoldage - Supply (Vcc/Vdd)4.5 V ~ 5.5 VYordag ConvertersAND 24x10bYorgam TypeInternalYorgam Type-Yorgam Type	Package	144-BQFP
Yore Size 16-Bit peed 40MHz Jonnectivity ASC, CAN, EBI/EMI, I2C, SSC, UART/USART onnectivity POR, PWM, WDT eripherals POR, PWM, WDT fumber of I/O 111 rogram Memory Size 512KB (512K x 8) rogram Memory Type FLASH EPROM Size - AM Size 36K x 8 Yoltage - Supply (Vcc/Vdd) 4.5 V ~ 5.5 V back Converters And D24x10b byperating Temperature -40°C ~ 125°C (TA) often Sige / Case 144-BQFP	Series	ST10
peed 40MHz connectivity ASC, CAN, EBI/EMI, I2C, SSC, UART/USART eripherals POR, PWM, WDT fumber of I/O 111 rogram Memory Size 512KB (512K x 8) rogram Memory Type FLASH EPROM Size - AM Size 36K x 8 Yoltage - Supply (Vcc/Vdd) 4.5 V ~ 5.5 V Actorverters A/D 24x10b Deparating Temperature -40°C ~ 125°C (TA) Atomiting Type -44BQFP	Core Processor	ST10
Connectivity ASC, CAN, EBI/EMI, I2C, SSC, UART/USART eripherals POR, PWM, WDT fumber of I/O 111 rogram Memory Size 512KB (512K x 8) rogram Memory Type FLASH EPROM Size - AM Size 36K x 8 Yoltage - Supply (Vcc/Vdd) 4.5 V ~ 5.5 V Acconverters A/D 24x10b bertaing Temperature -40°C ~ 125°C (TA) Autoning Type - ackage / Case 144-BQFP	Core Size	16-Bit
eripherals POR, PWM, WDT fumber of I/O 111 rogram Memory Size 512KB (512K x 8) rogram Memory Type FLASH rogram Memory Type - AM Size 36K x 8 roltage - Supply (Vcc/Vdd) 4.5 V ~ 5.5 V Voltage - Supply (Vcc/Vdd) A/D 24x10b Scillator Type Internal Operating Temperature -40°C ~ 125°C (TA) Advage / Case 144-BQFP	Speed	40MHz
Number of I/O 111 rogram Memory Size 512KB (512K x 8) rogram Memory Type FLASH EPROM Size - AM Size 36K x 8 Yoltage - Supply (Vcc/Vdd) 4.5 V ~ 5.5 V Vata Converters A/D 24x10b Scillator Type Internal Operating Temperature -40°C ~ 125°C (TA) Ackage / Case 144-BQFP	Connectivity	ASC, CAN, EBI/EMI, I2C, SSC, UART/USART
rogram Memory Size512KB (512K x 8)rogram Memory TypeFLASHEPROM Size-AM Size36K x 8'oltage - Supply (Vcc/Vdd)4.5 V ~ 5.5 Vvata ConvertersA/D 24x10bScillator TypeInternaloperating Temperature-40°C ~ 125°C (TA)Autage / Case144-BQFP	Peripherals	POR, PWM, WDT
rogram Memory TypeFLASHEPROM Size-AM Size36K x 8oltage - Supply (Vcc/Vdd)4.5 V ~ 5.5 Vbata ConvertersA/D 24x10bbacillator TypeInternaloperating Temperature-40°C ~ 125°C (TA)founting Type-ackage / Case144-BQFP	Number of I/O	111
EPROM Size-AM Size36K x 8Yoltage - Supply (Vcc/Vdd)4.5 V ~ 5.5 VVata ConvertersA/D 24x10bVata ConvertersInternalOperating Temperature-40°C ~ 125°C (TA)Youtning Type-Ackage / Case144-BQFP	Program Memory Size	512KB (512K x 8)
AM Size 36K x 8 Voltage - Supply (Vcc/Vdd) 4.5 V ~ 5.5 V Voltage - Supply (Vcc/Vdd) A/D 24x10b Descillator Type Internal Operating Temperature -40°C ~ 125°C (TA) Youting Type - Ackage / Case 144-BQFP	Program Memory Type	FLASH
Yoltage - Supply (Vcc/Vdd)4.5 V ~ 5.5 VData ConvertersA/D 24x10bDescillator TypeInternalOperating Temperature-40°C ~ 125°C (TA)Mounting Type-ackage / Case144-BQFP	EEPROM Size	-
Data ConvertersA/D 24x10bDescillator TypeInternalOperating Temperature-40°C ~ 125°C (TA)Aounting Type-ackage / Case144-BQFP	RAM Size	36K x 8
Descillator TypeInternalOperating Temperature-40°C ~ 125°C (TA)Mounting Type-ackage / Case144-BQFP	Voltage - Supply (Vcc/Vdd)	4.5 V ~ 5.5 V
Operating Temperature-40°C ~ 125°C (TA)Jounting Type-ackage / Case144-BQFP	Data Converters	A/D 24x10b
Iounting Type - ackage / Case 144-BQFP	Oscillator Type	Internal
ackage / Case 144-BQFP	Operating Temperature	-40°C ~ 125°C (TA)
• •	Mounting Type	-
	Package / Case	144-BQFP
upplier Device Package 144-PQFP (28x28)	Supplier Device Package	144-PQFP (28x28)
Report errors?		Report errors?

ST10F273M-4QR3 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ST10F273M-4QR3 Payment Methods



ST10F273M-4QR3 Shipping Methods



If you have any question about ST10F273M-4QR3, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com