



ST12T2M5ZG Information

Heisener.com

Part Number ST12T2M5ZG Manufacturer APEM Inc. Category Switches

Toggle Switches

Description SWITCH TOGGLE SPDT 6A 125V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ST12T2M5ZG Specifications

Manufacturer Part Number ST12T2M5ZG Manufacturer APEM Inc. Category Switches Package - Series ST Circuit SPDT Switch Function On-Off-On Current Rating 6A (AC), 7A (DC) Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Standard Round Actuator Length 17.45mm Illumination Non-Illuminated Illumination Yype, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.89mm Dia Bushing Thread 15/32-32 Ingress Protection - Features - Report errors?		
Category Switches Package - Series ST Circuit SPDT Switch Function On-Off-On Current Rating 6A (AC), 7A (DC) Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Standard Round Actuator Length 17.45mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.89mm Dia Bushing Thread 15/32-32 Ingress Protection - Features -	Manufacturer Part Number	ST12T2M5ZG
Package - Series ST Circuit SPDT Switch Function On-Off-On Current Rating 6A (AC), 7A (DC) Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Standard Round 17.45mm Illumination Type, Color 11luminated 11lumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.89mm Dia Bushing Thread 15/32-32 Ingress Protection - Features - SPDT	Manufacturer	APEM Inc.
Package - Series ST Circuit SPDT Switch Function On-Off-On Current Rating 6A (AC), 7A (DC) Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Standard Round Actuator Length 17.45mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.89mm Dia Bushing Thread 15/32-32 Ingress Protection - Features -	Category	Switches
SeriesSTCircuitSPDTSwitch FunctionOn-Off-OnCurrent Rating6A (AC), 7A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length17.45mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 11.89mm DiaBushing Thread15/32-32Ingress Protection-Features-		Toggle Switches
CircuitSPDTSwitch FunctionOn-Off-OnCurrent Rating6A (AC), 7A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length17.45mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 11.89mm DiaBushing Thread15/32-32Ingress Protection-Features-	Package	-
Switch Function Current Rating 6A (AC), 7A (DC) Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Standard Round Actuator Length 17.45mm Illumination Non-Illuminated Illumination Type, Color	Series	ST
Current Rating 6A (AC), 7A (DC) Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Standard Round Actuator Length 17.45mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.89mm Dia Bushing Thread 15/32-32 Ingress Protection Features	Circuit	SPDT
Voltage Rating - AC Voltage Rating - DC 30V Actuator Type Standard Round 17.45mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Sushing Thread Ingress Protection Features 125V 30V 30V 30V Standard Round 17.45mm Non-Illumination Non-Illuminated 17.45mm Non-Illuminated 17.45mm Non-Illuminated 17.45mm Non-Illuminated 17.45mm Non-Illuminated 17.45mm Non-Illuminated 15/32-32 Ingress Protection - Features	Switch Function	On-Off-On
Voltage Rating - DC30VActuator TypeStandard RoundActuator Length17.45mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 11.89mm DiaBushing Thread15/32-32Ingress Protection-Features-	Current Rating	6A (AC), 7A (DC)
Actuator Type Standard Round 17.45mm Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.89mm Dia Bushing Thread 15/32-32 Ingress Protection - Features -	Voltage Rating - AC	125V
Actuator Length 17.45mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.89mm Dia Bushing Thread 15/32-32 Ingress Protection - Features	Voltage Rating - DC	30V
IlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 11.89mm DiaBushing Thread15/32-32Ingress Protection-Features-	Actuator Type	Standard Round
Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.89mm Dia Bushing Thread 15/32-32 Ingress Protection - Features -	Actuator Length	17.45mm
Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.89mm Dia Bushing Thread 15/32-32 Ingress Protection Features -	Illumination	Non-Illuminated
Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 11.89mm DiaBushing Thread15/32-32Ingress Protection-Features-	Illumination Type, Color	-
Termination Style Panel Cutout Dimensions Circular - 11.89mm Dia Bushing Thread 15/32-32 Ingress Protection Features -	Illumination Voltage (Nominal)	-
Panel Cutout Dimensions Bushing Thread Ingress Protection Features Circular - 11.89mm Dia 15/32-32	Mounting Type	Panel Mount
Bushing Thread 15/32-32 Ingress Protection - Features -	Termination Style	Solder Lug
Ingress Protection - Features -	Panel Cutout Dimensions	Circular - 11.89mm Dia
Features -	Bushing Thread	15/32-32
	Ingress Protection	-
Report errors?	Features	-
		Report errors?

ST12T2M5ZG Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ST12T2M5ZG Payment Methods



















ST12T2M5ZG Shipping Methods













If you have any question about ST12T2M5ZG, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com