



ST12T3M4ZQ Information

Heisener.com

Part NumberST12T3M4ZQManufacturerAPEM Inc.CategorySwitches

Toggle Switches

Description SWITCH TOGGLE SPDT 6A 125V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ST12T3M4ZQ Specifications

Manufacturer Part Number ST12T3M4ZQ Manufacturer APEM Inc. Category Switches Package - Series ST Circuit SPDT Switch Function On-Off-On Current Rating 6A (AC), 7A (DC) Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Standard Round Actuator Length 11.68mm Illumination Non-Illuminated Illumination Voltage (Nominal) - Mounting Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.89mm Dia Bushing Thread 15/32-32 Ingress Protection - Features - Features -		
CategorySwitchesPackage-SeriesSTCircuitSPDTSwitch FunctionOn-Off-OnCurrent Rating6A (AC), 7A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length11.68mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 11.89mm DiaBushing Thread15/32-32Ingress Protection-Features-	Manufacturer Part Number	ST12T3M4ZQ
Package - Series ST Circuit SPDT Switch Function On-Off-On Current Rating 6A (AC), 7A (DC) Voltage Rating - AC Voltage Rating - DC Actuator Type Standard Round Actuator Length Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Termination Style Panel Cutout Dimensions Sundard Round Solder Lug Panel Cutout Dimensions Circular - 11.89mm Dia Bushing Thread Ingress Protection Features Toggle Switches ST Toggle Switches AC Toggle Switches AC Toggle Switches AC Toggle Switches AC AC AC AC Toggle Switches AC AC AC AC AC AC AC AC AC A	Manufacturer	APEM Inc.
Package - Series ST Circuit SPDT Switch Function On-Off-On Current Rating 6A (AC), 7A (DC) Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Standard Round Actuator Length 11.68mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.89mm Dia Bushing Thread 15/32-32 Ingress Protection - Features -	Category	Switches
SeriesSTCircuitSPDTSwitch FunctionOn-Off-OnCurrent Rating6A (AC), 7A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length11.68mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StylePanel MountPanel Cutout DimensionsCircular - 11.89mm DiaBushing Thread15/32-32Ingress Protection-Features-		Toggle Switches
Circuit SPDT Switch Function On-Off-On Current Rating 6A (AC), 7A (DC) Voltage Rating - AC 125 V Voltage Rating - DC 30 V Actuator Type Standard Round Actuator Length 11.68mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.89mm Dia Bushing Thread 15/32-32 Ingress Protection - Features -	Package	-
Switch Function On-Off-On Current Rating 6A (AC), 7A (DC) Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Standard Round Actuator Length 11.68mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.89mm Dia Bushing Thread 15/32-32 Ingress Protection - Features -	Series	ST
Current Rating6A (AC), 7A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length11.68mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StylePanel MountPanel Cutout DimensionsCircular - 11.89mm DiaBushing Thread15/32-32Ingress Protection-Features-	Circuit	SPDT
Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length11.68mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 11.89mm DiaBushing Thread15/32-32Ingress Protection-Features-	Switch Function	On-Off-On
Voltage Rating - DC30VActuator TypeStandard RoundActuator Length11.68mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 11.89mm DiaBushing Thread15/32-32Ingress Protection-Features-	Current Rating	6A (AC), 7A (DC)
Actuator Type Standard Round Actuator Length 11.68mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.89mm Dia Bushing Thread 15/32-32 Ingress Protection - Features -	Voltage Rating - AC	125V
Actuator Length 11.68mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.89mm Dia Bushing Thread 15/32-32 Ingress Protection - Features Features Indicated 11.68mm Con-Illuminated 11.68mm Circular - 11.89mm Circular	Voltage Rating - DC	30V
Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Solder Lug Panel Cutout Dimensions Circular - 11.89mm Dia Bushing Thread 15/32-32 Ingress Protection - Features	Actuator Type	Standard Round
Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.89mm Dia Bushing Thread 15/32-32 Ingress Protection - Features -	Actuator Length	11.68mm
Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.89mm Dia Bushing Thread 15/32-32 Ingress Protection - Features -	Illumination	Non-Illuminated
Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 11.89mm DiaBushing Thread15/32-32Ingress Protection-Features-	Illumination Type, Color	-
Termination Style Panel Cutout Dimensions Circular - 11.89mm Dia Bushing Thread 15/32-32 Ingress Protection - Features -	Illumination Voltage (Nominal)	-
Panel Cutout Dimensions Bushing Thread Ingress Protection Features Circular - 11.89mm Dia 15/32-32	Mounting Type	Panel Mount
Bushing Thread 15/32-32 Ingress Protection - Features -	Termination Style	Solder Lug
Ingress Protection - Features -	Panel Cutout Dimensions	Circular - 11.89mm Dia
Features -	Bushing Thread	15/32-32
	Ingress Protection	-
Report errors?	Features	-
		Report errors?

ST12T3M4ZQ Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ST12T3M4ZQ Payment Methods





















ST12T3M4ZQ Shipping Methods













If you have any question about ST12T3M4ZQ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com