

## **ST2-DC24V Information**



For Reference Only

Part Number ST2-DC24V

Manufacturer Panasonic Electric Works

**Category** Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE DPST 8A 24V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **ST2-DC24V Specifications**

Manufacturer Part Number  Manufacturer  Panasonic Electric Works  Relays  Power Relays, Over 2 Amps  Package  Series  ST  Relay Type  General Purpose  Coil Type  Non Latching  Coil Current  10mA  Coil Voltage  24VDC  Contact Form  DPST (2 Form A)  Contact Rating (Current)  8A  Switching Voltage  380VAC, 250VDC - Max  Turn On Voltage (Max)  19.2 VDC  Turn Off Voltage (Min)  Operate Time  10ms  Features  Sealed - Fully  Mounting Type  Through Hole  Termination Style	-	
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesSTRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current10mACoil Voltage24VDCContact FormDPST (2 Form A)Contact Rating (Current)8ASwitching Voltage380VAC, 250VDC - MaxTurn On Voltage (Max)19.2 VDCTurn Off Voltage (Min)2.4 VDCOperate Time15msRelease Time10msFeaturesSealed - FullyMounting TypeThrough Hole	Manufacturer Part Number	ST2-DC24V
Package Series ST Relay Type General Purpose Coil Type Non Latching Coil Current 10mA Coil Voltage 24VDC Contact Form DPST (2 Form A) Contact Rating (Current) 8A Switching Voltage 380VAC, 250VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 15ms Release Time 10ms Features Sealed - Fully Mounting Type Trhrough Hole	Manufacturer	Panasonic Electric Works
Package - Series ST Relay Type General Purpose Coil Type Non Latching Coil Current 10mA Coil Voltage 24VDC Contact Form DPST (2 Form A) Contact Rating (Current) 8A Switching Voltage 380VAC, 250VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 15ms Release Time 10ms Features Sealed - Fully Mounting Type Tripose	Category	Relays
Series ST Relay Type General Purpose Coil Type Non Latching Coil Current 10mA Coil Voltage 24VDC Contact Form DPST (2 Form A) Contact Rating (Current) 8A Switching Voltage 380VAC, 250VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 15ms Release Time 10ms Features Sealed - Fully Mounting Type Through Hole		Power Relays, Over 2 Amps
Relay Type General Purpose  Coil Type Non Latching  Coil Current 10mA  Coil Voltage 24VDC  Contact Form DPST (2 Form A)  Contact Rating (Current) 8A  Switching Voltage 380VAC, 250VDC - Max  Turn On Voltage (Max) 19.2 VDC  Turn Off Voltage (Min) 2.4 VDC  Operate Time 15ms  Release Time 10ms  Features Sealed - Fully  Mounting Type Through Hole	Package	-
Coil Type Non Latching Coil Current 10mA Coil Voltage 24VDC Contact Form DPST (2 Form A) Contact Rating (Current) 8A Switching Voltage 380VAC, 250VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 15ms Release Time 10ms Features Sealed - Fully Mounting Type Through Hole	Series	ST
Coil Current 10mA Coil Voltage 24VDC Contact Form DPST (2 Form A) Contact Rating (Current) 8A Switching Voltage 380VAC, 250VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 15ms Release Time 10ms Features Sealed - Fully Mounting Type Through Hole	Relay Type	General Purpose
Coil Voltage 24VDC  Contact Form DPST (2 Form A)  Contact Rating (Current) 8A  Switching Voltage 380VAC, 250VDC - Max  Turn On Voltage (Max) 19.2 VDC  Turn Off Voltage (Min) 2.4 VDC  Operate Time 15ms  Release Time 10ms  Features Sealed - Fully  Mounting Type Through Hole	Coil Type	Non Latching
Contact Form DPST (2 Form A)  Contact Rating (Current) 8A  Switching Voltage 380VAC, 250VDC - Max  Turn On Voltage (Max) 19.2 VDC  Turn Off Voltage (Min) 2.4 VDC  Operate Time 15ms  Release Time 10ms  Features Sealed - Fully  Mounting Type Through Hole	Coil Current	10mA
Contact Rating (Current)  Switching Voltage  380VAC, 250VDC - Max  Turn On Voltage (Max)  19.2 VDC  Turn Off Voltage (Min)  2.4 VDC  Operate Time  15ms  Release Time  10ms  Features  Sealed - Fully  Mounting Type  Through Hole	Coil Voltage	24VDC
Switching Voltage 380VAC, 250VDC - Max  Turn On Voltage (Max) 19.2 VDC  Turn Off Voltage (Min) 2.4 VDC  Operate Time 15ms  Release Time 10ms  Features Sealed - Fully  Mounting Type Through Hole	Contact Form	DPST (2 Form A)
Turn On Voltage (Max)  19.2 VDC  Turn Off Voltage (Min)  2.4 VDC  Operate Time  15ms  Release Time  10ms  Features  Sealed - Fully  Mounting Type  Through Hole	Contact Rating (Current)	8A
Turn Off Voltage (Min)  Operate Time  15ms  Release Time  10ms  Features  Sealed - Fully  Mounting Type  Through Hole	Switching Voltage	380VAC, 250VDC - Max
Operate Time 15ms Release Time 10ms Features Sealed - Fully Mounting Type Through Hole	Turn On Voltage (Max)	19.2 VDC
Release Time 10ms Features Sealed - Fully Mounting Type Through Hole	Turn Off Voltage (Min)	2.4 VDC
Features Sealed - Fully Mounting Type Through Hole	Operate Time	15ms
Mounting Type Through Hole	Release Time	10ms
	Features	Sealed - Fully
Termination Style PC Pin	Mounting Type	Through Hole
	Termination Style	PC Pin
Report errors?		Report errors?

### **ST2-DC24V Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **ST2-DC24V Payment Methods**





















## **ST2-DC24V Shipping Methods**













If you have any question about ST2-DC24V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com