

ST3-16B9

ST3-16B9 Information

Heisener.com	Part Number Manufacturer Category Description Package	ST3-16B9 Pulse Electronics Power Transformers Power Transformers XFRMR LAMINATED 2.4VA THRU HOLE - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ST3-16B9 Specifications

Manufacturer Part NumberST3-16B9ManufacturerPulse Electronics PowerCategoryTransformersPackage-SeriesSplit Bobin Plug-InTypeLaminated CoreVoltage - PrimaryISVVoltage - Secondary (Full Load)Parallel 300mA, Series 150mACurrent - Output (Max)SingleSecondary Winding(s)SingleSecondary Winding(s)NoPower - Max2.4 VAMounting TypeThrough HoleSize / DinensionSicosma L x 28.70mm WHeight - Secatol (Max)Sicosma L x 28.70mm WWoltage - IsolationSicosma L x 28.70mm WWinding SyleSicosma L x 28.70mm WWoltage - IsolationSicosma L x 28.70mm WWinding TypeSicosma L x 28.70mm WWinding TypeSicosma L x 28.70mm WWinding SyleSicosma L x 28.70mm W		
CategoryTransformersPackage-SeriesSplit Bobin Plug-InTypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)Parallel 8V, Series 16VCurrent - Output (Max)SinglePrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max2.4 VAMounting TypeScong HoleSize / DimensionSicosm L x 28.70m WSize / Dimension3.03mm L x 28.70m WVoltage - IsolationSicoVrmsWeightSico Vrms	Manufacturer Part Number	ST3-16B9
Power TransformersPackage-SeriesSplit Bobin Plug-InTypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)Parallel 8V, Series 16VCurrent - Output (Max)Parallel 300mA, Series 150mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max2.4 VAMounting TypeThrough HoleSize / DimensionS5.05m L x 28.70mm WSize / Dimension30.23mmVoltage - Isolation2500VrmsWeight0.25 lb (113.4g)	Manufacturer	Pulse Electronics Power
Package.SeriesSpit Bobbin Plug-InTypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)Paralel 8V, Series 16VCurrent - Output (Max)Paralel 300mA, Series 150mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - MaxArrough HolePrimination StyleStorm L x 2870mm WSize/ DimensionStorm L x 2870mm WHeight - Seated (Max)Storm L x 2870mm WWoltage - IsolationStorm Size Size Size Size Size Size Size Size	Category	Transformers
SeriesSplit Bobbin Plug-InTypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)Parallel 8V, Series 16VCurrent - Output (Max)Parallel 300mA, Series 150mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max2.4 VAMounting TypeThrough HoleTermination StyleS105m L x 28.70mm WSize / Dimension3.023mmHeight - Seated (Max)S00VrmsWeight0.25 lb (113.4g)		Power Transformers
TypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)Parallel 8V, Series 16VCurrent - Output (Max)Parallel 300mA, Series 150mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max2.4 VAMounting TypeThrough HoleTermination StyleS0.5mm L x 28.70mm WSize / Dimension30.23mmHeight - Seated (Max)2500VrmsWeight0.25 lb (113.4g)	Package	-
AVoltage - Primary115VVoltage - Secondary (Full Load)Parallel 8V, Series 16VCurrent - Output (Max)Parallel 300mA, Series 150mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max2.4 VAMounting TypeThrough HoleTermination StyleScomm L x 28.70mm WSize / Dimension30.23mmHeight - Seated (Max)2500VrmsWeight0.25 lb (113.4g)	Series	Split Bobbin Plug-In
Voltage - Secondary (Full Load)Parallel 8V, Series 16VCurrent - Output (Max)Parallel 300mA, Series 150mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max2.4 VAMounting TypeThrough HoleTermination StyleScofmm L x 28.70mm WSize / Dimension30.23mmHeight - Seated (Max)StofVrmsWeightStol 113.4g)	Туре	Laminated Core
Current - Output (Max)Parallel 300mA, Series 150mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max2.4 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension35.05mm L x 28.70mm WHeight - Seated (Max)30.23mmVoltage - Isolation2500VrmsWeight0.25 lb (113.4g)	Voltage - Primary	115V
Primary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max2.4 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension35.05mm L x 28.70mm WHeight - Seated (Max)30.23mmVoltage - Isolation2500VrmsWeight0.25 lb (113.4g)	Voltage - Secondary (Full Load)	Parallel 8V, Series 16V
Secondary Winding(s)DualCenter TapNoPower - Max2.4 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension35.05mm L x 28.70mm WHeight - Seated (Max)30.23mmVoltage - Isolation2500VrmsWeight0.25 lb (113.4g)	Current - Output (Max)	Parallel 300mA, Series 150mA
Center TapNoPower - Max2.4 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension35.05mm L x 28.70mm WHeight - Seated (Max)30.23mmVoltage - Isolation2500VrmsWeight0.25 lb (113.4g)	Primary Winding(s)	Single
Power - Max2.4 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension35.05mm L x 28.70mm WHeight - Seated (Max)30.23mmVoltage - Isolation2500VrmsWeight0.25 lb (113.4g)	Secondary Winding(s)	Dual
Mounting TypeThrough HoleTermination StylePC PinSize / Dimension35.05mm L x 28.70mm WHeight - Seated (Max)30.23mmVoltage - Isolation2500VrmsWeight0.25 lb (113.4g)	Center Tap	No
Termination StylePC PinSize / Dimension35.05mm L x 28.70mm WHeight - Seated (Max)30.23mmVoltage - Isolation2500VrmsWeight0.25 lb (113.4g)	Power - Max	2.4 VA
Size / Dimension35.05mm L x 28.70mm WHeight - Seated (Max)30.23mmVoltage - Isolation2500VrmsWeight0.25 lb (113.4g)	Mounting Type	Through Hole
Height - Seated (Max)30.23mmVoltage - Isolation2500VrmsWeight0.25 lb (113.4g)	Termination Style	PC Pin
Voltage - Isolation2500VrmsWeight0.25 lb (113.4g)	Size / Dimension	35.05mm L x 28.70mm W
Weight 0.25 lb (113.4g)	Height - Seated (Max)	30.23mm
	Voltage - Isolation	2500Vrms
Report errors?	Weight	0.25 lb (113.4g)
		Report errors?

ST3-16B9 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about ST3-16B9, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com