

ST4-24B18 Information

Heisener.com

Part Number ST4-24B18

Manufacturer Pulse Electronics Power

Category Transformers

Power Transformers

Description XFRMR LAMINATED 6VA THRU HOLE

Package

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ST4-24B18 Specifications

Manufacturer Part Number ST4-24B18 Manufacturer Pulse Electronics Power Category Transformers Power Transformers Power Transformers Series Split Bobbin Plug-In Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) Parallel 12V, Series 24V Current - Output (Max) Parallel 500mA, Series 250mA Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max 6 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 41.40mm L x 33.27mm W Height - Seated (Max) 33.27mm Voltage - Isolation 2500Vrms Weight 0.44 lb (199.58g)		
CategoryTransformersPackage-SeriesSplit Bobbin Plug-InTypeLaminated CoreVoltage - Primary115 VVoltage - Secondary (Full Load)Parallel 12V, Series 24VCurrent - Output (Max)Parallel 500mA, Series 250mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max6 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension41.40mm L x 33.27mm WVoltage - Isolation2500VrmsWeight0.44 lb (199.58g)	Manufacturer Part Number	ST4-24B18
Package Series Split Bobbin Plug-In Type Laminated Core Voltage - Primary Voltage - Secondary (Full Load) Parallel 12V, Series 24V Current - Output (Max) Parallel 500mA, Series 250mA Primary Winding(s) Secondary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max 6 V A Mounting Type Through Hole Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Voltage - Isolation Voltage - Isolation Power Transformers - Capacitation Split Bobbin Plug-In Laminated Core Split Bobon, Split Bo	Manufacturer	Pulse Electronics Power
Package-SeriesSplit Bobbin Plug-InTypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)Parallel 12V, Series 24VCurrent - Output (Max)Parallel 500mA, Series 250mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max6 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension41.40mm L x 33.27mm WHeight - Seated (Max)33.27mmVoltage - Isolation2500VrmsWeight0.44 lb (199.58g)	Category	Transformers
Series Split Bobbin Plug-In Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) Parallel 12V, Series 24V Current - Output (Max) Parallel 500mA, Series 250mA Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max 6 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 41.40mm L x 33.27mm W Height - Seated (Max) 33.27mm Voltage - Isolation 2500Vrms Weight 0.44 lb (199.58g)		Power Transformers
Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) Parallel 12V, Series 24V Current - Output (Max) Parallel 500mA, Series 250mA Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max 6 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 41.40mm L x 33.27mm W Height - Seated (Max) 33.27mm Voltage - Isolation 2500Vrms Weight 0.44 lb (199.58g)	Package	-
Voltage - Primary Voltage - Secondary (Full Load) Parallel 12V, Series 24V Current - Output (Max) Parallel 500mA, Series 250mA Primary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max 6 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 41.40mm L x 33.27mm W Height - Seated (Max) Voltage - Isolation Weight 115V Parallel 12V, Series 24V Parallel 500mA, Series 250mA Parallel 500mA, Series 250mA Parallel 500mA, Series 250mA Parallel 12V, Series 24V Parallel 12V, Series 250mA Parallel 12V,	Series	Split Bobbin Plug-In
Voltage - Secondary (Full Load) Parallel 12V, Series 24V Current - Output (Max) Parallel 500mA, Series 250mA Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max 6 VA Mounting Type Through Hole Termination Style Size / Dimension 41.40mm L x 33.27mm W Height - Seated (Max) Voltage - Isolation Voltage - Isolation Weight Parallel 12V, Series 24V Parallel 500mA Single Supple Secondary Winding(s) Dual Center Tap No 6 VA Mounting Type Through Hole 2500Vrms Voltage - Isolation O.44 lb (199.58g)	Туре	Laminated Core
Current - Output (Max) Parallel 500mA, Series 250mA Primary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max 6 VA Mounting Type Through Hole Termination Style Size / Dimension 41.40mm L x 33.27mm Voltage - Isolation Voltage - Isolation Veight Parallel 500mA, Series 250mA Parallel 500mA, Series 250mA Single Dual No 8 VA 9 VA 1 VOltage - Sover So	Voltage - Primary	115V
Primary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max 6 VA Mounting Type Through Hole Termination Style Size / Dimension 41.40mm L x 33.27mm W Height - Seated (Max) 33.27mm Voltage - Isolation 2500Vrms Weight 0.44 lb (199.58g)	Voltage - Secondary (Full Load)	Parallel 12V, Series 24V
Secondary Winding(s)DualCenter TapNoPower - Max6 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension41.40mm L x 33.27mm WHeight - Seated (Max)33.27mmVoltage - Isolation2500VrmsWeight0.44 lb (199.58g)	Current - Output (Max)	Parallel 500mA, Series 250mA
Center TapNoPower - Max6 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension41.40mm L x 33.27mm WHeight - Seated (Max)33.27mmVoltage - Isolation2500VrmsWeight0.44 lb (199.58g)	Primary Winding(s)	Single
Power - Max 6 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 41.40mm L x 33.27mm W Height - Seated (Max) 33.27mm Voltage - Isolation 2500Vrms Weight 0.44 lb (199.58g)	Secondary Winding(s)	Dual
Mounting Type Through Hole PC Pin Size / Dimension 41.40mm L x 33.27mm W Height - Seated (Max) 33.27mm Voltage - Isolation 2500Vrms Weight 0.44 lb (199.58g)	Center Tap	No
Termination Style PC Pin Size / Dimension 41.40mm L x 33.27mm W Height - Seated (Max) 33.27mm Voltage - Isolation 2500Vrms Weight 0.44 lb (199.58g)	Power - Max	6 VA
Size / Dimension 41.40mm L x 33.27mm W Height - Seated (Max) 33.27mm Voltage - Isolation 2500Vrms Weight 0.44 lb (199.58g)	Mounting Type	Through Hole
Height - Seated (Max) Voltage - Isolation Veight 33.27mm 2500Vrms 0.44 lb (199.58g)	Termination Style	PC Pin
Voltage - Isolation 2500Vrms Weight 0.44 lb (199.58g)	Size / Dimension	41.40mm L x 33.27mm W
Weight 0.44 lb (199.58g)	Height - Seated (Max)	33.27mm
	Voltage - Isolation	2500Vrms
Report errors?	Weight	0.44 lb (199.58g)
		Report errors?

ST4-24B18 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ST4-24B18 Payment Methods



















ST4-24B18 Shipping Methods













If you have any question about ST4-24B18, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com