

ST4-36B26 Information

Heisener.com

Part Number ST4-36B26

Manufacturer Pulse Electronics Power

Category Transformers

Power Transformers

Description XFRMR LAMINATED 6VA THRU HOLE

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ST4-36B26 Specifications

Manufacturer Part Number Manufacturer Pulse Electronics Power Transformers Power Transformers Power Transformers Power Transformers Power Transformers Power Transformers Power Transformers Power Transformers Power Transformers Power Transformers Power Transformers Power Transformers Power Transformers Power Transformers Power Transformers Power Transformers Power Institute I		
Category Transformers Power Transformers Package Series Split Bobbin Plug-In Type Laminated Core Voltage - Primary Voltage - Secondary (Full Load) Parallel 18V, Series 36V Current - Output (Max) Parallel 340mA, Series 170mA Primary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max Mounting Type Through Hole Termination Style	Manufacturer Part Number	ST4-36B26
Package - Series Split Bobbin Plug-In Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) Parallel 18V, Series 36V Current - Output (Max) Parallel 340mA, Series 170mA Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max 6 VA Mounting Type Through Hole Termination Style	Manufacturer	Pulse Electronics Power
Package - Series Split Bobbin Plug-In Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) Parallel 18V, Series 36V Current - Output (Max) Parallel 340mA, Series 170mA Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max 6 VA Mounting Type Through Hole Termination Style PC Pin	Category	Transformers
Series Split Bobbin Plug-In Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) Parallel 18V, Series 36V Current - Output (Max) Parallel 340mA, Series 170mA Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max 6 V A Mounting Type Through Hole Termination Style PC Pin		Power Transformers
Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) Parallel 18V, Series 36V Current - Output (Max) Parallel 340mA, Series 170mA Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max 6 VA Mounting Type Through Hole Termination Style PC Pin	Package	-
Voltage - Primary Voltage - Secondary (Full Load) Parallel 18V, Series 36V Current - Output (Max) Primary Winding(s) Secondary Winding(s) Center Tap No Power - Max Mounting Type Through Hole Termination Style 115V Parallel 18V, Series 36V Parallel 340mA, Series 170mA Parallel 340mA, Series 170mA No Parallel 340mA, Series 170mA Pinary Winding(s) Dual Center Tap No Power - Max 6 VA Mounting Type Through Hole	Series	Split Bobbin Plug-In
Voltage - Secondary (Full Load)Parallel 18V, Series 36VCurrent - Output (Max)Parallel 340mA, Series 170mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max6 VAMounting TypeThrough HoleTermination StylePC Pin	Туре	Laminated Core
Current - Output (Max) Primary Winding(s) Secondary Winding(s) Center Tap No Power - Max Mounting Type Termination Style Parallel 340mA, Series 170mA Single Dual Dual No Fova For No F	Voltage - Primary	115V
Primary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max6 VAMounting TypeThrough HoleTermination StylePC Pin	Voltage - Secondary (Full Load)	Parallel 18V, Series 36V
Secondary Winding(s)DualCenter TapNoPower - Max6 VAMounting TypeThrough HoleTermination StylePC Pin	Current - Output (Max)	Parallel 340mA, Series 170mA
Center TapNoPower - Max6 VAMounting TypeThrough HoleTermination StylePC Pin	Primary Winding(s)	Single
Power - Max 6 VA Mounting Type Through Hole Termination Style PC Pin	Secondary Winding(s)	Dual
Mounting Type Through Hole Termination Style PC Pin	Center Tap	No
Termination Style PC Pin	Power - Max	6 VA
	Mounting Type	Through Hole
Size / Dimension 41 40mm L x 33 27mm W	Termination Style	PC Pin
TI. TOTHILL IN 33.27 HILL W	Size / Dimension	41.40mm L x 33.27mm W
Height - Seated (Max) 33.27mm	Height - Seated (Max)	33.27mm
Voltage - Isolation 2500Vrms	Voltage - Isolation	2500Vrms
Weight 0.44 lb (199.58g)	Weight	0.44 lb (199.58g)
Report errors?		Report errors?

ST4-36B26 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ST4-36B26 Payment Methods





















ST4-36B26 Shipping Methods













If you have any question about ST4-36B26, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com