

ST5-28B23

ST5-28B23 Information

Heisener.com Betarieroce stant tee	Part Number Manufacturer Category Description Package	ST5-28B23 Pulse Electronics Power Transformers Power Transformers XFRMR LAMINATED 12VA THRU HOLE - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ST5-28B23 Specifications

Manufacturer Part NumberST5-28B23ManufacturerPulse Electronics PowerCategoryTransformersPackage-SeriesSplit Bobbin Plug-InTypeLaminated CoreVoltage - PrimaryI15VVoltage - Secondary (Full Load)Parallel 14V, Series 28VCurrent - Output (Max)Parallel 840mA, Series 420mAPrimary Winding(s)SingleSecondary Winding(s)DualPower - Max12VAMounting TypePrinogh HoleSize / Dimension47.24mm L x 39.62mm WHight - Seated (Max)SionsmVoltage - IsolationSionsmWinding SiSionsmSize / DimensionSionsmSize / DimensionSionsmWinding SiSionsmSize / DimensionSionsmWinding SiSionsmSize / DimensionSionsmSize / DimensionSionsmWinding SiSionsmWinding SiSionsmSize / DimensionSionsmWinding SiSionsmWinding SiSionsmSize / DimensionSionsmWinding SiSionsmWinding SiSionsmWinding SiSionsmSing PortingSionsmSing PortingSionsmWinding SiSionsmWinding SiSionsmWinding SiSionsmWinding SiSionsmWinding SiSionsmWinding SiSionsmWinding SiSionsm		
CategoryTransformersPower TransformersPackage-SeriesSplit Bobbin Plug-InTypeLaminated CoreVoltage - PrimaryIsVVoltage - Secondary (Full Load)Parallel 14V, Series 28VCurrent - Output (Max)SingleSecondary Winding(s)SuigleSecondary Winding(s)DualPower - Max12 VANo1Power - MaxPrinary Minding TypeSiz / DimensionPC PinSiz / DimensionSiz NameSiz / DimensionSiz Siz MangSiz / DimensionSiz Siz MangYotage - IsolationSiz Siz MangYotage - IsolationSiz Siz MangSiz / DimensionSiz Siz MangYotage - IsolationSiz Siz MangYotage - IsolationSiz Siz MangYotage - IsolationSiz MangYotage - IsolationYotageYotage - Isolation <td>Manufacturer Part Number</td> <td>ST5-28B23</td>	Manufacturer Part Number	ST5-28B23
Power TransformersPackage-SeriesSplit Bobbin Plug-InTypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)Parallel 14V, Series 28VCurrent - Output (Max)Parallel 840mA, Series 420mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max12 VAMounting TypeThrough HoleSize / Dinension47.24mm L x 39.62mm WHeight - Seated (Max)S500VrmsVoltage - Isolation500VrmsWeight0.7 Ib (317.51g)	Manufacturer	Pulse Electronics Power
Package-SeriesSpit Bobin Plug-InTypeLaminated CoreVoltage - Primary15VVoltage - Secondary (Full Load)Parallel 14V, Series 28VCurrent - Output (Max)Parallel 840mA, Series 420mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - MaxI 2 VAMounting TypePrinagh HoleSter JoinensionPrinagh HoleSter JoinensionSize Manuel And Series 420mANouting Stel Compared And Series 420mASeries And Series 420mAPower - MaxSeries And Series 420mANouting TypeSeries And Series 420mAStel JoinensionSeries And Series 420mAStel JoinensionSeries And Series 420mAVoltage - IsolationSeries And Series 420mAWeightSeries And Series 420mA	Category	Transformers
SeriesSplit Bobbin Plug-InTypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)Parallel 14V, Series 28VCurrent - Output (Max)Parallel 840mA, Series 420mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max12 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension47.24mm L x 39.62mm WHeight - Seated (Max)36.58mmVoltage - Isolation500VrmsWeight0.7 Ib (317.51g)		Power Transformers
TypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)Parallel 14V, Series 28VCurrent - Output (Max)Parallel 840mA, Series 420mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max12 VAMounting TypeThrough HoleTermination Style9C PinSize / Dimension47.24mm L x 39.62mm WHeight - Seated (Max)36.58mmVoltage - Isolation2500VrmsWeight0.7 lb (317.51g)	Package	-
YeiInstrumentationVoltage - Primary115VVoltage - Secondary (Full Load)Parallel 14V, Series 28VCurrent - Output (Max)Parallel 840mA, Series 420mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max12 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension47.24mm L x 39.62mm WHeight - Seated (Max)36.58mmVoltage - Isolation0.7 lb (317.51g)	Series	Split Bobbin Plug-In
Voltage - Secondary (Full Load)Parallel 14V, Series 28VCurrent - Output (Max)Parallel 840mA, Series 420mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max12 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension47.24mm L x 39.62mm WHeight - Seated (Max)36.58mmVoltage - Isolation2500VrmsWeight0.7 lb (317.51g)	Туре	Laminated Core
Current - Output (Max)Parallel 840mA, Series 420mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max12 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension47.24mm L x 39.62mm WHeight - Seated (Max)36.58mmVoltage - Isolation2500VrmsWeight0.7 lb (317.51g)	Voltage - Primary	115V
Primary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max12 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension47.24mm L x 39.62mm WHeight - Seated (Max)S6.58mmVoltage - Isolation2500VrmsWeight0.7 lb (317.51g)	Voltage - Secondary (Full Load)	Parallel 14V, Series 28V
Secondary Winding(s)DualCenter TapNoPower - Max12 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension47.24mm L x 39.62mm WHeight - Seated (Max)36.58mmVoltage - Isolation2500VrmsWeight0.7 lb (317.51g)	Current - Output (Max)	Parallel 840mA, Series 420mA
Center TapNoPower - Max12 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension47.24mm L x 39.62mm WHeight - Seated (Max)36.58mmVoltage - Isolation2500VrmsWeight0.7 lb (317.51g)	Primary Winding(s)	Single
Power - Max12 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension47.24mm L x 39.62mm WHeight - Seated (Max)36.58mmVoltage - Isolation2500VrmsWeight0.7 lb (317.51g)	Secondary Winding(s)	Dual
Nounting TypeThrough HoleTermination StylePC PinSize / Dimension47.24mm L x 39.62mm WHeight - Seated (Max)36.58mmVoltage - Isolation2500VrmsWeight0.7 lb (317.51g)	Center Tap	No
Termination StylePC PinSize / Dimension47.24mm L x 39.62mm WHeight - Seated (Max)36.58mmVoltage - Isolation2500VrmsWeight0.7 lb (317.51g)	Power - Max	12 VA
Size / Dimension47.24mm L x 39.62mm WHeight - Seated (Max)36.58mmVoltage - Isolation2500VrmsWeight0.7 lb (317.51g)	Mounting Type	Through Hole
Height - Seated (Max)36.58mmVoltage - Isolation2500VrmsWeight0.7 lb (317.51g)	Termination Style	PC Pin
Voltage - Isolation2500VrmsWeight0.7 lb (317.51g)	Size / Dimension	47.24mm L x 39.62mm W
Weight 0.7 lb (317.51g)	Height - Seated (Max)	36.58mm
	Voltage - Isolation	2500Vrms
Report errors?	Weight	0.7 lb (317.51g)
•		Report errors?

ST5-28B23 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about ST5-28B23, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com