

ST60-24P(50)

ST60-24P(50) Information

		Part Number	ST60-24P(50)	
	JI THE DE	Manufacturer	Hirose Electric Co Ltd	121,259,121
	heisener.com	Category	Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets	167748
		Description	CONN RECEPT 24POS SMD	
		Package	-	in the left
	For Reference Only		For the pricing/inventory/lead time, please contact us	
			Website: https://www.heisener.com	Request a Quote

E-mail: salesdept@heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ST60-24P(50) Specifications

Manufacturer Part NumberST60-24P(50)ManufacturerHirose Electric Co LtdCategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-ScriesSTConnector TypeReceptacleContact TypeReceptacleYuleBoard to Cable/WireNumber of Positions LoadedAllNumber of Positions Loaded0.020° (0.50mm)Number of Rows1Number of RowsSolderYerminationSolderStatening TypeGoldContact Finish - MatingGoldContact Finish - MatingGoldContact Finish - MatingIstek HolderStatening TypeIstek HolderStatening TypeIstek HolderContact Finish - MatingGoldContact Finish Phitckness - MatingIstek HolderStation ColorIstekStation HeightI.18° (3.00mm)Contact Length - Post-Station HeightIti 44 Vo		
CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesSTConnector TypeReceptacleContact TypeNon-GenderedStyleBoard to Cable/WireNumber of Positions24Number of Positions LoadedAllNumber of Rows1Number of Rows0.020" (0.50mm)Number of Rows1Number of RowsSolder Addet Ad	Manufacturer Part Number	ST60-24P(50)
Package-SeriesSTConnector TypeReceptacleContact TypeNon-GenderedStyleBoard to Cable/WireNumber of Positions24Number of Positions LoadedAllPitch - Mating0.020" (0.50mm)Number of Rows1Row Spacing - MatingSolderYater MiningSolderFerminationSolderStatening TypeLatch HolderContact Finish - Mating-SolderSolderFastening TypeGoldContact Finish - Mating-SolderSolderFastening TypeBackSoltari Finish Thickness - Mating-Soltari Finish Thickness - Mating	Manufacturer	Hirose Electric Co Ltd
Package-SeriesSTConnector TypeReceptacleContact TypeNon-GenderedStyleBoard to Cable/WireNumber of Positions24Number of Positions LoadedAllPitch - Mating0.020" (0.50mm)Number of Rows1Row Spacing - Mating-Mounting TypeBoard Edge, Surface Mount, Right AngleTerminationSolderFastening TypeLatch HolderContact Finish - Mating-Soldart Erinish Thickness - Mating-Insulation ColorBlackInsulation Height0.118" (3.00mm)Contact Length - Post-Operating Temperature-30°C ~ 80°C	Category	Connectors, Interconnects
SeriesSTConnector TypeReceptacleContact TypeNon-GenderedStyleBoard to Cable/WireNumber of Positions24Number of Positions LoadedAllPitch - Mating0.020" (0.50mm)Number of Rows1Row Spacing - MatingSolder Cable, Surface Mount, Right AngleNourting TypeSolderFarminationSolderContact Finish - Mating-Contact Finish - Mating-Insulation ColorBackInsulation Height0.118" (3.00mm)Contact Length - Post-Solder-Station Height-Solder-Solder Cable, Post-Solder-Station Type-Solder-Station Type-Solder-Station Type-Solder-Solder-Station Type-Station Type-		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector TypeReceptacleContact TypeNon-GenderedStyleBoard to Cable/WireNumber of Positions24Number of Positions LoadedAllPitch - Mating0.020" (0.50mm)Number of Rows1Row Spacing - Mating-Mounting TypeBoard Edge, Surface Mount, Right AngleTerminationSolderContact Finish - MatingGoldContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.118" (3.00mm)Contact Length - Post-Operating Temperature-Operating Temperature-Solor-<	Package	-
Contact TypeNon-GenderedStyleBoard to Cable/WireNumber of Positions24Number of Positions LoadedAllPitch - Mating0.020" (0.50mm)Number of Rows1Row Spacing - Mating-Mounting TypeBoard Edge, Surface Mount, Right AngleTerminationSolderFastening TypeLatch HolderContact Finish - Mating-Insulation ColorBlackInsulation Height0.118" (3.00mm)Contact Length - Post-Operating Temperature-30°C ~ 80°C	Series	ST
StyleBoard to Cable/WireNumber of Positions24Number of Positions LoadedAllPitch - Mating0.020" (0.50mm)Number of Rows1Row Spacing - Mating-Row Spacing - MatingSolard Edge, Surface Mount, Right AngleTerminationSolderFastening TypeLatch HolderContact Finish - Mating-Rout Spacing - Mating-Insulation ColorBlackInsulation Height0.118" (3.00mm)Contact Fungt- Post-Operating Temperature-30°C ~ 80°C	Connector Type	Receptacle
Number of Positions24Number of Positions LoadedAllPitch - Mating0.020" (0.50mm)Number of Rows1Row Spacing - Mating-Mounting TypeBoard Edge, Surface Mount, Right AngleTerminationSolderFastening TypeLatch HolderContact Finish - Mating-Routation ColorBlackInsulation Height0.118" (3.00mm)Contact Length - Post-Operating Temperature-30°C ~ 80°C	Contact Type	Non-Gendered
Number of Positions LoadedAllPitch - Mating0.020" (0.50mm)Number of Rows1Row Spacing - Mating-Mounting TypeBoard Edge, Surface Mount, Right AngleTerminationSolderFastening TypeLatch HolderContact Finish - Mating-Insulation ColorBlackInsulation Height0.118" (3.00mm)Contact Length - Post-Operating Temperature-30°C~ 80°C	Style	Board to Cable/Wire
Pitch - Mating0.020" (0.50mm)Number of Rows1Row Spacing - Mating-Row Spacing - Mating-Mounting TypeBoard Edge, Surface Mount, Right AngleTerminationSolderFastening TypeLatch HolderContact Finish - MatingGoldContact Finish Thickness - MatingBackInsulation Color0.118" (3.00mm)Contact Length - Post-Operating Temperature-30°C ~ 80°C	Number of Positions	24
Number of Rows1Row Spacing - Mating-Mounting TypeBoard Edge, Surface Mount, Right AngleTerminationSolderFastening TypeLatch HolderContact Finish - MatingGoldContact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.118" (3.00mm)Contact Length - Post-Operating Temperature-30°C ~ 80°C	Number of Positions Loaded	All
Row Spacing - Mating-Row Spacing - MatingBoard Edge, Surface Mount, Right AngleTerminationSolderFastening TypeLatch HolderContact Finish - MatingGoldContact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.118" (3.00mm)Contact Length - Post-Operating Temperature-30°C ~ 80°C	Pitch - Mating	0.020" (0.50mm)
Mounting TypeBoard Edge, Surface Mount, Right AngleTerminationSolderFastening TypeLatch HolderContact Finish - MatingGoldContact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.118" (3.00mm)Contact Length - Post-Operating Temperature-30°C ~ 80°C	Number of Rows	1
TerminationSolderFastening TypeLatch HolderContact Finish - MatingGoldContact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.118" (3.00mm)Contact Length - Post-Operating Temperature-30°C ~ 80°C	Row Spacing - Mating	-
Fastening TypeLatch HolderContact Finish - MatingGoldContact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.118" (3.00mm)Contact Length - Post-Operating Temperature-30°C ~ 80°C	Mounting Type	Board Edge, Surface Mount, Right Angle
Contact Finish - MatingGoldContact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.118" (3.00mm)Contact Length - Post-Operating Temperature-30°C ~ 80°C	Termination	Solder
Contact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.118" (3.00mm)Contact Length - Post-Operating Temperature-30°C ~ 80°C	Fastening Type	Latch Holder
Insulation ColorBlackInsulation Height0.118" (3.00mm)Contact Length - Post-Operating Temperature-30°C ~ 80°C	Contact Finish - Mating	Gold
Insulation Height0.118" (3.00mm)Contact Length - Post-Operating Temperature-30°C ~ 80°C	Contact Finish Thickness - Mating	-
Contact Length - Post-Operating Temperature-30°C ~ 80°C	Insulation Color	Black
Operating Temperature $-30^{\circ}\text{C} \sim 80^{\circ}\text{C}$	Insulation Height	0.118" (3.00mm)
	Contact Length - Post	-
Material Flammability Rating UII 94 V-0	Operating Temperature	-30°C ~ 80°C
	Material Flammability Rating	UL94 V-0

Contact Finish - Post	-
Mated Stacking Heights	-
Ingress Protection	-
Features	Board Guide, Shielded

Report errors?

ST60-24P(50) Guarantees **Quality Guarantees** We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition. **Service Guarantees** SFRVI We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers. ST60-24P(50) Payment Methods WIRE transfer S MoneyGram Alipay VISA DISCOVER PayPal ST60-24P(50) Shipping Methods FedEx. 🚳 COO

If you have any question about ST60-24P(50), please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com