



ST72F325K6T6 Information



For Reference Only

Part Number ST72F325K6T6

Manufacturer STMicroelectronics

Category Integrated Circuits (ICs)
Embedded - Microcontrollers

Description IC MCU 8BIT 32KB FLASH 32LQFP

Package 32-LQFF

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ST72F325K6T6 Specifications

Manufacturer Part Number ST72F325K6T6 Manufacturer STMicroelectronics Category Integrated Circuits (ICs) Package 32-LQFP Series ST7 Core Processor ST7 Core Size 8-Bit Speed 8MHz Connectivity I2C, SCI, SPI Peripherals LVD, POR, PWM, WDT Number of I/O 24 Program Memory Size 32KB (32K x 8) Program Memory Type FLASH EEPROM Size - RAM Size IK x 8 Voltage - Supply (Vcc/Vdd) 3.8 V ~ 5.5 V Data Converters A/D 6x10b Oscillator Type Internal Operating Temperature -40°C ~ 85°C (TA) Mounting Type - Package / Case 32-LQFP Supplier Device Package - Feport errors?		
Category Integrated Circuits (ICs) Embedded - Microcontrollers Package 32-LQFP Series ST7 Core Processor ST7 Core Size 8-Bit Speed 8MHz Connectivity I2C, SCI, SPI Peripherals LVD, POR, PWM, WDT Number of I/O 24 Program Memory Size 32KB (32K x 8) Program Memory Type FLASH EEPROM Size - RAM Size IK x 8 Voltage - Supply (Vcc/Vdd) 3.8 V ~ 5.5 V Data Converters A/D 6x10b Oscillator Type Internal Operating Temperature -40°C ~ 85°C (TA) Mounting Type - Package / Case 32-LQFP Supplier Device Package -	Manufacturer Part Number	ST72F325K6T6
Package 32-LQFP Series ST7 Core Processor ST7 Core Size 8-Bit Speed 8MHz Connectivity 12C, SCI, SPI Peripherals LVD, POR, PWM, WDT Number of I/O 24 Program Memory Size 32KB (32K x 8) Program Memory Type FLASH EEPROM Size - RAM Size 1K x 8 Voltage - Supply (Vcc/Vdd) 3.8 V ~ 5.5 V Data Converters A/D 6x10b Oscillator Type Internal Operating Temperature -40°C ~ 85°C (TA) Mounting Type - Package / Case 32-LQFP Supplier Device Package -	Manufacturer	STMicroelectronics
Package 32-LQFP Series ST7 Core Processor ST7 Core Size 8-Bit Speed 8MHz Connectivity 12C, SCI, SPI Peripherals LVD, POR, PWM, WDT Number of I/O 24 Program Memory Size 32KB (32K x 8) Program Memory Type FLASH EEPROM Size - RAM Size 1K x 8 Voltage - Supply (Vcc/Vdd) 3.8 V ~ 5.5 V Data Converters A/D 6x10b Oscillator Type Internal Operating Temperature -40°C ~ 85°C (TA) Mounting Type - Package / Case 32-LQFP Supplier Device Package -	Category	Integrated Circuits (ICs)
Series ST7 Core Processor ST7 Core Size 8-Bit Speed 8MHz Connectivity I2C, SCI, SPI Peripherals LVD, POR, PWM, WDT Number of I/O 24 Program Memory Size 32KB (32K x 8) Program Memory Type FLASH EEPROM Size - RAM Size 1K x 8 Voltage - Supply (Vcc/Vdd) 3.8 V ~ 5.5 V Data Converters A/D 6x10b Oscillator Type Internal Operating Temperature -40°C ~ 85°C (TA) Mounting Type - Package / Case 32-LQFP Supplier Device Package -		Embedded - Microcontrollers
Core Processor ST7 Core Size 8-Bit Speed 8MHz Connectivity 12C, SCI, SPI Peripherals LVD, POR, PWM, WDT Number of I/O 24 Program Memory Size 32KB (32K x 8) Program Memory Type FLASH EEPROM Size - RAM Size 1K x 8 Voltage - Supply (Vcc/Vdd) 3.8 V ~ 5.5 V Data Converters A/D 6x10b Oscillator Type Internal Operating Temperature -40°C ~ 85°C (TA) Mounting Type - Package / Case 32-LQFP Supplier Device Package -	Package	32-LQFP
Core Size 8-Bit Speed 8MHz Connectivity I2C, SCI, SPI Peripherals LVD, POR, PWM, WDT Number of I/O 24 Program Memory Size 32KB (32K x 8) Program Memory Type FLASH EEPROM Size - RAM Size 1K x 8 Voltage - Supply (Vcc/Vdd) 3.8 V ~ 5.5 V Data Converters A/D 6x10b Oscillator Type Internal Operating Temperature -40°C ~ 85°C (TA) Mounting Type - Package / Case 32-LQFP Supplier Device Package -	Series	ST7
Speed 8MHz Connectivity I2C, SCI, SPI Peripherals LVD, POR, PWM, WDT Number of I/O 24 Program Memory Size 32KB (32K x 8) Program Memory Type FLASH EEPROM Size - RAM Size 1K x 8 Voltage - Supply (Vcc/Vdd) 3.8 V ~ 5.5 V Data Converters A/D 6x10b Oscillator Type Internal Operating Temperature -40°C ~ 85°C (TA) Mounting Type Package / Case 32-LQFP Supplier Device Package -	Core Processor	ST7
ConnectivityI2C, SCI, SPIPeripheralsLVD, POR, PWM, WDTNumber of I/O24Program Memory Size32KB (32K x 8)Program Memory TypeFLASHEEPROM Size-RAM Size1K x 8Voltage - Supply (Vcc/Vdd)3.8 V ~ 5.5 VData ConvertersA/D 6x10bOscillator TypeInternalOperating Temperature-40°C ~ 85°C (TA)Mounting Type-Package / Case32-LQFPSupplier Device Package-	Core Size	8-Bit
Peripherals LVD, POR, PWM, WDT Number of I/O 24 Program Memory Size 32KB (32K x 8) Program Memory Type FLASH EEPROM Size - RAM Size 1K x 8 Voltage - Supply (Vcc/Vdd) 3.8 V ~ 5.5 V Data Converters A/D 6x10b Oscillator Type Internal Operating Temperature 40°C ~ 85°C (TA) Mounting Type - Package / Case Supplier Device Package - LVD, POR, PWM, WDT 24 LVD, POR, PWM, WDT 24 Non 1	Speed	8MHz
Number of I/O Program Memory Size 32KB (32K x 8) Program Memory Type FLASH EEPROM Size - RAM Size 1K x 8 Voltage - Supply (Vcc/Vdd) 3.8 V ~ 5.5 V Data Converters A/D 6x10b Oscillator Type Internal Operating Temperature -40°C ~ 85°C (TA) Mounting Type - Package / Case Supplier Device Package - Supplier Device Package	Connectivity	I2C, SCI, SPI
Program Memory Size Program Memory Type FLASH EEPROM Size RAM Size 1K x 8 Voltage - Supply (Vcc/Vdd) Data Converters A/D 6x10b Oscillator Type Internal Operating Temperature Package / Case Package / Case Supplier Device Package 32KB (32K x 8) FLASH FLASH FLASH FLASH FLASH - Internal - 40°C ~ 85°C (TA) - 3.8 V ~ 5.5 V Internal -40°C ~ 85°C (TA) - 32-LQFP Supplier Device Package	Peripherals	LVD, POR, PWM, WDT
Program Memory Type EEPROM Size - RAM Size 1K x 8 Voltage - Supply (Vcc/Vdd) 3.8 V ~ 5.5 V Data Converters A/D 6x10b Oscillator Type Internal Operating Temperature -40°C ~ 85°C (TA) Mounting Type - Package / Case 32-LQFP Supplier Device Package -	Number of I/O	24
EEPROM Size - IK x 8 Voltage - Supply (Vcc/Vdd) 3.8 V ~ 5.5 V Data Converters A/D 6x10b Oscillator Type Internal Operating Temperature -40°C ~ 85°C (TA) Mounting Type - Package / Case 32-LQFP Supplier Device Package -	Program Memory Size	32KB (32K x 8)
RAM Size Voltage - Supply (Vcc/Vdd) 3.8 V ~ 5.5 V Data Converters A/D 6x10b Oscillator Type Internal Operating Temperature -40°C ~ 85°C (TA) Mounting Type - Package / Case 32-LQFP Supplier Device Package	Program Memory Type	FLASH
Voltage - Supply (Vcc/Vdd)3.8 V ~ 5.5 VData ConvertersA/D 6x10bOscillator TypeInternalOperating Temperature-40°C ~ 85°C (TA)Mounting Type-Package / Case32-LQFPSupplier Device Package-	EEPROM Size	-
Data ConvertersA/D 6x10bOscillator TypeInternalOperating Temperature-40°C ~ 85°C (TA)Mounting Type-Package / Case32-LQFPSupplier Device Package-	RAM Size	1K x 8
Oscillator TypeInternalOperating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ (TA)Mounting Type-Package / Case 32-LQFP Supplier Device Package-	Voltage - Supply (Vcc/Vdd)	3.8 V ~ 5.5 V
Operating Temperature -40°C ~ 85°C (TA) Mounting Type - Package / Case 32-LQFP Supplier Device Package -	Data Converters	A/D 6x10b
Mounting Type - Package / Case 32-LQFP Supplier Device Package -	Oscillator Type	Internal
Package / Case 32-LQFP Supplier Device Package -	Operating Temperature	-40°C ~ 85°C (TA)
Supplier Device Package -	Mounting Type	-
	Package / Case	32-LQFP
Report errors?	Supplier Device Package	-
		Report errors?

ST72F325K6T6 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ST72F325K6T6 Payment Methods





















ST72F325K6T6 Shipping Methods













If you have any question about ST72F325K6T6, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com