

### **STD20 Information**

Part Number STD20
Manufacturer Eaton
Cotecory Circuit

**Category** Circuit Protection

Electrical, Specialty Fuses

**Description** FUSE CRTRDGE 20A 240VAC CYLINDR

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **STD20 Specifications**

Manufacturer Part Number         STD20           Manufacturer         Eaton           Category         Circuit Protection           Package         Cylindrical, Specialty Fuses           Package         Cylindrical, Blade Terminal (Bolt)           Series         STD           Fuse Type         Cartridge           Current Rating         20A           Voltage Rating - AC         240V           Voltage Rating - DC         -           Response Time         -           Applications         Electrical, Industrial           Features         -           Class         -           Approvals         -           Operating Temperature         -           Breaking Capacity @ Rated Voltage         33kA           Mounting Type         Bolt Mount           Package / Case         Cylindrical, Blade Terminal (Bolt)           Size / Dimension         0.476" Dia x 0.945" L (12.10mm x 24.00mm)		
CategoryCircuit ProtectionPackageCylindrical, Specialty FusesSeriesSTDFuse TypeCartridgeCurrent Rating20AVoltage Rating - AC240VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage33kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.476" Dia x 0.945" L (12.10mm x 24.00mm)	Manufacturer Part Number	STD20
PackageElectrical, Specialty FusesSeriesSTDFuse TypeCartridgeCurrent Rating20AVoltage Rating - AC240VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage33kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.476" Dia x 0.945" L (12.10mm x 24.00mm)	Manufacturer	Eaton
PackageCylindrical, Blade Terminal (Bolt)SeriesSTDFuse TypeCartridgeCurrent Rating20AVoltage Rating - AC240VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage33kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.476" Dia x 0.945" L (12.10mm x 24.00mm)	Category	Circuit Protection
SeriesSTDFuse TypeCartridgeCurrent Rating20AVoltage Rating - AC240VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage33kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.476" Dia x 0.945" L (12.10mm x 24.00mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 20A Voltage Rating - AC Voltage Rating - DC Response Time	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating 20A  Voltage Rating - AC 240V  Voltage Rating - DC -  Response Time -  Applications Electrical, Industrial  Features -  Class -  Approvals -  Operating Temperature -  Breaking Capacity @ Rated Voltage 33kA  Mounting Type Bolt Mount  Package / Case Cylindrical, Blade Terminal (Bolt)  Size / Dimension 0.476" Dia x 0.945" L (12.10mm x 24.00mm)	Series	STD
Voltage Rating - AC  Voltage Rating - DC  Response Time  Applications  Electrical, Industrial  Features  - Class  - Approvals  - Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  240V  260  260  260  260  260  260  260  2	Fuse Type	Cartridge
Voltage Rating - DC  Response Time  Applications  Electrical, Industrial  Features  - Class  - Approvals  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Size / Dimension  - Class  Cylindrical, Blade Terminal (Bolt)  Cylindrical, Blade Terminal (Bolt)  Cylindrical, Blade Terminal (Bolt)  Cylindrical, Blade Terminal (Bolt)	Current Rating	20A
Response Time Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension - Overating Temperature Operating Tem	Voltage Rating - AC	240V
Applications Electrical, Industrial  Features - Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 33kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.476" Dia x 0.945" L (12.10mm x 24.00mm)	Voltage Rating - DC	-
Features - Class - Approvals - Coperating Temperature - Seraking Capacity @ Rated Voltage 33kA Bolt Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.476" Dia x 0.945" L (12.10mm x 24.00mm)	Response Time	-
Class - Approvals - Coperating Temperature - Streaking Capacity @ Rated Voltage 33kA  Mounting Type Bolt Mount  Package / Case Cylindrical, Blade Terminal (Bolt)  Size / Dimension 0.476" Dia x 0.945" L (12.10mm x 24.00mm)	Applications	Electrical, Industrial
Approvals Operating Temperature	Features	-
Operating Temperature  Breaking Capacity @ Rated Voltage  33kA  Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  0.476" Dia x 0.945" L (12.10mm x 24.00mm)	Class	-
Breaking Capacity @ Rated Voltage 33kA  Mounting Type Bolt Mount  Package / Case Cylindrical, Blade Terminal (Bolt)  Size / Dimension 0.476" Dia x 0.945" L (12.10mm x 24.00mm)	Approvals	-
Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  0.476" Dia x 0.945" L (12.10mm x 24.00mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.476" Dia x 0.945" L (12.10mm x 24.00mm)	Breaking Capacity @ Rated Voltage	33kA
Size / Dimension 0.476" Dia x 0.945" L (12.10mm x 24.00mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
	Size / Dimension	0.476" Dia x 0.945" L (12.10mm x 24.00mm)
Report errors?		Report errors?

### **STD20 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **STD20 Payment Methods**





















## **STD20 Shipping Methods**













If you have any question about STD20, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com