

# STD30PF03L-1

### **STD30PF03L-1 Information**

| M<br>C<br>www.l.vrsener.com<br>D | lanufacturer<br>ategory<br>escription<br>ackage | STD30PF03L-1<br>STMicroelectronics<br>Discrete Semiconductor Products<br>Transistors - FETs, MOSFETs - Single<br>MOSFET P-CH 30V 24A IPAK<br>TO-251-3 Short Leads, IPak, TO-251AA<br>For the pricing/inventory/lead time, please contact |                 |
|----------------------------------|---|--|-----------------|
| For Reference Only               |   | us<br>Website: https://www.heisener.com<br>E-mail: salesdept@heisener.com  | Request a Quote |

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# **STD30PF03L-1 Specifications**

| Manufacturer Part Number               | STD30PF03L-1                         |
|--|--------------------------------------|
| Manufacturer                           | STMicroelectronics                   |
| Category                               | Discrete Semiconductor Products      |
|  | Transistors - FETs, MOSFETs - Single |
| Package                                | TO-251-3 Short Leads, IPak, TO-251AA |
| Series                                 | STripFET? II                         |
| FET Type                               | P-Channel                            |
| Technology                             | MOSFET (Metal Oxide)                 |
| Drain to Source Voltage (Vdss)         | 30V                                  |
| Current - Continuous Drain (Id) @ 25°C | 24A (Tc)                             |
| Drive Voltage (Max Rds On, Min Rds On) | 5V, 10V                              |
| Vgs(th) (Max) @ Id                     | 1V @ 250µA                           |
| Gate Charge (Qg) (Max) @ Vgs           | 28nC @ 5V                            |
| Input Capacitance (Ciss) (Max) @ Vds   | 1670pF @ 25V                         |
| Vgs (Max)                              | ±16V                                 |
| FET Feature                            | -                                    |
| Power Dissipation (Max)                | 70W (Tc)                             |
| Rds On (Max) @ Id, Vgs                 | 28 mOhm @ 12A, 10V                   |
| Operating Temperature                  | 175°C (TJ)                           |
| Mounting Type                          | Through Hole                         |
| Supplier Device Package                | I-Pak                                |
| Package / Case                         | TO-251-3 Short Leads, IPak, TO-251AA |
|  | Report errors?                       |

#### STD30PF03L-1 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE EUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### STD30PF03L-1 Payment Methods



## STD30PF03L-1 Shipping Methods



If you have any question about STD30PF03L-1, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com