

STD4 Information

www.helsener.een

For Reference Only

Part Number STD4
Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CARTRIDGE 4A 240VAC CYLINDR

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









STD4 Specifications

Manufacturer Part NumberSTD4ManufacturerEatonCategoryCircuit Protection Electrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesSTDFuse TypeCartridgeCurrent Rating4AVoltage Rating - AC240VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage33kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.476" Dia x 0.945" L (12.10mm x 24.00mm)Report errors?		
Category Circuit Protection Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series STD Fuse Type Cartridge Current Rating 4A Voltage Rating - AC Voltage Rating - DC Response Time - Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Breaking Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Circuit Protection Electrical, Specialty Fuses Electrical, Industrial Features - Class -	Manufacturer Part Number	STD4
Backage Cylindrical, Blade Terminal (Bolt) Series STD Fuse Type Cartridge Current Rating 4A Voltage Rating - AC 240V Voltage Rating - DC - Response Time - Applications Electrical, Industrial Features - Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 33kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension STD STD Cartridge Current Rating (Cylindrical, Blade Terminal (Bolt) Size / Dimension (STD) STD Cartridge Car	Manufacturer	Eaton
PackageCylindrical, Blade Terminal (Bolt)SeriesSTDFuse TypeCartridgeCurrent Rating4AVoltage Rating - AC240VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage33kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.476" Dia x 0.945" L (12.10mm x 24.00mm)	Category	Circuit Protection
Series STD Fuse Type Cartridge Current Rating 4A Voltage Rating - AC 240V Voltage Rating - DC - Response Time - Applications Electrical, Industrial Features - Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 33kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension STD 240V Cartridge Cartridge Cartridge Cartridge Cartridge Cartridge Cartridge AA AB AB AB Cartridge Cartridge Cartridge Cartridge Cartridge Cartridge Cartridge		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating4AVoltage Rating - AC240VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage33kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.476" Dia x 0.945" L (12.10mm x 24.00mm)	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating Voltage Rating - AC 240V Voltage Rating - DC Response Time - Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 4A 4A 4A 4A 4A 4A 4A 4A 4B 4B	Series	STD
Voltage Rating - AC Voltage Rating - DC Response Time Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Bolt Mount Package / Case Size / Dimension 240V 240V 240V 240V 240V - 840V 240V - 840V 640V 640	Fuse Type	Cartridge
Voltage Rating - DC Response Time Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension - 0.476" Dia x 0.945" L (12.10mm x 24.00mm)	Current Rating	4A
Response Time Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension - Overating Temperature Bolt Mount Overating Temperature Bolt Mount Bolt Mount Overating Temperature Bolt Mount Overating Temperature Overating Tem	Voltage Rating - AC	240V
Applications Electrical, Industrial Features - Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 33kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.476" Dia x 0.945" L (12.10mm x 24.00mm)	Voltage Rating - DC	-
Features - Class - Class - Component of the Component of	Response Time	-
Class - Approvals - Coperating Temperature - Seraking Capacity @ Rated Voltage 33kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.476" Dia x 0.945" L (12.10mm x 24.00mm)	Applications	Electrical, Industrial
Approvals Operating Temperature Breaking Capacity @ Rated Voltage Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension O.476" Dia x 0.945" L (12.10mm x 24.00mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 33kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.476" Dia x 0.945" L (12.10mm x 24.00mm)	Class	-
Breaking Capacity @ Rated Voltage 33kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.476" Dia x 0.945" L (12.10mm x 24.00mm)	Approvals	-
Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.476" Dia x 0.945" L (12.10mm x 24.00mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.476" Dia x 0.945" L (12.10mm x 24.00mm)	Breaking Capacity @ Rated Voltage	33kA
Size / Dimension 0.476" Dia x 0.945" L (12.10mm x 24.00mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	0.476" Dia x 0.945" L (12.10mm x 24.00mm)
		Report errors?

STD4 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

STD4 Payment Methods



















STD4 Shipping Methods













If you have any question about STD4, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com