

STD6 Information

www.heisener.eem

For Reference Only

Part Number STD6 Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CARTRIDGE 6A 240VAC CYLINDR

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









STD6 Specifications

Manufacturer Part Number STD6 Manufacturer Eaton Category Circuit Protection Package Cylindrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series STD Fuse Type Cartridge Current Rating 6A Voltage Rating - AC 240V Voltage Rating - DC - Response Time - Applications Electrical, Industrial Features - Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 33kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.476" Dia x 0.945" L (12.10mm x 24.00mm)		
Category Circuit Protection Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series STD Fuse Type Cartridge Current Rating 6A Voltage Rating - AC Voltage Rating - DC Response Time - Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Breaking Capacity @ Rated Voltage Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Circuit Protection Electrical, Specialty Fuses Electrical, Industrial Features - Class - Class - Class - Class - Class - Cylindrical, Blade Terminal (Bolt) Size / Dimension O.476" Dia x 0.945" L (12.10mm x 24.00mm)	Manufacturer Part Number	STD6
Backage Cylindrical, Blade Terminal (Bolt) Series STD Fuse Type Cartridge Current Rating 6A Voltage Rating - AC 240V Voltage Rating - DC - Response Time - Applications Electrical, Industrial Features - Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 33kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.476" Dia x 0.945" L (12.10mm x 24.00mm)	Manufacturer	Eaton
PackageCylindrical, Blade Terminal (Bolt)SeriesSTDFuse TypeCartridgeCurrent Rating6AVoltage Rating - AC240VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage33kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.476" Dia x 0.945" L (12.10mm x 24.00mm)	Category	Circuit Protection
Series STD Fuse Type Cartridge Current Rating 6A Voltage Rating - AC 240V Voltage Rating - DC - Response Time - Applications Electrical, Industrial Features - Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 33kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension SAA		Electrical, Specialty Fuses
Fuse Type Current Rating 6A Voltage Rating - AC Voltage Rating - DC Response Time - Applications Electrical, Industrial Features - Class - Approvals - Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Cartridge Cartridge 6A Cartridge 6A A Cartridge 6A Cartridge 6A Call Call Call Call Call Call Call Call Cartridge 6A An An An An Call Call Call Call Call Cartridge Call Ca	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating Voltage Rating - AC 240V Voltage Rating - DC Response Time - Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 6A 6A 6A 6A 6A 6A 6A 6A 6A 6	Series	STD
Voltage Rating - AC Voltage Rating - DC Response Time Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 240V 240V 240V 240V 240V - 840V 240V 2400 240V 240	Fuse Type	Cartridge
Voltage Rating - DC Response Time	Current Rating	6A
Response Time Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension - Class - Class Class Cylindrical, Blade Terminal (Bolt) Control of the state of the stat	Voltage Rating - AC	240V
Applications Electrical, Industrial Features - Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 33kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.476" Dia x 0.945" L (12.10mm x 24.00mm)	Voltage Rating - DC	-
Features - Class - Approvals - Coperating Temperature - Seraking Capacity @ Rated Voltage 33kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.476" Dia x 0.945" L (12.10mm x 24.00mm)	Response Time	-
Class - Approvals - Coperating Temperature - Streaking Capacity @ Rated Voltage 33kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.476" Dia x 0.945" L (12.10mm x 24.00mm)	Applications	Electrical, Industrial
Approvals Operating Temperature Breaking Capacity @ Rated Voltage Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension O.476" Dia x 0.945" L (12.10mm x 24.00mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 33kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.476" Dia x 0.945" L (12.10mm x 24.00mm)	Class	-
Breaking Capacity @ Rated Voltage 33kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.476" Dia x 0.945" L (12.10mm x 24.00mm)	Approvals	-
Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.476" Dia x 0.945" L (12.10mm x 24.00mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.476" Dia x 0.945" L (12.10mm x 24.00mm)	Breaking Capacity @ Rated Voltage	33kA
Size / Dimension 0.476" Dia x 0.945" L (12.10mm x 24.00mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	0.476" Dia x 0.945" L (12.10mm x 24.00mm)
		Report errors?

STD6 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

STD6 Payment Methods





















STD6 Shipping Methods













If you have any question about STD6, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com